GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6/DFS/MS/2011/ GH/3545

Dated 15 12 11

FIRE SAFETY CERTIFICATE

Certified that the Mirja Guest House, located at 776, Motor Market, Jama Masjid Delhi06 comprised of Ground + four upper floors having 08 Guest rooms (Ground floor is used for
commercial purpose, First floor has 06 rooms, Second floor has 06 guest rooms, third floor has
02 guest rooms, Fourth floor is used for owner residence and terrace floor having open area
Water tanks) was granted NOC by this department vide letter No F 6 / DFS / MS / GH / 2009 /
223 dated 27.01.2009. The premise was re-inspected by the officer concerned of this department
on 30.11.2011 in the presence of Mr. S.R. Mirza found that the said Guest House have deemed
complied with fire prevention and fire safety requirements in accordance with Rule 33 of the
Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I
with effect from [15.1] [1.1.] for a period of three years in accordance with rule 36 unless
renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the
conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ...\. . \. . \. . \. . \. at New Delhi

DIRECTOR DELHI FIRE SERVICE

Copy to: -

- 1. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.
- 2. The Owner, Mirja Guest House, located at 776, Motor Market, Jama Masjid Delhi-06

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

Building covered under special great. 2. No.

old Cose

INSPECTION REPORT

	1. Name & address of the building Mix 2. Type of Occupancy	39 Givest House	776, Motor market	Jamamasi	
2	2. Type of Occupancy Gr	oup-A-1, Resi	dencial.	- Delhi-e	
2		: New Case/ Renewal			
Z	4. Details of previous NOC : Let				
5					
. (5. Date of inspection				
7	. Name of the Inspecting Officers: ADO - StlyAM 1AL				
8					
	from the building side :				
9	P. Year of Construction 196	60, (lobeds in 8	Guest Rooms at	st Trad Tord on	
1	0. Applicant's letter No. :	Care Care Care Care Care Care Care Care		THE HOD	
S.	Minimum Standards on fire	Girculars Gi.H.	Provided at site	Remarks	
No.	prevention and fire safety U/R 33	Requirement		MR/NMR	
1	Access to building				
	 Road width 	N/F)	9 mbs.	MR	
	• Gate width	NIA		MN	
	Width of internal road	NIA		ml	
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	one	one	ML	
	 Upper Floors 	one	one	mR	
8	 Basements 	N/0-	NiL	NM	
	b. Width of staircases	80 cm.	80 cms	m/	
	 Upper Floors 	AD CM	80 cms	m e_	
	 Basements 	NM	NiL		
	c. Protection of exits		/ 5, C		
	 Fire check door 	NIA	NIA		
	 Pressurization 	NIA			
	e. No. of continuous staircases to terrac	e pnl	one	ml	
	g. Width of Corridor	N/A		,	
	h. Door Size	NIN			

	,		NIA	ور وین
	Compartmentation.	• • • • • • • • • • • • • • • • • • • •		
	• Fire check door	NA		
	 Sealing of electrical shafts 	N/A)		
	 Fire Rating of shaft door 	MA		
	 Water Curtain 	NA		
	• Fire Dampers	NA		
ļ.	Smoke Management System.		NIA	
	Basements	30 a/c per hour	, , , , ,	
	 Upper floors 	12 a/c per hour		
	S.F.F.			
5	Fire Extinguishers		C	m a
	Total numbers		6 W.CO2 = 3	A
	Types		AB 65kg = 3	MR
	 IS marking 	ISI marked	yes.	MR
6	First-Aid Hose Reels.	* 00		NL
	Total numbers on each floor	-O'ne	one	MI
	 Length of hose reel hose 	30 m	yes	1 1
	Nozzle diameter	5 mm	yes	MIL
7	Automatic fire detection and alarmi	ng system.	NIA	
	 Type of detectors 	N/A	,	
	 Location of Main Panel 	N/A		
	Location of Repeater Panel	NIA		8
	Alternate source of power	NA		
	Hooters' Location	NA		
8	MOEFA	N/A	NIA Provided.	
9	Public Address System.	N/It	frovided.	
10	Automatic Sprinkler System.		MA	
	Basement	NA		

Upper Floor Sprinkler above false ceiling N/B					
11 Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box 12 Vard Hydrants. • Total number of hydrants • Hose Box 13 Pumping Arrangements. • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump out put > Standby Pump lead > Auto Starting/ Manual stopping > Pump flouse Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump 14 Captive Water Storage for fire fighting. • Underground tank capacity N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A			N/D		
Size of riser/down-comer Number of hydrants per floor Hose Box VAA Vard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey Pump out put Standby Pump pump Head Standby Pump Head Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Head of the pump Head of the pump Auto Starting of pump Auto Starting of pump Head of the pump Auto Starting of pump Underground tank capacity NIR		• Sprinkler above false ceiling	NA	,	
Number of hydrants per floor Hose Box 12 Yard Hydrants. Total number of hydrants Hose Box N/A Hose Box N/A N/A N/A N/A N/A Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump N/A Number of main pumps Jockey Pump out put Jockey Pump out put Standby Pump Head Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 14 Captive Water Storage for fire fighting. Underground tank capacity N/A N/A N/A N/A N/A N/A N/A N/	1	1 Internal Hydrants	*	A (/ 1	
Total number of hydrants Hose Box Hose Box Image: Hose		 Number of hydrants per floor 	N/A N/A	N/A	
Hose Box Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump	12	2 Yard Hydrants.	,		
• Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting.			NA	NIA	
• Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Auto Starting of pump Captive Water Storage for fire fighting.	13	Pumping Arrangements.	10/		
> Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump 14 Captive Water Storage for fire fighting. Underground tank capacity N/A		 Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head 	N/A	NIR	
Head of the pump Power Supply Auto Starting of pump 14 Captive Water Storage for fire fighting. Underground tank capacity N/R		 Standby Pump Head Auto Starting/ Manual stopping Pump House Access 	N/A N/A N/A		
14 Captive Water Storage for fire fighting. • Underground tank capacity **NIR**		Head of the pumpPower Supply		225 Hs Invinit	
 Underground tank capacity 	14	Captive Water Storage for fire fighting	·		
		Underground tank capacity		NIR	

	Fire service inlet			
	> Access to tank			
	Overhead Tank capacity		2500 Lts	
15	Exit Signage.	Staircase.	Provided	
16	Provision of Lifts.		MA	
	Pressurization of Lift Shaft		77)6	
	Pressurization of Lift lobby			>
	Communication In lift Car			
	Fireman's Grounding Switch			
	Lift Signage			
	Thi signage			
17	Standby power supply		NIA	
18	Refuge Area.			
	> Total Area		MA	
	> Location			
19	Fire Control Room			
	Detector System Panel		14/74	
	• Flow Switch Panel			
	PA System Panel			
	Batter backup			
	Building Floor Plans			
20	Special Fire Protection Systems for			8
	Protection of special Risks, if any:		NIL	
			9	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

5

Signature of the Inspecting Officer

Name

Designation

D. 0 - (c)

Signature of the Inspecting Officer

Name SHYAM LAL

Designation Assitt. Divn. officer.