GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI-110001

No. F6/DFS/MS/9H/2012/109

Dated: 12/01/12

FIRE SAFETY CERTIFICATE

Certified that the Hem Kunt Guest House located at 2/32, Kalkaji Ext., New Delhi. comprised of Ground + 2 Upper Floors (20 guest rooms) was granted NOC by this department vide letter No. F6/DFS/MS/GH/2008/3496 dated 19/12/08 The premises was re-inspected by the officer concerned of this department on 18/12/11 in the presence of Mr. B.S.Kalra and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Lodging or Rooming House Residential Group-A with effect from 22/12/11 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire subject to conditions printed overleaf.

Issued 12/01/12---at New Delhi by.

Chief Fire Officer For Director Delhi Fire Service

0) c

Copy to:- (1) The Addl. Commissioner of Police, (Lic.), First Floor, PS Defence Colony, New Delhi

(2) Hem Kunt Guest House, 2/32, Kalkaji Ext., New Delhi Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

110

INSPECTION REPORT

- 1. Name & address of the building:- Hem Kunt Guest House,2/32, Kalkaji Ext., New Delhi.
- 2. Type of occupancy:- Lodging or Rooming Houses Residential Group A.
- 3 Type of case:- Renewal
- 4 Details of previous NOC:- F6/DFS/MS/GH/2008/3496 dated 19/12/08
- 5 Fire safety directives No.- No
- 6. Date of inspection:-
- 18-12-1
- 7 Name of the inspecting officer:- A.D.O. S.S. Kaushik
- 8 Name & designation of officer
 - From the building side:- Mr. B.S.Kalra.
- 9 Year of construction:- 1995

10 Applicant's letter No.1209 dated 16/11/11 Ground + 2 Upper Floors

10 A	10 Applicant's letter No.1209 dated 16/11/11 Ground + 2 Upper Floors					
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR		
1.	Access to Building	-				
	1) Road width	Required	Provided	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrange	ment of Exits				
	A. Number of staircases	Required	Provided	MR		
	1. Upper floors	Required	2 Nos.	MR		
	2. Basement	N/A	N/A	N/A		
	B. Width of staircase	N/A	N/A	N/A		
	1. Upper floors	N/A	95 cms.each	N/A		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits	N/A	N/A	N/A		
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase	Required	one	MR		
	to terrace	1 1	0110	1111		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	N/A	N/A	N/A		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
	Smoke Management System					
	1) Basements	30 a/c per hour	N/A	N/A		
	2) Upper floors	12 a/c per hour	Provided	MR		
•	Fire Extinguishers					
	1) Total numbers		10 Nos.	MR		
	2) Types		Co2,W.Co2 &	MR		
	1	ISI Marked	ABC			
	3) ISI marking		Yes	MR		
6.	First-Aid Hose Reel					
	1) Total number of each floor	Required	One at each floor	MR		
	2) Length of hose reel hose	30 m	Yes	MR		
	3) Nozzle diameter	5 mm	Yes	MR		
•	Automatic Fire Detection & Alarming	System				

	Exit Signage. Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch e) Lift signage Stand by Power Supply Refuge Area Total area location	Required N/A	Provided N/A N/A N/A N/A N/A N/A N/A N/A N/A Provided N/A N/A N/A	MR N/A	
16. 17.	Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch e) Lift signage Stand by Power Supply	N/A N/A N/A N/A N/A N/A N/A Required	N/A N/A N/A N/A N/A N/A Provided	N/A N/A N/A N/A N/A N/A N/A MR	
	Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch e) Lift signage	N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A	
	Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch	N/A N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A N/A	
6.	Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car	N/A N/A N/A N/A	N/A N/A N/A	N/A N/A N/A N/A	
6.	Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car	N/A N/A N/A N/A	N/A N/A N/A	N/A N/A N/A	
6.	Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby	N/A N/A N/A	N/A N/A N/A	N/A N/A	
6.	Provision of Lifts. a) Pressurization of lift shaft	N/A N/A	N/A	N/A	
6.	Provision of Lifts.	N/A			
6		-			
	Fyit Signage	D 1	D	3.50	
5.	d) Over head tank capacity	Required	2,500 Ltr.	MR	
		N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	a) Draw-off connection	N/A	N/A	MR	
	Under ground tank capacity		NT/A	MD	
14.	d) Auto starting of pump N/A N/A N/A Captive Water Storage for Fire Fighting				
	d) Auto starting of pump	N/A	N/A	N/A	
	c) Power supply	N/A Required,	30mhin A	MRY	
	b) Head of pump	Reguired		MRL	
	a) Discharge of pump	Required L		MRE	
	2) Terrace level		N/A Previded	N/A	
	h) Auto starting/Manual stopping	N/A N/A	N/A	N/A	
	g) Stand by pump head	N/A N/A	N/A	N/A	
	f) Stand by pump output	N/A N/A	N/A	N/A	
	e) Jockey pump head	N/A N/A	N/A	N/A	
	d) Jockey pump out put	N/A N/A		N/A	
	c) Number of main pump	N/A	N/A		
	b) Head of main pump	NAL		NA	
	a) Discharge of main pump	NAL	NA -		
	1) Ground level	MAL	NA	NA	
13.	Pumping Arrangement				
	1 /	14/11	14/71	11/71	
	2) Hose box	N/A	N/A	N/A	
	1) Total number of hydrants	N/A	N/A	N/A	
12.	Yard Hydrants	1	- 1/4 4	11/11	
	3) Hose box	N/A	N/A	N/A	
	2) Number of hydrants per floor	N/A	N/A	N/A	
	1) Size of riser/down-comer	N/A	N/A	N/A	
11.	Internal Hydrants				
	3) Sprinkler above false ceiling	N/A	N/A	N/A	
	2) Upper floors	N/A	N/A	N/A	
	1) Basement	N/A	N/A	N/A	
10.	Automatic Sprinkler System		110,1000	1744	
9.	Public Address System	Required	Provided	MR	
8.	MOEFA	Required	Provided	MR	
	5) Hooter's Location	N/A	N/A	N/A	
	4) Alternate source of power	N/A	N/A	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	Type of detectors Location of main panel	N/A N/A	N/A N/A	N/A N/A	

19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection system provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010-----

Accordingly DFA is put up please

Signature of the inspecting officer

Signature of the inspecting officer

Name

Name S.S. Kawstuk

Designation Asst Div. Officer

Designation