## FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. 66/265/015/2012/580

Dated: 21/62/2012

## **FIRE SAFETY CERTIFICATE**

Certified that the Ess Cee See & Assoiated (I) Pvt. Ltd (TDI Paragon) Cinema, Plot no.2, Shivaji Place, Rajouri Garden, New Delhi-110027., comprised of Lower basement & Upper basement & ground+three upper floors was granted **NOC** by this department vide letter No.: F6/DFS/MS/Cinema/2006/2893 dated 28/09/2006. The premises was re-inspected by the officers concerned of this department on 09.02.2012. in the presence of Shri B. R. Puri (Manager) of the Mall and found that the building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010. Hence the NOC is renewed and premises is fit for Class-F (Mercantile) occupancy with effect from 2//02/12 for a period of three years subject to conditions printed below.

Issued on.  $\frac{21}{\log 2}$   $\frac{12}{\log 2}$  at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy to: Shri B. R. Puri (Manager) Ess Cee See & Assoiated (I) Pvt. Ltd (TDI Paragon) Cinema, Plot no.2, Shivaji Place, Rajouri Garden, New Delhi-110027.

Note:- For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working g conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on <a href="www.dfs">www.dfs</a>. delhigovt. nic.in

powert - (self.)

May Kindly peruse letter no. nil dated 19-01-2012 received from Shri B. R. for Puri Ess Cee Cee & Associates (India) Pvt. Ltd. regarding renewal of NOC in r/o Paragon Mall located at Plot no.2, Shivaji Place, Rajouri Garden, New Delhi-110027. premises was inspected by the undersigned & the fire safety arrangements are put up on the prescribed Performa.

1. Name &address of the building : Ess Cee See & Assoiated (I) Pvt. Ltd (TDI Paragon) Cinema,

Plot no.2, Shivaji Place, Rajouri Garden, New Delhi-110027.

2. Type of Occupancy : Class –F (Mercantile)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/Cinema/2006/2893 dated 28/09/2006

5. Fire Safety directives letter No. : F6/DFS/MS/BP/2004/2529 dated 21/10/2004

6. Date of inspection : 09.02.2012

7. Name of the Inspecting Officers : Divisional Officer Sunil Chowdhary

8. Name and designation of officers

From the building side : Shri B. R. Puri (Manager)

9. Year of Construction : 2004-2005

10. Applicant's letter No. : nil

## **INSPECTION REPORT**

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR		
1.	Access to building					
5	Road width	12 mtrs	24 mtr	M/R		
	Gate width	4.5 mtr	5 mtr	M/R		
	Width of internal road	6 mtr	P	M/R		
2.	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	09	09	M.R		
	• Upper Floors	07	07	M.R		
	• Basement	09	09	M.R		

	b. Width of staircases					
	Upper Floors	1.5 mtr	Provided	M.R.		
	Basement	2 mtr, 1.65 mtr & 1.5 mtr	Provided	M.R.		
	c. Protection of exits	1.5 mu				
	Fire check door	Required	Provided	M.R		
	Pressurization	Required	Provided	M.R		
	d. No. of continuous staircases to terrace					
	e. Width of Corridor	Required	Provided	M.R		
	f. Door size	1.5 mtr	Provided	M.R.		
3.	Compartmentation.					
	Fire check door	Required	Provided	M.R		
	Sealing of electrical shafts	Required	Provided	M.R		
	Fire Rating of shaft door	Required	Provided	M.R		
	Water Curtain	Required	Provided	M.R		
	Fire Dampers	Required	Provided	M.R		
4. ~	Smoke Management System.					
	Basements	Required	Provided	M.R		
	Upper floors	Required	Provided	M.R		
5.	Fire Extinguishers					
	Total numbers	50	Provided	M.R		
	• Types	ABC & CO <sub>2</sub>	provided	M.R		

<u>k</u>		T			
	IS marking	ISI marks	provided	M.R	
6.	First-Aid Hose Rees.				
	Total numbers on each floor	4	4	M.R	
	Length of hose reel hose	30 m	provided	M.R	
	Nozzle diameter	5 mm	provided	M.R	
7.	Automatic fire detection and alarming system.				
	Type of detectors	Smoke & Heat type	Provided	M.R	
	Location of Main Panel	Ground floor	Provided	M.R	
	Location of Repeater Panel	Ground floor	Provided	M.R	
	Alternate source of power	Required	Provided	M.R	
	Hooter's Location	Required	Provided	M.R	
18.	MOEFA	Required	Provided	M.R	
9.	Public Address System.	Required	Provided	M.R	
10.	Automatic Sprinkler system			ž.	
	Basement	Required	Provided	M.R.	
	Upper Floor	Required	Provided	M.R	
	Sprinkler above false ceiling	Required	Provided	M.R	
11.	Internal Hydrants				
	Size of riser/down-comer	150 mm	provided	M.R	
	Number of hydrants per floor	4	Provided	M.R	

	Hose Box	4	Provided	M.R	
12.	Yard Hydrants.			u u	
	Total number of hydrants	6	Provided	M.R	
ω.	Hose Box	6	Provided	M.R	
13.	Pumping Arrangements.				
	<b>Ground Level</b>				
	Discharge of main pump	4500 LPM	Provided	M.R	
	➤ Head of Main pump	60 mtr	Provided	M.R	
	Number of main pumps	3 Pumps 1. Electrical pump =Wet riser 1. Electrical pump =Sprinkler 1. Diesel driven pump=Stand by	Provided	M.R	
	> Jockey Pump out put	Two 180 LPM each	Provided	M.R	
	> Jockey pump head	60 mtr	Provided	M.R	
	> Standby pump out put	4500 LPM	Provided	M.R	
	> Standby pump Head	60 mtr	Provided	M.R	
	> Auto Starting/Manual stopping	Required	Provided	M.R	
	> Pump Hose Access	Required	Provided	M.R	
	Terrace level				
	<ul><li>Discharge of pump</li></ul>	450 LPM	Provided	M.R	
	➤ Head of the pump	40 mtr.	Provided	M.R	
	> Power supply	Provided	Provided	M.R	

K					
	➤ Auto Starting of pump	Required	Provided	M.R	
14.	Captive Water Storage for fire fighting.				
	Underground tank capacity	3 lakh	Provided	M.R	
	Draw -off connection	Required	Provided	M.R	
	➤ Fire service inlet	Required	Provided	M.R	
	> Access to tank	Required	Provided	M.R	
	<ul><li>Overhead Tank Capacity</li></ul>	30, 000 ltr	Provided	M.R	
15	Exit Signage.	Required	Provided	M.R	
16.	Provision of Lifts				
	Pressurization of Lift Shaft	Required	Provided	M.R	
	Pressurization of Lift lobby	Required	Provided	M.R	
	Communication In lift Car	Required	Provided	M.R	
	Fireman's Grounding     Switch	Required	Provided	M.R	
	Lift Signage	Required	Provided	M.R	
17.	Standby power supply	Required	450 KVA	M.R /	
18.	Refuge Area			2	
	> Total Area	N.R.	N.R.	Not applicable	
2	> Location	N.R.	N.R.	Not applicable	
19.	Fire Control Room				

				H.
	<ul><li>Detector System Panel</li></ul>	Required	Provided	M.R
	> Flow Switch Panel	Required	Provided	M.R
	> PA system Panel	Required	Provided	M.R
	> Batter backup	Required	Provided	M.R
	Building Floor plans	Required	Provided	M.R
20.	Special Fire Protection Systems for	N.R.	N.R.	M.R
	Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the inspection Officer

Signature of the Inspection Officer

Name SUNIL CORWONARY

Name

Designation D. O.

Designation