GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT LANE NEW DELHI-110 001.

No. F6/DAS/ons/school/2012/466

Dated: 10/02/12

FIRE SAFETY CERTIFICATE

Certified that the GOVT. BOYS SENIOR SECONDARY SCHOOL located at BADLI, Delhi-110 042, comprised of three blocks of ground plus one upper floor only and less than 9 meters in height, have complied with the fire prevention and fire safety requirement in accordance with Director of Edcuation circular dated 01.03.2001 and verified by the officer concerned of fire service on 19.01.2012 in the presence of Dr. Chandra Singh, Principal and that the building/ premises is fit for occupancy class Educational class with effect from 10/02/12 for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on _______ at New Delhi by

Delhi Fire Service

Dr. Chandra Singh, Principal, GOVT. BOYS SENIOR SECONDARY SCHOOL, BADLI, Delhi-110 042.

Copy to:

The Director, Dte. Of Education. Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

INSPECTION REPORT

1.	Name &address of the building	GOVT. BOYS SR. SEC. SCHOOL, BADLI
2.	Type of Occupancy	: ScHool (Gene)
3.	Type of Case	· New Case
4.	Details of previous NOC	: _ N.A.
5.	Fire Safety directives letter No.	: F.16 Estate cc Fin Safety 2011 3298-3398 D1.1.3.20
6.	Date of inspection	: 19.01.2012
7.	Name of the Inspecting Officers	: SHRI RAJMAL KHOKHAR
8.	Name and designation of officers	
	From the building side	: N.A.
9.	Year of Construction	:1993.
10.	Applicant's letter No.	GBSSS Badlil 2011-11 Dated ATIN 11

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR
1.	Access to building		-	THETTIME
	Road width	Accessible	Accessible	mr
	Gate width	- u	-u-	-ie -
	 Width of internal road 	-	•	
2.	Number, Width, Type & Arrange	ment of Exits		1
	a. Number of staircases	Forus	Four	MR.
«	• Upper Floors	-h/ -	-k-	-n _
	• Basement	~	-	~
4	b. Width of staircases	150 Clus	160 Cms	mR
	Upper Floors	-u-	-u -	- KC
	• Basement			_
	c. Protection of exits		-	
	Fire check door	- Tong	5 7	
	Pressurization			
	d. No. of continuous staircases to terrace	Form	For	m R
	e. Width of Corridor	12 Melins	21 Meles	-u -
	f. Door size	Double Down	Souble Dorr	m R

	Compartmentation.			
	Fire check door	-	V-	-
	Sealing of electrical shafts	-	,	
	Fire Rating of shaft door		-	
	Water Curtain			-
	Fire Dampers	- "	-	_
4.	Smoke Management System.	,	NA.	
	Basements		,	
		•		2
	Upper floors	_	_	∠
5.	Fire Extinguishers			8
J.			Provided	
	Total numbers		20	MR
	• Types	. , ,	ABCTYPE	-ucs
	IS marking	ISI marked	ABC Type 151 Marked	-11-
6.	First-Aid Hose Rees.	-	NA	
	Total numbers on each floor		•	
	Length of hose reel hose	30 m	-	_
	Nozzle diameter	5 mm	-	
7.	Automatic fire detection and alar	14 · A	14 · A	
	Type of detectors	-	-	
	Location of Main Panel	_	•	U
	Location of Repeater Panel	-	-	
	Alternate source of power		•	
	Hooter's Location	-		
8.	MOEFA	2	NA	
9.	Public Address System.	Required	Provided	mr

	Automatic Sprinkler system		NA	
1	Basement	~	. j	,
	Upper Floor	-	-	~
	Sprinkler above false ceiling	-		_
11.	Internal Hydrants		NA	
	Size of riser/down-comer	•		
	Number of hydrants per floor		-	
	Hose Box	gu		
12.	Yard Hydrants.		NA	
	Total number of hydrants		•	•
	Hose Box	_	~	_
13.	Pumping Arrangements.		NA	
	Ground Level			
	Discharge of main pump	-	-	•
	Head of Main pump	-	_	_
	Number of main pumps		-	_
	➤ Jockey Pump out put	-	-	~
	Jockey pump head	· · ·	-	-
	Standby pump out put	-	-	_
	Standby pump Head	<u> </u>		•
	Auto Starting/Manual stopping		•	
		-	_	
	> Pump Hose Access Terrace level	<u>~</u>	_	~
			-	
	Discharge of pump	-	,	
	➤ Head of the pump	- 1 · · · · · · · · · · · · · · · · · ·		
	> Power supply	"	_	-
	> Auto Starting of pump	_	_	-

	Captive Water Storage for fire fig	hting.	NA	
F	Underground tank capacity	_	6	7
	> Draw -off connection	<u>~</u>		
v	Fire service inlet			_
	> Access to tank	-	-	· ·
	Overhead Tank Capacity		-	
15	Exit Signage.	Repused	Provided	mr
16.	Provision of Lifts		NA	
	Pressurization of Lift Shaft	-	_	-
	Pressurization of Lift lobby	-	6	1
	Communication In lift Car	-	ſ	1
	Fireman's Grounding Switch	K	6	
	Lift Signage	_		-
17.	Standby power supply		NA	
18.	Refuge Area		NA	
,	> Total Area		(20, 4)	
	> Location	-	_	
19.	Fire Control Room		NA	
	Detector System Panel	2	_	-
	Flow Switch Panel	•	<u>-</u>	_
	➤ PA system Panel	-	_	
	➤ Batter backup	~	-	
	➤ Building Floor plans	~		<u></u>
20.	Special Fire Protection Systems for Protection of special Risks, if any:	-		_

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial number.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name

SHRI RAJMAL KHOKHAR

Name

Designation

ASSTT. DIV. OFFICER

Disignation

CMM) OR

a speur