

No. 66/06-8/08/84/2012/170

Dated: 19/01 /12

FIRE SAFETY CERTIFICATE

Issued 1.7. /. at New Delhi by.

CHIEF FIRE OFFICER
for DIRECTOR
DELHI FIRE SERVICE

Copy to:

- 1. Shri Surinder Pal Singh, M/s York Restaurant, K-10, Connaught Circus, New Delhi-110001
- 2. Shri P.K Sharma, Medical officer of Health, Health Department, Palika Kendra, Sansad Marg, New Delhi-110001

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

	INSPECT	TION REPORT		2 4		
	yo-	EK Restausan	to 10-11, K b	lock,		
1.	Name & address of the building: Canaught cizcus, New Della-1/2001. Type of Occupancy Postant anti-					
	. restausent					
	3. Type of Case : New Case/ Renewal					
4.	: Letter I	No. FG/DFS/MS/B	EH /2008 /1975 Date	d. 15-07-200		
	5. Fire Safety directives letter No : NIL 6. Date of inspection : 13-01-2012					
7.	The mapecing Officers:	S. yadav A	20.0	1		
8.	Name and designation of officers					
0	•	s Balbie Si				
	Year of Construction : Ps	102 to 1982.				
S. 10	Applicant's letter No.	Il dated		old case		
No.	Minimum Standards on fire	NBC	Provided at site	Remarks		
	prevention and fire safety U/R 33	Requirement		MR/NMR		
1	Access to building					
	 Road width 	12 M	more than	M.R		
	 Gate width 	1.25 M	1.25 M	M.R		
	 Width of internal road 	- N.A-	- N.A-			
2	Number, Width, Type & Arrangement of		- N. H-	-N.A-		
	a. Number of staircases	O LAILS				
	 Upper Floors 	Two Exits	Mezanine flos			
	• Basements	-N.A -	Istail + 1 Exit	m·R		
	b. Width of staircases	- //	-N. 01.	- N.A -		
	 Upper Floors 		100	į.		
	Basements	TWO Exits	go cmg	M.R		
	c. Protection of exits	-N. A-	- N. A-	- N.A -		
	5					
	• Fire check door	N.A -	9			
	• Pressurization	9				
	e. No. of continuous staircases to terrace	N.A				
	g. Width of Corridor	- N. A				
	h. Door Size	1.25 M.	1-25 M	M. R		

contd:

York Restausant, K-10-11 canaught einend

	Compartmentation.	MA	,	,	
	• Fire check door	JVC 1			
1	 Sealing of electrical shafts 			8 3 1	
	• Fire Rating of shaft door	3			
	Water Curtain				
	 Fire Dampers 			y	
4	Smoke Management System.	*			
	Basements	30 a/c per hour	-N. A -	-NA-	
	Upper floors	12 a/c per hour	ips	M.R.	
5	Fire Extinguishers	2 2			
	Total numbers		Five eoz Type = 2 N W. Coz Type = 2 N	M.R.	
	Types		602 Type = 2 N	108 M.R.	
	IS marking	ISI marked	ABC Type= 1 No	o. M.R.	
6	First-Aid Hose Reels.	9			
	Total numbers on each floor		one pose	1 m.R	
	 Length of hose reel hose 	30 m	Leel at great	m.R	
	Nozzle diameter	5 mm	yes	M.R	
7	Automatic fire detection and alarming system.				
	Type of detectors	N.	A		
	 Location of Main Panel 				
	• Location of Repeater Panel				
	Alternate source of power				
	Hooters' Location				
8	MOEFA	48	yes	m· R	
9	Public Address System.	N. A		1	
10	Automatic Sprinkler System.				
-	Basement	N. A			

conta.

York Restaulant 10-11, K black, canaught circul, New Delli-11:00

y s	• Upper Floor	1108	3.00	1
c	 Sprinkler above false ceiling 	ges	yes	M·R.
11	Internal Hydrants	- N.A -		
		,	1	
	Size of riser/down-comer	~ N-	4	
	Number of hydrants per floorHose Box			
	TIOSE DOX	4,		
12	Yard Hydrants.			
	 Total number of hydrants 	N. A		T
	Hose Box			
13	Pumping Arrangements.			
	Ground Level			
	Discharge of main Pump	N.H		
	> Head of Main pump			
	Number of main pumps			
	> Jockey Pump out put			
	> Jockey pump head			
	> Standby Pump out put		1	10
	Standby Pump Head			
	➤ Auto Starting/ Manual			. 3/
	stopping			
	> Pump House Access			
	Terrace level			
	Discharge of pump	450 LPM	450 2 PM	m.R
	> Head of the pump	. 30 M	30 M	MR
	Power Supply	yes	DG. €	M. R
1.5	> Auto Starting of pump	ye.g	BSES yes	M. R
14	Captive Water Storage for fire fighting		J T	
	Underground tank capacity	-N.A		
	> Draw-off connection	N. A		

contd:

York Restaulant KION canonist ciacus

	> Fire service inlet	yes	yes .	M.R
	Access to tank	yes.	yes	M.R.
	Overhead Tank capacity	5,000 litres	5000 liter	M.R.
15	Exit Signage.	:		
16	Provision of Lifts.			1
	• Pressurization of Lift Shaft	N.	A	
u U	 Pressurization of Lift lobby 			
	• Communication In lift Car			
	• Fireman's Grounding Switch	A.,		
	• Lift Signage		8 e 8 20 20 1	
	zat biginge			
17	Standby power supply	yes.	DG. Set	m·R
18	Refuge Area.			
	> Total Area	N. A		
8	> Location			
19	Fire Control Room			
	Detector System Panel	N.	A	
	Flow Switch Panel			
	PA System Panel			
	Batter backup			
			8	The fig. of a g
20	Building Floor Plans			
20	Building Floor Plans Special Fire Protection Systems for	N- A		
20	Building Floor Plans	N- A		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

