FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/EH/2012/539

Dated: 17 /02 /2012

FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

0100

Copy to:
Sh. Naveet Guppta (Director)
Berco's Restaurant
Plot no. 18, Pankaj Arcade, Road No.44,
Rani Bagh Commercial Complex
Pitam Pura, New Delhi-110034

Note:- For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working g conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on www.dfs.delhigovt.nic.in

May Kindly peruse letter no. nil dated 01-02-2012 received from Sh. Naveet Guppta (Director) for Holy Shrine Hotel Pvt. Ltd. regarding of NOC in r/o Berco's Restaurant located at Plot no. 18, Pankaj Arcade, Road No.44, Rani Bagh Commercial Complex Pitam Pura, New Delhi-110034. premises was inspected by the undersigned & the fire safety arrangements are put up on the prescribed Performa:

1. Name &address of the building : Berco's Restaurant located at Plot no. 18, Pankaj Arcade, Road

No.44, Rani Bagh Commercial Complex Pitam Pura, New

Delhi-110034.

2. Type of Occupancy : Class-D (Assembly)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/EH/2006/2662 dated 20/09/2006

5. Fire Safety directives letter No. N.A.

6. Date of inspection : 09/02/2012

7. Name of the Inspecting Officers : Divisional Officer Sunil Chowdhary

8. Name and designation of officers

From the building side : Sh. Naveet Guppta (Director)

Year of Construction

9. Applicant's letter No. : nil dated 01-02-2012

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR			
1.	Access to building						
	Road width	12 mtrs	15 mtr	M/R			
	Gate width	4.5 mtr	Building is open on all side	M/R			
	Width of internal road	6 mtr	more than 6 mtr	M/R/			
2.	2. Number, Width, Type & Arrangement of Exits						
	a. Number of staircases	3	2	M.R			
	• Upper Floors	3	2	M.R			

		N.A.	N.A.	Not applicable		
	Basement			- Area of Francisco		
	b. Width of staircases					
	Upper Floors	Two 1.5 mtr	Two 1.5 mtr & one 1.25 mtr	M.R.		
	Basement	N.A.	N.A.	Not applicable		
	c. Protection of exits					
	Fire check door	N/R	N/R	Not applicable		
	Pressurization	N/R	N/R	Not applicable		
	d. No. of continuous staircases to terrace	2	3	M.R		
	e. Width of Corridor	2 mtr	Provided	M.R		
	f. Door size	2 mtr & 1.5 mtr	Provided	M.R.		
3.	Compartmentation.					
	Fire check door	N/R	N/R	Not applicable		
	Sealing of electrical shafts	N/A	N/A	Not applicable		
	Fire Rating of shaft door	N/A	N/A	Not applicable		
	Water Curtain	N/R	N/R	Not applicable		
	Fire Dampers	N/A	N/A	Not applicable		
4.	Smoke Management System.		1			
	• Basements	N/R	N/R	Not applicable		
	Upper floors	Required	Provided	M.R		
5.	Fire Extinguishers	9				
	Total numbers	4	10	M.R		

				T	
	• Types	ABC & CO ₂	provided	M.R	
	IS marking	ISI marks	provided	M.R	
6.	First-Aid Hose Rees.	I			
	Total numbers on each floor	1	Provided	M.R	
	Length of hose reel hose	30 m	provided	M.R	
	Nozzle diameter	5 mm	provided	M.R	
7.	Automatic fire detection and alar	ming system.			
	Type of detectors	Smoke & Heat type	Provided	M.R	
	Location of Main Panel	Ground floor	Provided	M.R	
	Location of Repeater Panel	N/R	N/R	Not applicable	
	Alternate source of power	Required	Provided	M.R	
	Hooter's Location	Required	Provided	M.R	
8.	MOEFA	Required	Provided	M.R	
9.	Public Address System	Required	Provided	M.R	
10.	Automatic Sprinkler system				
	Basement	N/R	N/R	Not applicable	
	• Upper Floor	N/R	Provided	M.R	
	 Sprinkler above false ceiling 	Required	Provided	M.R	
11.	Internal Hydrants	1			
	Size of riser/down-comer	100 mm	provided	M.R	

	Number of hydrants per floor	1	Provided	M.R
	Hose Box	1	Provided	M.R
12.	Yard Hydrants.	,		
	Total number of hydrants	N/R	N/R	Not applicable
	Hose Box	N/R	N/R	Not applicable
13.	Pumping Arrangements.			
	Ground Level			
	Discharge of main pump	N/R	N/R	Not applicable
	➤ Head of Main pump	N/R	N/R	Not applicable
	Number of main pumps	N/R	N/R	Not applicable
	➤ Jockey Pump out put	180 LPM	Provided	M.R
	> Jockey pump head	40 mtr	Provided	M.R
	Standby pump out put	N/R	N/R	Not applicable
	➤ Standby pump Head	N/R	N/R	Not applicable
	Auto Starting/Manual stopping	Required	Provided	M.R
	> Pump Hose Access	Required	Provided	M.R
	Terrace level			
	Discharge of pump	450 LPM	Provided	M.R
	➤ Head of the pump	40 mtr	Provided	M.R

	➤ Power supply	Required	Provided	M.R
	➤ Auto Starting of pump	Required	Provided	M.R
14.	Captive Water Storage for fire f	ighting.		
	Underground tank capacity	N/R	N/R	Not applicable
	Draw -off connection	N/R	N/R	Not applicable
	➤ Fire service inlet	N/R	N/R	Not applicable
	> Access to tank	N/R	N/R	Not applicable
	Overhead Tank Capacity	10, 000 ltr	Provided	M.R
15	Exit Signage.	Required	Provided	M.R
16.	Provision of Lifts			
	Pressurization of Lift Shaft	N/A	N/A	Not applicable
	Pressurization of Lift lobby	N/A	N/A	Not applicable
	Communication In lift Car	N/A	N/A	Not applicable
	 Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total Area Location 	N/A	N/A	Not applicable
	Lift Signage	N/A	N/A	Not applicable
17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area	N.R.	N.R	Not applicable
	> Total Area	N.R.	N.R.	Not applicable
	> Location	N.R.	N.R.	Not applicable
19.	Fire Control Room	Ŷ.	4	

- 10				
- 1	L			
-3	TO.	A		

	Detector System Panel	N.R.	N.R.	Not applicable
	> Flow Switch Panel	N.R.	N.R.	Not applicable
	> PA system Panel	N.R.	N.R.	Not applicable
	Batter backup	N.R.	N.R.	Not applicable
	Building Floor plans	N.R.	N.R.	Not applicable
20.	Special Fire Protection Systems for Protection of special Risks, if any:	N.R.	N.R.	Not applicable /

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

Signature of the Inspection Officer

Name SUMIN CHAMBNAR-)

Name

Designation () -

Designation