GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT LANE NEW DELHI-110 001.

No. F6/DF-S/ors/school/2012/467

Dated: 10/02/12

## FIRE SAFETY CERTIFICATE

Issued on \_\_\_\_\_\_\_ at New Delhi by

Director

Delhi Fire Service

De We

Shri S.P. Sehrawat, Principal, GOVT. GIRLS SR. SEC. SCHOOL, Bankner, Delhi-110 040.

Copy to:

The Director,
Dte. Of Education,
Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

Name & address of the building SCHOOL, BANKNER, DELHI-LO Type of Occupancy 2. SCHOOL Type of Case NEW CASE Details of previous NOC N.A. Fire Safety directives letter No. Date of inspection SHRI RAJMAL KHOKHAR 7. Name of the Inspecting Officers ADO 8. Name and designation of officers : SHRI S.P. SEHRAWAT From the building side PRINCIPAL 9. Year of Construction : 1987, 2010, 2011 10. Applicant's letter No. GGSSS BKN 11 564 Dated 14.12.11

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	Nivering NBC livin dt Requirement 1-3-1)	Provided at site	Remarks MR/NMR	
1.	Access to building		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	WINTER	
	Road width	Accessible	-Accessibile	mR	
	Gate width	-11-	<u>−</u> α ← −	u	
	Width of internal road		*	-	
2.	Number, Width, Type & Arrangement of Exits A Bock - 2 Stairs, B + C Mock - 1 Stair each.				
	d. Trumber of stancases	Four	Form	mR.	
	Upper Floors		<del></del> u		
	• Basement	e e e e e e e e e e e e e e e e e e e	~		
	b. Width of staircases	150 Cms, 150 Cms,	160 ans, 160 cms	MR	
	• Upper Floors	<u> </u>	n	u_	
	• Basement	_	<b>←</b>	•	
	c. Protection of exits			6	
	• Fire check door	~	-	<u> </u>	
	<ul> <li>Pressurization</li> </ul>	•		_	
	d. No. of continuous staircases to terrace	Form	For	mR	
	e. Width of Corridor	15 Melns	2 Melis	-u-	
	f. Door size	Double Don 100 Cms Each	Double Door	mR	

<u> </u>	Compartmentation.		NA	
	Fire check door	_		57
	Sealing of electrical shafts	~	+	5
	Fire Rating of shaft door	- '	-	~
	Water Curtain	8	-	- '
	Fire Dampers	-		-
4.	Smoke Management System.		NA	
	Basements	, <del></del>	•	~
	Upper floors			
		_	•	
5.	Fire Extinguishers		Provided	d
	Total numbers		15	mR
	• Types		9 - ABC Type 4 - CO2 Type	- U -
	IS marking	ISI marked	2 - Fram Type ISI Marked	-u-
6.	First-Aid Hose Rees.		NA	
	Total numbers on each floor			
	Length of hose reel hose	30 m	•	_
	Nozzle diameter	5 mm	_	-
7.	Automatic fire detection and alar	ming system.	NA	
	Type of detectors		•	10
	Location of Main Panel	-	_	-
	Location of Repeater Panel	_	*	
	Alternate source of power		_	7
9	Hooter's Location			-
8.	MOEFA	•	AU	~
9.	Public Address System.	Repuised	Provided	MR

5	Automotic Sprinkland			
<u> </u>	Sprinkler system		NA	
	• Basement	-		5
	Upper Floor	-	_	-
	Sprinkler above false ceiling	-		_
11.	Internal Hydrants	3	) - A	2
			MA	
	Size of riser/down-comer	•		*
	<ul> <li>Number of hydrants per floor</li> </ul>	te-	-	
	Hose Box	-	-	_
12.	Yard Hydrants.		NA	
			1	
	Total number of hydrants		7	6
12	Hose Box	-	-	-
13.	Pumping Arrangements.		NA	
	Ground Level			
	Discharge of main pump	•		-
	Head of Main pump	-	_	
	Number of main pumps			-
	Jockey Pump out put	-	-	
	Jockey pump head		¥ .	_
	Standby pump out put		_	
	Standby pump Head	-	pm.	-
	Auto Starting/Manual stopping	*	•	<b>L</b>
	Pump Hose Access		-	_
	Terrace level	5	_	_
	Discharge of pump	-	_	
	► Head of the pump	-		
	> Power supply	*		_
	➤ Auto Starting of pump	_	-	-

4.	Captive Water Storage for fire fighti	ng.	NA		
	Underground tank capacity				
	> Draw -off connection			<b>~</b>	
	> Fire service inlet		~	•	
	> Access to tank		-	-	
	<ul><li>Overhead Tank Capacity</li></ul>	b	_	~	
15	Exit Signage.	Required	fronded	mr	
16.	Provision of Lifts		NA		
10.	Pressurization of Lift Shaft		-	-	
	Pressurization of Lift lobby	•	-	-	
	Communication In lift Car	em)	, -	_	
	Fireman's Grounding		_	_	
	<ul><li>Switch</li><li>Lift Signage</li></ul>	^		-,	
17.	Standby power supply		A Vi		
			NA	3 A	
	> Total Area	-		275	
	> Location	•	3		
19.	Fire Control Room		NA		
	> Detector System Panel			-	
	> Flow Switch Panel	b			
	> PA system Panel	· .		50	
	> Batter backup		~	_	
	<ul><li>Building Floor plans</li></ul>		*	5	
20	Special Fire Protection Systems for Protection of special Risks, if any:	_	_		

10

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial number.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name

SHRI RAJMAL KHOKHAR

Name

Designation ASSTT. DIV OFFICER

Disignation