

No. 66/06-8/08/84/2012/170

Dated: 19/01/12

FIRE SAFETY CERTIFICATE

Issued 1.7. /.at. New Delhi by.

CHIEF FIRE OFFICER for DIRECTOR DELHI FIRE SERVICE

Copy to:

- 1. Shri Surinder Pal Singh, M/s York Restaurant, K-10, Connaught Circus, New Delhi-110001
- 2. Shri P.K Sharma, Medical officer of Health, Health Department, Palika Kendra, Sansad Marg, New Delhi-110001

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

	INSPECT	ION REPORT		lock	
	Name & address of the building: Canaught circus, New Della-11000/. Type of Occupancy Restaulant				
1.	Name & address of the building: Canaught circus, New Dela -11				
2.	1				
3.	. New Case/ Renewal				
4.	Letter No. P6/Drs/M5/LM/2008/1975 Dated: 15-07-20			:15-07-2008	
	5. Fire Safety directives letter No :				
6.	Date of inspection $\frac{13 - 01 - 2012}{13 - 01}$				
7.	7. Name of the Inspecting Officers: D.S. yadav. ADO				
8.	8. Name and designation of officers				
	from the building side	i Balbie Sin	ngh .		
		102 to 1982.			
1		L dated		old case	
S.	Minimum Standards on fire	NBC	Provided at site	Remarks	
No.	prevention and fire safety U/R 33	Requirement	r v	MR/NMR	
1	Access to building	9		,	
	 Road width 	12 M	more than	M.R	
	Gate width	1.25 M	1.25 M	M.R	
	Width of internal road	- N.A-	- N.A-	-N.A-	
2	Number, Width, Type & Arrangement	of Exits	***************************************		
	a. Number of staircases		8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8		
	Upper Floors	Two Brits	Mezanine floor	m·R	
	Basements	-N.A-	- N. A	- N.A -	
	b. Width of staircases				
	Upper Floors	TWO Exits	Mezanine flow	M.R	
	Basements	-N. A-	90 cmp	- N.A -	
	c. Protection of exits	- /// //			
	Fire check door	N.A -		9-7	
	Pressurization				
=	e. No. of continuous staircases to terrace	N.A			
	g. Width of Corridor	1/ 0		, i	
	h. Door Size	1.25 M:	1-25 M	M. R	
	2001 bizo	1 43	1 20 10	1 / /	

contd:

York Restausant, K-10-11, canaught einend

 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking 	30 a/c per hour 12 a/c per hour	Five con Type = 2 N W. Con Type = 2 N	-N. A - M. R.	
 Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types 	12 a/c per hour	ips	M.R.	
 Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types 	12 a/c per hour	ips	M.R.	
 Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types 	12 a/c per hour	ips	M.R.	
 Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types 	12 a/c per hour	ips	M.R.	
 Basements Upper floors Fire Extinguishers Total numbers Types 	12 a/c per hour	ips	M.R.	
 Upper floors Fire Extinguishers Total numbers Types 	12 a/c per hour	ips	M.R.	
Fire Extinguishers Total numbers Types				
Total numbersTypes		Five cor Type = 2 N	M. R.	
Total numbersTypes	ISI	Five con Type = 2 M	m.R.	
• Types	ISI	Five eoz Type = 2 N	M·R.	
50 50	ICI1	eo2 Type = 2N	nx.	
IS marking	TOT 1 1		08 M.R.	
	ISI marked	ABC Type= 1 M	m.R.	
First-Aid Hose Reels.		. 0		
 Total numbers on each floor 		one pose	n n-R	
 Length of hose reel hose 	30 m	floor.	m.R	
Nozzle diameter	5 mm	yes	MR	
Automatic fire detection and alarming system.				
• Type of detectors	N.	A		
• Location of Main Panel				
Location of Repeater Panel				
Alternate source of power				
Hooters' Location				
	2 2			
MOEFA	48	yes	m. R	
Public Address System.	MA			
Automatic Sprinklar System			-	
	 Automatic fire detection and alarming Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA	Automatic fire detection and alarming system. Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System.	Automatic fire detection and alarming system. Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System.	

contd:

York Restaulant 10-11, K black, canaught circul, New Delli-1100

	Upper FloorSprinkler above false ceiling	ye8	yes	M·R.
11		- N.A -		
- 1 1	Internal Hydrants	-	= 2	
	Size of riser/down-comer	- N-	4	
	Number of hydrants per floor			
	Hose Box			
12	Yard Hydrants.			
				4
	Total number of hydrants	N. A		
13	Hose Box		•	
	Pumping Arrangements.			
	Ground Level	N. A		
	Discharge of main Pump			
	Head of Main pump	14.8		
	Number of main pumps		-	
	> Jockey Pump out put			
=	> Jockey pump head			
	➤ Standby Pump out put			
	Standby Pump Head			
	· · · · · · · · · · · · · · · · · · ·			100
	Auto Starting/ Manual			
	stopping	*		į, t
	Pump House Access			
	Terrace level	WT- I PM	1 0 00	
	Discharge of pump	450 LPM	450 2 PM	M.R
	> Head of the pump	30 M	30 M	MR
	> Power Supply	yop	D.G. C BSES	M. R
	➤ Auto Starting of pump	yes	yes	M.R
14	Captive Water Storage for fire fighting	•	V	
	Underground tank capacity	-N.A		
	> Draw-off connection	N/A		

contd:

york Restaulant

	> Fire service inlet			
	> Access to tank	yes	yes	M.R
	Overhead Tank capacity	yes.	yes	M.R
15		5,000 litres	5000 liteer	M.R
16	Exit Signage.			
10	Provision of Lifts.			· cont
	Pressurization of Lift Shaft	N.	A	
	• Pressurization of Lift lobby			
	• Communication In lift Car			-
	• Fireman's Grounding Switch			
	• Lift Signage			
177				
17	Standby power supply	yes	DG Set	
18	Refuge Area.			m·R
	> Total Area	N.A		
2	> Location	1		2
19	Fire Control Room			
	Detector System Panel	No	9	
	Flow Switch Panel	1//	7	
4				
	PA System Panel			
	Batter backup			
20	Building Floor Plans			4
20	Special Fire Protection Systems for	N.A		
	Protection of special Risks, if any:			
		i e gale		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers...

And the second s	york Restaulant & 10-11 carought energy New Delli-11 cool. (5)
A Property	
	9godo 01-2012
# # # # # # # # # # # # # # # # # # #	Signature of the Inspecting Officer Signature of the Inspecting Officer
	Name D.S. yadav
	Designation Designation Designation Designation Designation Designation Designation Designation
	Do Cesteal)