GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE

No. 66/065/ms/44/2012/148

13

Dated: 16/01/12

FIRE SAFETY CERTIFICATE

Certified that the Ivory 32 Guest House, Plot No. C-32 located at Greater Kailash-I, New Delhi-110048 comprised of Basement, Ground + 3 Upper Floors (22 guest rooms). The premises was re-inspected by the officer concerned of this department on 16/12/11 in the presence of Mr. R.K Gupta and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Lodging or Rooming House of Group – A with effect from 22/12/11 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire subject to conditions printed below.

Issued ----- at New Delhi by.

Chief Fire Officer for Director Delhi Fire Service

- Copy to:- (1) Deputy Health Officer,
 Municipal Corporation of Delhi,
 Health Department Central Zone, Lajpat Nagar, New Delhi.
 (2) Addl. C.P.(Lic.),Police Station Defendee Colony,New Delhi
 - (3) Plot No. C-32, Greater Kailash-I, New Delhi-110048.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

- 1. Name & address of the building:- Plot No. C-32, Greater Kailash-I, New Delhi-110048.
- 2. Type of occupancy:- Lodging or Rooming House
- 3. Type of case:-New
- 4. Details of previous NOC:-No
- 5. Fire safety directives No.- No
- 6. Date of inspection:-
- 7. Name of the inspecting officer:-A.D.O. S.S. Kaushik & D.O Drampal Bhardway
- 8. Name & designation of officer From the building side:-
- 9. Year of construction: 2005-07

9. Y	rear of construction:- 20 05- 67 Applicant's letter No:-Nil dated 28/11/11	Decement Com	1.21.	a makenord		
S.No.	Minimum Standards on fire	NBC	Provided at	Remarks		
ACRAGE N	Prevention and fire safety U/R 33	Requirement	site	MR/NMR		
1.	Access to Building	quastantia	5100	IVIIOIVIIC		
	1) Road width	Required	Provided	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrange	ment of Exits				
	A. Number of staircases	Required	1 Nos.	MR		
	1. Upper floors	Required	Provided	MR		
9	2. Basements	Required	2 Nos. Provided	MR		
	B. Width of staircase					
	1. Upper floors	Required	1.25 cms.	MR Construction		
	2. Basements	Required	Two exit	MR 2005 L		
	C. Protection of exits	N/A	N/A	N/A		
	1. Fire check door	Required	Provided	mRa		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	Required	one	MR		
	E. Width of corridor	Not required	Provided	MR		
	F. Door size	N/A	N/A	N/A		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 a/c per hour	Exhaust fan provided	MR		
	2) Upper floors	12 a/c per hour	N/A	N/A		
5.	Fire Extinguishers			~ 1/4 4		
	1) Total numbers		12 Nos.	MR		
	2) Types	ISI Marked	ABC & W.Co2	MR		
	3) ISI marking		Yes	MR		
6.	First-Aid Hose Reel					

-x1/4-

	- 179			
	1) Total number of each floor	Required	One at each floor	MR
	2) Length of hose reel hose	30 m	Yes	MR
	3) Nozzle diameter	5 mm	Yes	MR
7.	Automatic Fire Detection & Alarmin			IVIK
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	N/A	Previded	MR
10.	Automatic Sprinkler System		KARO VICILIA V	IVIIC
	1) Basement	Required	Provided	MR
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false ceiling	N/A	N/A	
1.	Internal Hydrants	11/11	IV/A	N/A
	1) Size of riser/down-comer	N/A	N/A	NI/A
	2) Number of hydrants per floor	N/A		N/A
	3) Hose box	N/A	N/A	N/A
2.	Yard Hydrants	14/14	N/A	N/A
	1) Total number of hydrants	N/A	DI/A	37/
	2) Hose box	N/A N/A	N/A	N/A
		IN/A	N/A	N/A
3.	Pumping Arrangement			
	1) Ground level	N/A	N/A	27/4
	a) Discharge of main pump	N/A		N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A N/A	N/A	N/A
	g) Stand by pump head		N/A	N/A
	h) Auto starting/Manual stopping	N/A	N/A	N/A
	2) Terrace level	N/A	N/A	N/A
	a) Discharge of pump	Required	Provided	MR
	a) Disentinge of pullip	Required 9	450 LPM & 180 LPM	MR
	b) Head of pump	Required	30 mtr.	MR
	c) Power supply	Required	D.G. set	MR
			provided	IVIK
	d) Auto starting of pump	Required	Yes	MR
4.	Captive Water Storage for Fire Fightin	ng		
	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	Required	10,000 Ltr.	MR
	Exit Signage.	Required	Provided	MR
ó,	Provision of Lifts.		TTOVIUCU	IVIK
	a) Pressurization of lift shaft	N/A	N/A	NI/A
	b) Pressurization of lift lobby	N/A		N/A
	c) Communication in lift car		N/A	N/A
	/ in the car	Required	Provided	MR

	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
- 3	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	Required	Provided	MR
20.	Special Fire Protection System for Protection of special Risk, if any:			

The fire protection system provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010-----

Signature of the inspecting officer

Signature of the inspecting officer

Name Dharmpal Bhardway'
Designation wirismal Afran

Name

Maushy 21/14/11 S.S. KAUSHIK

Designation AssA Div. Mrcu