FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. 66/28/01/2012/410

Dated: 07 / 02 / 2012

FIRE SAFETY CERTIFICATE

Chief Fire Officer
For Director
Delhi Fire Service

Men

Copy to: M/s Khaaja Chowk (a unit of Economy Foods) TF-03. City Square, Shivaji place, Raja Garden New Delhi-110027

Note:- For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on www.dfs. delhigovt. nic.in

May Kindly peruse letter no. nil dated 05-01-2012 received from Sh. Kavya Tandon Khaaja Chowk regarding issue of NOC in r/o M/s Khaaja Chowk (a unit of Economy Foods) TF-03, City Square, Shivaji place, Raja Garden New Delhi-110027. This Mall has already been issue NOC wide letter no. F6/DFS/MS/2005/2314 dated 08/11/2005. However following fire safety points are put up on the prescribe Performa.

1. Name &address of the building : M/s Khaaja Chowk (a unit of Economy Foods) TF-03, City

Square, Shivaji place, Raja Garden New Delhi-110027

2. Type of Occupancy : Class-D (Assembly)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/EH//2008//3229 dated 24/11/2008

5. Fire Safety directives letter No. : Nil

6. Date of inspection :

7. Name of the Inspecting Officers : Divisional Officer Sunil Chowdhary & A.D.O. S.S. Tuli

8. Name and designation of officers

From the building side : Kavya Tandon

9. Year of Construction

10. Applicant's letter No. : nil dated 05-01-2012

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building				
	Road width	09mtrs	30 mtr	M/R	
	Gate width	5 mtr	5 mtr	M/R	
	Width of internal road	6 mtr	6 mtr	M/R	
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases				
	• Upper Floors	Three	Three	In Mall/M.R	
	Basement	Five	Five	'' / M.R	

			ж	
	b. Width of staircases	6		
	• Upper Floors	1.5 mtr & 1.25 mtrs	Provided	Specification has already being be checked during earlier inspection.
	Basement	1.5 mtr & 1.25 mtrs	Provided	M.R
	c. Protection of exits			
	Fire check door	Required	Provided	M.R
	Pressurization	Required	Provided	M.R
	d. No. of continuous staircases to terrace	three	three	M.R
	e. Width of Corridor	Required	Provided	M.R
	f. Door size	Minimum Two exits of 2 mtrs width	Provided	M.R.
3.	Compartmentation.			
	Fire check door	Required	Provided	In Mall/ M.R
	Sealing of electrical shafts	Required	Provided	" / M.R
	Fire Rating of shaft door	2 hrs	Provided	'' / M.R
	Water Curtain	Required	Provided	In Mall / M.R
	Fire Dampers	Required	Provided	'' / M.R
4.	Smoke Management System.	2		
145	Basements	Required	Provided	In Mall / M.R
	Upper floors	Required	Provided	" / M.R
5.	Fire Extinguishers		4	
	Total numbers	20	provided	'' / M.R
	• Types	ABC & CO ₂	0	

			provided	" / M.R	
	• IS marking	required	provided	" / M.R	
6.	First-Aid Hose Rees.				
·\$1	Total numbers on each floor	two	two	In Mall/M.R	
	Length of hose reel hose	30 m	30 mtr	" / M.R	
	Nozzle diameter	5 mm	5 mm	'' / M.R	
7.	Automatic fire detection and alarming system.				
	Type of detectors	Smoke & Head	Provided	In Mall/M.R	
	Location of Main Panel	Ground floor	Provided	'' / M.R	
	Location of Repeater Panel	Ground floor	Provided	'' / M.R	
	Alternate source of power	Required	2 generator 450 KVA each	'' / M.R	
	Hooter's Location	Required	Provided	"'/M.R	
8.	MOEFA	Required	Provided	'' / M.R	
9.	Public Address System.	Required	Provided	'' / M.R	
10.	Automatic Sprinkler system				
	Basement	Required	Provided	" / M.R	
	Upper Floor	Required	Provided	'' / M.R	
	Sprinkler above false ceiling	Required	Provided	'' / M.R	
11.	Internal Hydrants			-	
	Size of riser/down-comer	150 mm	150 mm	'' / M.R	
W.	Number of hydrants per floor	2	2	'' / M.R.	

	Hose Box	2	2	'' / M.R
12.	Yard Hydrants.			
	Total number of hydrants	4	Provided	" / M.R
	Hose Box	required	Provided	" / M.R
13.	Pumping Arrangements.			
	Ground Level	Required	Provided	It has already been checked during earlier inspection In Mall /M.R
	Discharge of main pump	2850 LPM	Provided	22 22
	➤ Head of Main pump	80 mtr	Provided	22 22
	Number of main pumps	2	Provided	22 22
	➤ Jockey Pump out put	180 LPM	Provided	
	Jockey pump head	80 mtr	Provided	22 22
	Standby pump out put	o		22 22
	Standby pump Head	2850 LPM	Provided	" "
	Auto Starting/Manual stopping	80 mtr	Provided	22 22
	> Pump Hose Access	Required	Provided	22 22
	Terrace level	Required	Provided	22 22
	Discharge of pump			
	➤ Head of the pump	900 LPM 80 mtr	Provided Provided	"
	> Power supply	Required	Provided	" / M.R

	> Auto Starting of pump	Required	Provided	'' / M.R	
14.	Captive Water Storage for fire fighting.				
	Underground tank capacity	100,000	100,000	'' / M.R	
	Draw -off connection	Required	Provided	'' / M.R	
	➤ Fire service inlet	Required	Provided	'' / M.R	
	Access to tank	Required	Provided	'' / M.R	
	Overhead Tank Capacity	Required 30,000 ltrs	Provided	'' / M.R	
15	Exit Signage.	Required	Provided	In Mall & Restaurant	
16.	Provision of Lifts				
	Pressurization of Lift Shaft	Required	Provided	In Mall / M.R	
	Pressurization of Lift lobby	>> >>	22 22	22 22	
	Communication In lift Car	>> >>	22 22	>> >>	
	Fireman's Grounding Switch	22 22	22 22	22 22	
	Lift Signage	22.22	22 22	22 22	
17.	Standby power supply	Required	Provided	In Mall/ M.R	
18.	Refuge Area	N.R.	N.R	In Mall/ M.R	
	> Total Area	22 22 7	22 22	22 22	
	➤ Location	22 22)))) [- ()	22 22	
19.	Fire Control Room				
=	> Detector System Panel	Required	Provided	In Mall/ M.R	

		Required	Provided	"
	Flow Switch Panel			
		Required	Provided	""
	PA system Panel			
	➤ Batter backup	Required	Provided	""
	Building Floor plans		P S	
20.	Special Fire Protection Systems for	N.R.	N.R.	Not applicable
	Protection of special Risks, if any:		9	

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

Name

Signature of the Inspection Officer

Name SUNIL (MAWDSHR)

Designation 9.0 (nust)

Designation