GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT LANE: NEW DELHI. Dated: 05 | 03 | 12

No. f6 [OFS/ms/2012/773

## FIRE SAFETY CERTIFICATE

Certified that the PUSHPA DEVI BAGRODIA DHARAMSHALA located at PSP Area-3, Sector-5, Rohini, Delhi-110 040, was issued NOC vide this office letter No. F.6/DFS/MS/2009/368 dated 06.02.2009 deemed to have complied with the fire prevention and fire safety requirements in accordance with the rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 17.01.2012 in the presence of Sh. R.K. Bhasin, Manager & that the buyilding/ premises is fit for occupancy Class A (Residential Bly) with effect from 05/03/12 for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on os os 12 at New Delhi by

Delhi Fire Service

To,

1

Addl. Commissioner of Police, Licensing Unit, 1<sup>st</sup> Floor, PS Defence Colony, Delhi.

Copy to:

Shri R.K. Bhasin, Manager, Pushpa Devi Bagrodia Dharamshala, PSP Area-3, Sector-5, Rohini, Delhi.

Following fire safety directives must be adhered to:-

- a) All the fire safety management provided their in shall be maintained in good working conditions at all time.
- b) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- c) The trained fire fighting staff should be available round the clock.
- d) Any deviation, with regards to construction etc. shall be verified by the concerned building sanctioning agency.
- e) The basement shall be used strictly as per the provision of building bye-laws.
- f) The certificate cannot be treated in any case for regularisations of unauthorised construction / unauthorised of land if any.
- g) Thre owner/ occupier shall submit a declaration every ear in form 'K' provided in the first schedule of Delhi Fire Service Ruels, 2010. This is available on www.dfs.delhigovt.nic.in.

May kindly see the letter No.61131/Addl.C.P./Lic.(H) dated 13,12,2011 received from Addl. Commissioner of Police, Licensing unit, Delhi regarding the revewal of NOC from fire safety point of view in espect of Pushpa Devi Bagrodia Dharamshala at PSP Area-3, Sector-5, Rohini, Delhi. Wherein earlier NOC was issued vide letter No. F.6/DFS/MS/09/368 dated 06.02.2009. Premises was re-inspected by the ADO (WP) on 15.01.2012 & observed that the building is comprised of ground & two upper floors only having plot area 2000 sq meters approximately and covered area is 500 sq. meters.

The point wise compliance of the safety recommendations as per the Delhi Fire Service Act, 2007 and Delhi Fire Service Rules, 2010 are given below:

## **INSPECTION REPORT**

1.	Name &address of the building	:	Pushpa Devi Bagrod	lia Dhasamshals, 8	OSP Asea-3, Sec-5, Ro
2.	Type of Occupancy	;	Assembly Group	A Residential F	Broldings
3.	Type of Case	:	Renewal Case Col		
4.	Details of previous NOC	:	F.6 DFS MS 09 368	Dated 06:02.20	No 9
5.	Fire Safety directives letter No.	:	Nh		
6.	Date of inspection	:.	15.01.2012		
7.	Name of the Inspecting Officers	:_	Mr. Rajmal Khokho	w, ADO(WA)	
8.	Name and designation of officers From the building side	:_	Mr. R. K. Bhasin,	Manefor	
9.	Year of Construction	:_	Year 1998 Cold Bldy	s).	
10.	Applicant's letter No.	:_	61131/Addi CP/Lic(H)	dated 13.12.201	1
S.	Minimum Standards on fire Prevention and fire safety U/R 3.	3	NBC Requirement	Provided at site	Remarks MR/NMR

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC Requirer		Provided at sit	te Remarks MR/NMR
1.	Access to building	NOC	alstody	issued to	Josenuses
	Road width	50	J		
	Gate width	,			
	Width of internal road				
2.	Number, Width, Type & Arrange	ment of Exits		1	
	a. Number of staircases				1
	Upper Floors				
	Basement	æ			
	b. Width of staircases				
	• Upper Floors				
	Basement				
	c. Protection of exits	g.			
	Fire check door		1		
	• Pressurization				

	d. No. of continuous staircas	ses		
0	to terrace			
	e. Width of Corridor			
3.	f. Door size			
J.	Compartmentation.			1
	<ul> <li>Fire check door</li> </ul>			
	Sealing of electrical shaft:	NR	NP	
	Fire Rating of shaft door	NR	NP	-
	Water Curtain	NR	NP	
	• Fire Dampers	NR	NP	7
4.	Smoke Management System.	NR	NP	
	amore management System.			
	• Basements	NR	0	
	<ul> <li>Upper floors</li> </ul>		NP	
5. F	Fire Extinguishers	NR	NP	
	The Extinguishers			
	• Total numbers		20 Provided	mR.
,	• Types		10 ABC Type 10 Con Type	
	IS marking	ISI marked		ml
Fi	irst-Aid Hose Rees.		151 Marked	MR
	- T 1		one each floor	# 1
	• Total numbers on each floor		and one on Tessare	mR.
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Bom	mR
•	1,02210 diameter	5 mm	5 mm	mR
Au	itomatic fire detection and alar	ming system.		
	Type of detectors			
		NR	NP	
	Location of Main Panel	NR	NP	
_	L COOtton - CD		0	
•	Location of Repeater Panel	NR	NP	-
•	Alternate source of power Hooter's Location	NR	NP	

8.	MOEFA	Repuised	Provided	mr
9.	Public Address System.	Repuised	Provided	MR
10.	Automatic Sprinkler system			
	Basement	NA	NP	
	Upper Floor	NR	NP	-
	<ul> <li>Sprinkler above false ceiling</li> </ul>	NA	NP	_
1.	Internal Hydrants			
	Size of riser/down-comer	100 mm	Provided	mp.
	Number of hydrants per floor	one on each floor & our	Provided	ma
	Hose Box	one on each floor & one on tersace	Provided	nd.
2.	Yard Hydrants.		, , , , , , , , , , , , , , , , , , ,	
	<ul> <li>Total number of hydrants</li> </ul>	one No	Provided	mR
	Hose Box	One No	Provided Provided	mR
3.	Pumping Arrangements.			
	Ground Level	MR	MP	•
9	<ul><li>Discharge of main pump</li><li>Head of Main pump</li></ul>	NR	NP	) -
	<ul><li>Head of Main pump</li><li>Number of main pumps</li></ul>	NR	NP	
		NR	NP	-
	Jockey Pump out put	NR	NP	
	Jockey pump head	NR.	NP	-
	Standby pump out put	NR	NP	· ~
8	> Standby pump Head	NR	NP	
	Auto Starting/Manual stopping	NR	NP	-
	➤ Pump Hose Access	MR	NP	~
	Terrace level	Regused	Provided	mR.
	Discharge of pump	900 Lpm & 180 Lpm as Jockey	Provided	mR
	➤ Head of the pump	40 mby	Provided	m R.
	Power supply	NR	NP	•
	> Auto Starting of pump	NR	NP	

n

. (	Captive Water Storage for fire figh	ting.		
1	T. I	50,000 litres	Provided	md
1	Underground tank capacity	MR	NP	
5.	> Draw -off connection	NR	NP	-
	> Fire service inlet	NR	NP	•
	> Access to tank		Pronded	ma
5	> Overhead Tank Capacity  Exit Signage.	12,500 litres Repuired	Provided	mR
.5	Exit Signage.	Require		
16.	Provision of Lifts	210	NP	_
	Pressurization of Lift Shaft	NR	NP	57
8	Pressurization of Lift lobby	MR	Nr	-
	Communication In lift Car	NR	NP	<b>10</b>
	Fireman's Grounding  Switch	NR	NP	
	<ul><li>Switch</li><li>Lift Signage</li></ul>	NR	MP	-
17.	Standby power supply	MR	NP	•
18.	Refuge Area	141-		5
10.	Terruge Tries.		0	# F
	> Total Area	MR	NP	
	> Location	NR	NP	
19.				
	> Detector System Panel	NR	NB	
	> Flow Switch Panel	NR	NP	
	> PA system Panel	NR	MB	_
	> Batter backup	IVR	MP	-
	Building Floor plans	NR	NP	
20	O. Special Fire Protection Systems for Protection of special Risks, if any	101	иA	

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial number.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name

SHRI RATMAL KHOKNAR

Name

Designation

ASSTT. DW. OFFICER

Disignation