## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. FEIDASIMS/ 2012/94/ 864

## FIRE SAFETY CERTIFICATE

- 1. Means of escape shall not be kept locked or bolted from outside and shall be easily open able by guests in an event of emergency.
- 2. All employees shall be acquainted with the use and maintenance of all the fire fighting installation/equipments.
- 3. The fire suppression / protection arrangements provided in the guest house are to minimize losses, if maintained in good working condition. These systems cannot give any guarantee that there will be no fire or losses in the event of one.
- 4. Any loss of life and property due to non-functional of fire safety arrangements and other installations shall be the responsibility of the licensee.
- 5. This report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

Chief Fire Officer
For Director
Delhi Fire Service

Dated: 09/03/2012

Copy to:

- 1. The Additional Commissioner of Police (Lic), 1st 13or, Police Station, Defense Colony, New Delhi w.r.t letter No 7890/Addl. C.P. /ILic. (H) Dated 08/02/2012.
- 2. Smt Manjeet Kaur, National Lodge Guest House, 24-A/7880, Arakashan Road, Paharganj, New Delhi

## INSPECTION REPORT

	1. Name & address of the building	: Na Paka	tional lodge	24-A/7880, A	abashan Road
	2. Type of Occupancy	: /	Quest House		
			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
	3. Type of Case	: New C	ase / Ren	newal	
2	4. Details of previous NOC	: Letter N	No. F6/DFs/ms/G	CH/2w9/1359 Date	d: 18/5/2009
1	5. Fire Safety directives letter No	•			
(	6. Date of inspection	: 21/	102/2012		,
	7. Name of the Inspecting Officers	: A2	D. S. Yada	NEDO. Ata	il Golg
8	3. Name and designation of officer	`S			
	from the building side	:	h Vinod kee	mar Manage	er
Ç	). Year of Construction	:	1999		
The state of the s	0. Applicant's letter No.	: 78	90   Add  . CP.,	(Lie (H) dtd	8/2/12
lo.	Minimum Standards on fi prevention and fire safety U/		NBC Requirement	Provided at site	Remarks MR/NMR
	Access to building			1	
	<ul> <li>Road width</li> </ul>		6 M	Privided	m/R
	• Gate width		_		_
	• Width of internal road		6 M	Prided	m/R
8	Number, Width, Type & Arrang	gement o	f Exits		
	a. Number of staircases		one gliss mir	Provided	MR
	• Upper Floors	-	-//-	-//-	-// -
	Basements				

	b. Width of staircases	125MT-	1.22 to 1.25 m/r	MA
	Upper Floors	-1/ -	- (/	MR
	• Basements	_	_	
3	c. Protection of exits			
	Fire check door	N/A	NP	MA
	<ul> <li>Pressurization</li> </ul>	-"-	- " -	2 11 20
	e. No. of continuous staircases to terrace	one	Prinched	m/R
	g. Width of Corridor	_		-
	h. Door Size	1 mtr	Princed	m/R
3	Compartmentation.	NR	MP	NA
	Fire check door			
	<ul> <li>Sealing of electrical shafts</li> </ul>	_		
	• Fire Rating of shaft door			1
	Water Curtain			
	Fire Dampers	_	_	_

	4	Smoke Management System.			
		• Basements	30 a/c per hour	_	
		• Upper floors	12 a/c per hour	_	
	5	Fire Extinguishers		L	
		Total numbers		10 Nos	MK
		<ul><li>Types</li></ul>	ISI marked	SABC SCOL	MR
		IS marking		yes	yes
	6	First-Aid Hose Reels.			
		Total numbers on each floor		Privided en each floor	MIR
		<ul> <li>Length of hose reel hose</li> </ul>	30 m	yes	yes
		Nozzle diameter	5 mm	yes	yes
And the state of t	7	Automatic fire detection and alarming	system.		
and profession and the second second second second second second second second		Type of detectors	NK	NP	MA
		<ul> <li>Location of Main Panel</li> </ul>	_		
		<ul> <li>Location of Repeater Panel</li> </ul>			-
		Alternate source of power	Regel	30 KVA DG set Privided	MR
Andrew Statement and the statement of th	9	Hooters' Location		_	
	8	MOEFA	Regd	Princel	MM
	9	Public Address System.			

10	Automatic Sprinkler System.	N/R	NP	MA
	Basement			_
	Upper Floor	_		_
	Sprinkler above false ceiling		~	~
The second	Internal Hydrants	MR	NP	NA
	Size of riser/down-comer		_	
	Number of hydrants per floor		_	
	Hose Box	- ,	-	_
12	Yard Hydrants.			
	Total number of hydrants	_	~	_
	<ul> <li>Hose Box</li> </ul>		_	_
13	Pumping Arrangements.	1 2 302		
r	Ground Level	_	_	
	Discharge of main Pump		_	
	Head of Main pump		_	_
	Number of main pumps	_	~	_
	Jockey Pump out put	enter the state of	~	
	> Jockey pump head	_	-	
	> Standby Pump out put	and the second	~	_
	> Standby Pump Head			

•	SP.	Auto Starting/ Manual stopping		1		
		Pump House Access				
		Terrace level				
	e V	Discharge of pump	450 LPM	Prided	m/k	
		Head of the pump	40 M	UO M	m/R	
		Power Supply		_		
		> Auto Starting of pump	2	_		
14	Capti	ve Water Storage for fire fighting.	N/R	NP	NA	
		Underground tank capacity		_	_	
	*	Draw-off connection	_	_	_	-
	<b>&gt;</b>	Fire service inlet	-		_	
	>	Access to tank		-		
	•	Overhead Tank capacity	2500 Itr	Porided	MR	
			1			

15	Exit Signage.	Regd	Previded	MR
16	Provision of Lifts.	N/R	Priced	ma
	Pressurization of Lift Shaft		~	_
	<ul> <li>Pressurization of Lift lobby</li> </ul>	_		
	Communication In lift Car		-	
	Fireman's Grounding Switch		Priviled	MAK
	Lift Signage	_	- // -	- 11-
17	Standby power supply	Regd	30 KVA DG set	m/K
18	Refuge Area.	MARCH ALL	NAP	w/A
	> Total Area	- N.A		
2	> Location	· Otoka		
19	Fire Control Room			
	Detector System Panel	- N.A		
2	• Flow Switch Panel			
	PA System Panel	and the second	_	
	Batter backup		~	
	Building Floor Plans		_	
20	Special Fire Protection Systems for Protection of special Risks, if any:	ar armaba a	_	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of the Inspecting Officer

Name D.S. yadav

Designation Assistant Divisional

Officer

Name ATULGARS

Designation DD/CC