## FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35]

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/EH/2012/738

Dated: 02 / 03 /2012

## **FIRE SAFETY CERTIFICATE**

Chief Fire Officer Delhi Fire Service

de

Copy to:

M/s Lee Pacific Restaurant

31/35 First floor & Second floor

Rohtak Road, West Punjabi Bagh New Delhi

Note:- For general fire safety directives please over leaf.

May Kindly peruse letter no. D-1533/DH/WZ dated 04-11-2011 received from DHO regarding of NOC in r/o M/s Lee Pacific Restaurant at 31/35 F.F. & S.F Rohtak Road West Punjabi Bagh New Delhi. Premises was inspected by the undersigned & observed that building is constructed on a plot area measuring 464.503 sq. mtr, comprising B + stilt + UG + Ist + IInd floor. Height of the bldg. is more than 10 mtr, but not exceeding 15 metrs. Fire safety arrangements are put up on the prescribed Performa.

1. Name & address of the building : M/s Lee Pacific Restaurant at 31/35 F.F. & S.F

Rohtak Road West Punjabi Bagh New Delhi.

2. Type of Occupancy : (Assembly)

3. Type of Case : New

4. Details of previous NOC : Nil

5. Fire Safety directives letter No. : Nil

6. Date of inspection : 22-02-2012

7. Name of the Inspecting Officers : Divisional Officer Sunil Chowdhary

8. Name and designation of officers

From the building side : Mr. Shankar Bansal

9. Year of Construction

10. Applicant's letter No. : D-1553/HD/WZ

## **INSPECTION REPORT**

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building				
	Road width	6 mtrs	9 mtrs	MR	
	Gate width	4.5 mtr	6 mtr	MR	
	Width of internal road	N.R.	N.R.	MR	
2.	Number, Width, Type & Arrange	ement of Exits			
	a. Number of staircases	2	P	M.R	
	Upper Floors	2	P	M.R	
	Basement	2	2	M.R	

	b. Width of staircases					
	Upper Floors	1.5 mtrs	Provided	M.R		
	• Basement	1.5 mtr	Provided	MR		
	c. Protection of exits					
	Fire check door	Required	Provided	M.R		
	<ul> <li>Pressurization</li> </ul>	N.R.	Ņ.R.	M.R		
	d. No. of continuous staircases to terrace	2	2	M.R.		
	e. Width of Corridor	Halls only	Halls only	M.R.		
	f. Door size	2 mtrs & 1.5 mtr	Provided	M.R.		
3.	Compartmentation.	== .	7	,		
	Fire check door	Required	Provided	M.R.		
	• Sealing of electrical shafts	N.A.	N.A.	Not applicable		
	• Fire Rating of shaft door	N.R.	N.R.	Not applicable		
	Water Curtain	N.R.	N.R.	Not applicable		
	• Fire Dampers	N.R.	N.R.	Not applicable		
4.	Smoke Management System.					
	Basements	Required	Exhaust Fan Provided	M.R		
	• Upper floors	N.R.	N.R.	NR		
5.	Fire Extinguishers					
	Total numbers	20	22	M.R		
	• Types	Co2 ABC type	Provided	M.R		
	• IS marking	ISI marks R	Provided	MR		

6.	First-Aid Hose Rees.				
	Total numbers on each floor	one	One	M.R	
	Length of hose reel hose	30 m Required	Provided	MR	
	Nozzle diameter	5 mm Required	Provided	M.R	
7.	Automatic fire detection and alar	ming system.			
	Type of detectors	Smoke & heat	Provided	MR	
	Location of Main Panel	G floor	Provided	MR	
	Location of Repeater Panel	Each floor	Provided	MR	
	Alternate source of power	Required	Provided	MR	
	Hooter's Location	Required	Provided	MR	
8.	MOEFA	Required	Provided	M.R	
9.	Public Address System.	N.R.	N.R	M.R	
10.	Automatic Sprinkler system				
	Basement	Required	Provided	MR	
	• Upper Floor	N. R.	Provided	MR	
	Sprinkler above false ceiling	Required	Provided	MR	
11.	Internal Hydrants				
	Size of riser/down-comer	100 mm 1	Provided	MR	
	Number of hydrants per floor	1	Provided	M.R	
	Hose Box	1	Provided	MR	

_					
14.	Captive Water Storage for fire fighting.				
	Underground tank capacity	50,000 ltrs	50,000	M.R	
	> Draw -off connection	Required	Provided	MR	
	Fire service inlet	Required	Provided	MR	
	> Access to tank	Required	Provided	MR	
	<ul><li>Overhead Tank Capacity</li></ul>	10, 000 ltrs	Provided	M.R	
15	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts	N.A.	N.A.	Not applicable	
	Pressurization of Lift Shaft	N.A.	N.A.	Not applicable	
	Pressurization of Lift lobby	N.A.	N.A.	Not applicable	
	Communication In lift Car	N.A.	N.A.	Not applicable	
	Fireman's Grounding     Switch	N.A.	1 - 1 - N.A.	Not applicable	
	Lift Signage	N.A.	N.A.	Not applicable	
17.	Standby power supply	Required	Provided	MR -	
18.	Refuge Area				
	> Total Area	N.R.	N.R.	Not applicable	
	> Location	N.R.	N.R.	Not applicable	
19.	Fire Control Room	a	2 N <sub>2</sub> 1 2		

		I		1
	> Detector System Panel	N.R.	N.R.	Not applicable
	Flow Switch Panel	N.R.	N.R.	Not applicable
	PA system Panel	N.R.	N.R.	Not applicable
	➤ Batter backup	N.R.	N.R.	Not applicable
	Building Floor plans	N.R.	N.R.	Not applicable
20.	Special Fire Protection Systems	N.R.	ND	N.4 11-
20.	for	IN.K.	N.R.	Not applicable
	Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Sumil Chaw dhasy

Name

Designation

D. O.

Designation