GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT LANE NEW DELHI-110 001.

No. F6/OFS/as/school/2012/344

Dated: 02/02/12

FIRE SAFETY CERTIFICATE

Certified that the M.C. PRIMARY SCHOOL located at Ladpur, Delhi-110 081, comprised of ground plus one upper floor only and less than 9 meters in height, have complied with the fire prevention and fire safety requirement in accordance with Director of Edcuation circular dated 01.03.2001 and verified by the officer concerned of fire service on 23.01.2012 in the presence of Shri Sandeep Kumar Mor, Principal and that the building/ premises is fit for occupancy class Educational class with effect from or location of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ______ at New Delhi by

Director
Delhi Fire Service

Shri Sandeep Kumar Mor, Principal, M.C. PRIMARY SCHOOL, Ladpur, Delhi-110 081.

Copy to:

The Director,
Dte. Of Education,
Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

INSPECTION REPORT

the

PRIMARY BOYS SCHOOL, LADRIR, DELHI-81 1. Name &address of the building SCHOOL Type of Occupancy NEW CASE Type of Case N.A. 4. Details of previous NOC 3298-3398 Dt. 1-3-2091 5. Fire Safety directives letter No. Date of inspection KHOKHAR RAJMAL Name of the Inspecting Officers SHRI . ADO 7. 8. Name and designation of officers SONDEED RUMAR MOR, PRINCIPAL From the building side 2010 9. Year of Construction 15/12/11 10. Applicant's letter No. satisf No. 1

			()		
S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building				
	Road width	Accessible	Access, ble	MR.	
	• Gate width	u			
	Width of internal road	-	-	D	
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	Two	Two	mR.	
	 Upper Floors 	50		· · · · ·	
	• Basement	······································	-	-	
	b. Width of staircases	150 Cms	170 cms each	mr	
	 Upper Floors 	- « « · · · · · · · · · · · · · · · · ·		-u_	
	• Basement	_	_	_	
	c. Protection of exits	_	_		
	• Fire check door	_	+		
	 Pressurization 	-	_	_	
	d. No. of continuous staircases to terrace	Timo	Times	mr	
	e. Width of Corridor	15 Melus	2 1 Melens	mr.	
	f. Door size	Single Door	Double Dorr 105cm each	mR	

1.	Compartmentation.	NA		
Y.	Fire check door	-		
	Sealing of electrical shafts		*	
	Fire Rating of shaft door	0-	1,2	*
	Water Curtain	•	-	-
	Fire Dampers	-		*
4.	Smoke Management System.		NA	
	Basements			
	Upper floors	-		
	copper floors	_	, —	-
5.	Fire Extinguishers		Provided	
	Total numbers		4 - 5 Kg	mR
	• Types	9	2 - 3kg	11112
			ABC Type	
	IS marking	ISI marked	151 Marked	- 11-
6.	First-Aid Hose Rees.	NA		
	Total numbers on each floor		6	-
	Length of hose reel hose	30 m		*
	Nozzle diameter	5 mm		
7.	Automatic fire detection and alar	ming system.	NA	
	Type of detectors	~	~	-
	• Location of Main Panel	•		en en
	Location of Repeater Panel	→	, <u> </u>	· ·
	Alternate source of power		_	-
	Hooter's Location		F	•
8.	MOEFA	•	NA	~
9.	Public Address System.	Required	Pronded	MR

		NA	
Basement	**		
Upper Floor	_	-	
Sprinkler above false ceiling		_	_
Internal Hydrants	Χ.	N.A.	*
			ė.
	-	~	6
Number of hydrants per floor	5	6	+
Hose Box	<u>-</u>	-	-
Yard Hydrants.	N.A		
Total number of hydrants	4 ·	~	-
Hose Box	-	_	<u>_</u>
Pumping Arrangements.		N.A.	I
Ground Level			
Discharge of main pump	9		←
Head of Main pump	-	-	-
Number of main pumps			
Jockey Pump out put	-		
Jockey pump head	5		6
> Standby pump out put	-		-
> Standby pump Head	•	•-	-
> Auto Starting/Manual			·
	~	~	-
		-	-
	-	-	
	-	-	
	*		-
➤ Auto Starting of pump		_	_
	 Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby pump Head Auto Starting/Manual stopping Pump Hose Access Terrace level Discharge of pump Head of the pump Power supply 	• Sprinkler above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants. • Total number of hydrants • Hose Box Pumping Arrangements. Ground Level > Discharge of main pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby pump Head > Auto Starting/Manual stopping > Pump Hose Access Terrace level > Discharge of pump > Head of the pump > Power supply	• Upper Floor • Sprinkler above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants. • Total number of hydrants • Hose Box Pumping Arrangements. Ground Level > Discharge of main pump > Head of Main pump > Jockey Pump out put > Standby pump head > Standby pump Head > Auto Starting/Manual stopping > Pump Hose Access Terrace level > Discharge of pump > Head of the pump > Head of the pump > Power supply

4.	Captive Water Storage for fire fight	ing.	NA	
2	Underground tank capacity	-		
	> Draw -off connection	•	- '	,
	> Fire service inlet	-	-	
	> Access to tank	•	· -	-
	> Overhead Tank Capacity	bon.	_	
15	Exit Signage.	Repured	fromded	mR
16.	Provision of Lifts			
	Pressurization of Lift Shaft		-	7
	Pressurization of Lift lobby	~	~	
3	Communication In lift Car	•	_	1
	• Fireman's Grounding Switch	_		-
	Lift Signage	-	-	_
17.	Standby power supply		PA.	
18.	Refuge Area			
	> Total Area	•	-	-
	> Location	£	-	-
19.	19. Fire Control Room NA			
	> Detector System Panel	•		~
	➤ Flow Switch Panel	-		_
v	PA system Panel		-	-
	➤ Batter backup		-	-
	Building Floor plans	-		_
20.	Special Fire Protection Systems for Protection of special Risks, if any:	•	-	

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial number.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name SHRI RAJMAL KHOKHAR

Name

Designation ASSTT. DIV. OFFICER

Disignation

50 (Ny)