FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE
[SEE SUB-RULE (1) OF RULE 35]
GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. f6/065/ms/2012/983

Dated:20 / 63/2012

## FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

ole

Copy to:

Mr. S.M. Rishi, Chief Safety Officer PARSVNATH METRO MALL,

Inder Lok, New Delhi

Note:- For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on <a href="www.dfs">www.dfs</a>. delhigovt. nic.in

May Kindly peruse letter no. BPPL/HO\_Corp./2011-2012 dated 06/02/2012 received from Authorized Signatory regarding of NOC in r/o Parsvnath Metro Mall, located at Inder Lok, New Delhi. premises was inspected by the undersigned & the fire safety arrangements are put up on the prescribed Performa

1. Name &address of the building : PARSVNATH METRO MALL, located at Inder Lok,

New Delhi.

2. Type of Occupancy : Class –F (2) (Mercantile)

3. Type of Case : Renewal

4. Details of previous NOC : Nil

5. Fire Safety directives letter No. : F-6/DFS/MS/BP/2003/2634 dated 24.10.2003

6. Date of inspection : 05-03-2012

7. Name of the Inspecting Officers : A.D.O. Rajmal Khokhar & D.O. Sunil Chawdhary

8. Name and designation of officers

From the building side : Mr. S.M. Rishi, Chief Safety Officer

9. Year of Construction : 1999-2000

10. Applicant's letter No. : nil

## **INSPECTION REPORT**

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL/BBL Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building	<u> </u>			
	Road width	12mtrs	60mtr.	M.R	
×	• Gate width	4.5 mtr	5 mtr	M.R	
	Width of internal road	6 mtr	10 mtr	M/R	
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases				
	• Upper Floors	5	5	M.R.	
	Basement	N.A.	N.A.	N.A.	

	b. Width of staircases			
	Upper Floors	1.5 mtr	Provided	M.R.
	Basement	N.A.	N.A.	N.A.
	c. Protection of exits			
	Fire check door	Required	Provided	M.R
50	Pressurization	Required	Provided	M.R
	d. No. of continuous staircases to terrace	05	05	M.R
	e. Width of Corridor	2.4	3 mtr	M.R.
	f. Door size	2 mtrs	2.5 mtrs	M.R.
3.	Compartmentation.			
	Fire check door	Required	Provided	M.R
	Sealing of electrical shafts	Required	Provided	M.R
	Fire Rating of shaft door	Required	Provided	M.R
	Water Curtain	Required	Provided	M.R
	Fire Dampers	Required	Provided	M.R
4.	Smoke Management System.			
×	• Basements	N.A.	N.A.	N.A.
	• Upper floors	Required	Provided	M.R.
5.	Fire Extinguishers			
	Total numbers	50	65	M.R
	• Types	ABC & CO <sub>2</sub> type	provided	M.R
	ISI marking	ISI marked	provided	M.R

6.	First-Aid Hose Rees.					
	Total numbers on each floor	3	Provided	M.R		
	Length of hose reel hose	30 m	Provided	M.R ~		
	Nozzle diameter	5 mm	Provided	M.R		
7.	Automatic fire detection and alarming system.					
	Type of detectors	Required	Provided	M.R.		
	Location of Main Panel	Ground floor	Provided	M.R.		
	Location of Repeater Panel	Each floor	Provided	M.R.		
	Alternate source of power	Required	Provided	M.R.		
	Hooter's Location	Required	Provided	M.R.		
8.	MOEFA	Required	Provided	M.R.		
9.	Public Address System.	Required	Provided	M.R.		
10.	Automatic Sprinkler system					
	Basement	N.A.	N.A.	Not applicable		
	Upper Floor	Required	Provided	M.R.		
	Sprinkler above false ceiling	Required	Provided	M.R.		
11.	Internal Hydrants			1		
	Size of riser/down-comer	150 mm	Provided	M.R.		
2	Number of hydrants per floor	3	Provided	M.R.		

5.

	Hose Box	3	Provided	M.R.
12	Yard Hydrants.		19	
	Total number of hydrants	Required	Provided	M.R.
	Hose Box	Required	Provided	M.R.
13.	Pumping Arrangements.			
	Ground Level			
	Discharge of main pump	2280 LPM	Provided	M/R
	Head of Main pump	70 mtr	Provided	M/R
	Number of main pumps	2	Provided	M/R
	Jockey Pump out put	180 LPM	Provided	M/R
	Jockey pump head	70 mtr	Provided	M/R
	Standby pump out put	2280 LPM.	Provided	M/R
	> Standby pump Head	70 mtr	Provided	M/R
5.	Auto Starting/Manual stopping	auto	Provided	M/R
	► Pump Hose Access	Required	Provided	M/R
	Terrace level			
	Discharge of pump	900 LPM	Provided	M.R
	➤ Head of the pump	45 mtr	provided	M.R
	> Power supply	Required	Provided	M.R
	<ul><li>Auto Starting of pump</li></ul>	Required	Provided	M.R.

Underground tank capacity	1,40,00 ltrs	provided	M.R.
> Draw -off connection	required	provided	M.R.
➤ Fire service inlet	required	provided	M.R.
> Access to tank	required	provided	M.R.
Overhead Tank Capacity	1,40,000 ltrs	provided	M.R
Exit Signage.	Required	Provided	M.R.
Provision of Lifts	N.R.	N.R.	Not applicable
Pressurization of Lift Shaft	Required	Provided	M.R.
Pressurization of Lift lobby	Required	Provided	M.R.
Communication In lift Car	required	provided	M.R.
Fireman's Grounding     Switch	required	provided	M.R.
Lift Signage	required	provided	M.R.
Standby power supply	Required.	Provided	M.R
Refuge Area	N.R.	N.R	Not applicable
> Total Area	N.R.	N.R.	Not applicable
> Location	N.R.	N.R.	Not applicable
Fire Control Room	Required	provided	M.R.
> Detector System Panel	Required	provided	M.R.
➤ Flow Switch Panel	Required	provided	M.R.
> PA system Panel	Required	provided	M.R.
	<ul> <li>▶ Draw -off connection</li> <li>▶ Fire service inlet</li> <li>▶ Access to tank</li> <li>▶ Overhead Tank Capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area</li> <li>▶ Total Area</li> <li>▶ Location</li> <li>Fire Control Room</li> <li>▶ Detector System Panel</li> <li>▶ Flow Switch Panel</li> </ul>	▶ Draw -off connection       required         ▶ Fire service inlet       required         ▶ Access to tank       required         ▶ Overhead Tank Capacity       1,40,000 ltrs         Exit Signage.       Required         Provision of Lifts       N.R.         • Pressurization of Lift Shaft       Required         • Pressurization of Lift lobby       Required         • Communication In lift Car       required         • Fireman's Grounding Switch       required         • Lift Signage       Required         Standby power supply       Required.         Refuge Area       N.R.         ▶ Total Area       N.R.         ▶ Location       N.R.         Fire Control Room       Required         ▶ Detector System Panel       Required         ▶ Flow Switch Panel       Required	➤ Draw-off connection       required       provided         ➤ Fire service inlet       required       provided         ➤ Access to tank       required       provided         ➤ Overhead Tank Capacity       1,40,000 ltrs       provided         Exit Signage.       Required       Provided         Provision of Lifts       N.R.       N.R.         • Pressurization of Lift Shaft       Required       Provided         • Pressurization of Lift lobby       Required       Provided         • Communication In lift Car       required       provided         • Fireman's Grounding Switch       required       provided         • Lift Signage       Required       Provided         Standby power supply       Required       Provided         Refuge Area       N.R.       N.R.         N.R.       N.R.       N.R.         ➤ Total Area       N.R.       N.R.         ➤ Location       Required       provided         ➤ Detector System Panel       Required       provided         ➤ Flow Switch Panel       Required       Provided

		Required	provided	M.R.
2	➤ Batter backup		*	
	Building Floor plans	Required	provided	M.R.
20.	Special Fire Protection Systems for	N.R.	N.R.	Not applicable
	Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

Signature of the Inspection Officer

Name RAJMAL KHOK MAR

Name

Designation

Designation A.D.O