GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/0/5/ans/school/2012/1004

Dated 20/03/12

FIRE SAFETY CERTIFICATE

Issued on.....2.0./ 9.3./1.2.....at New Delhi by

Chief Fire Officer
For Director
Delhi Fire Service

To

Principal
Govt. Girls Sr. Sec. School,
ShivaJi Park, Shahdara, Delhi-32

Copy to:-

- Govt. Boys Sr. Sec. School, ShivaJi Park, Shahdara, Delhi-32
- The Joint Director of Education (Land & Estate)
 Directorate of Education, Lucknow Road, Delhi -54.

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

				45
	INSPECT	TION REPORT		
	Ray	Kinga Senior S	ceondan girk Se	hool
1	Name & address of the building : G	SCS Shiva	ji Park, Shaha	edra
2				
3	Type of Case : New Ca	ase/ Renewal		
4	Details of previous NOC : Letter N	No	Date	d:
5	Fire Safety directives letter No : 15-16	Estate (c) F	ire Salely / 2011/3:	298 63398
6	5. Fire Safety directives letter No: 16/Estate Cc Fire Safety 2011 3298 to 3399 6. Date of inspection 1:3-2011			
7		o Suresh	Singh	
8		je ,		
	from the building side : Mrz	Saray Jain	Vice Prin	g pal
9	Year of Construction : 197	0, 2011		
. 10			10.1.2012	
S.	Minimum Standards on fire	NBC	Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMR
1	Access to building			1
	Road width	6 M	6 M	MR
	Gate width		3.80 H	4
	Width of internal road	-	5	- Z
2	Number, Width, Type & Arrangement	of Exits	2	L
	a. Number of staircases	4	4	HR.
	Upper Floors	4	4	MIR
-	Basements			
	b. Width of staircases	1.50 A	1.50 H	MER
	Upper Floors	02.1	1.50 4	MIR
	Basements			
	c. Protection of exits			
	Fire check door			
	Pressurization		1	
	e. No. of continuous staircases to terrace		•	
	g. Width of Corridor	1.50.	1:50	MIR
	h. Door Size	1	1 1 N	MR

		* 19		
			0	
	£	5		
3	Compartmentation.	ŧ	-	
	Fire check door			
	 Sealing of electrical shafts 		1 ~	_
	Fire Rating of shaft door			
	Water Curtain			-
	• Fire Dampers			~
4	Smoke Management System.	MIA		-1
	• Basements	30 a/c per hour		
	Upper floors	12 a/c per hour	, , , , , , , , , , , , , , , , , , , ,	
5	Fire Extinguishers	Regulared		·
	Total numbers	1) HO	11 110	MR
	• Types	E	CA2+ ABC	MR
	IS marking	ISI marked	12)	MIR
6	First-Aid Hose Reels.	NIA		
	Total numbers on each floor			
	Length of hose reel hose	30 m		
	Nozzle diameter	5 mm		
7	Automatic fire detection and alarming s	system. 14A		
	Type of detectors		,	
	Location of Main Panel	_		
	Location of Repeater Panel			-
	Alternate source of power		,	
	Hooters' Location			
8	MOEFA	1414		
9	Public Address System.		Yes	
10	Automatic Sprinkler System.	NIA		
	Basement	•		
				

Γ	:	-	- The sales of	
	• Upper Floor			
	Sprinkler above false ceiling		-	1
11	Internal Hydrants	MA		Mari J
	Size of riser/down-comer			
	Number of hydrants per floor			~
	Hose Box		•	~
12	Yard Hydrants.	1114		
	 Total number of hydrants 			~
	Hose Box			
13	Pumping Arrangements.	(414	я .	
	Ground Level			
	Discharge of main Pump			
	➤ Head of Main pump	(Management over 1	^	
	Number of main pumps			
	> Jockey Pump out put			
	> Jockey pump head			
	Standby Pump out put			
	Standby Pump Head	, ·		
	> Auto Starting/ Manual			
100	stopping			
	> Pump House Access	· ·	·	,
87	Terrace level			
· .	 Discharge of pump 			
	➤ Head of the pump			
	> Power Supply			
	Auto Starting of pump			
14	Captive Water Storage for fire fighting.	NIA		
	Underground tank capacity			
	> Draw-off connection			

	Fire service inlet			
	Access to tank			
	Overhead Tank capacity			
15	Exit Signage.	14.1A :		
16	Provision of Lifts.	HIA		
	Pressurization of Lift Shaft		-	
	Pressurization of Lift lobby			
	Communication In lift Car			
	• Fireman's Grounding Switch			
	• Lift Signage			
17	Standby power supply			
18	Refuge Area.	+114		
		+110	T	
	Total Area			
	> Location			
19	Fire Control Room	NIA		
c.	 Detector System Panel 		-	
Þ	 Flow Switch Panel 			
	PA System Panel		· ·	
	Batter backup			
	Building Floor Plans			7.
20	Special Fire Protection Systems for	/d /n		
8	Protection of special Risks, if any:	7 / 1		
		14 14		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer Signature of the Inspecting Officer Name Curest Sings Name Designation