GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/98-8/ms/5/2012/85/

FIRE SAFETY CERTIFICATE

Certified that the Nigam Pratibha Girls Vidayalaya no.1 at Mandawali Extn., Delhi-92. Comprised of ground plus one upper floor owned/occupied by M/s Nigam Pratibha Girls Vidayalaya have complied with the fire prevention and fire safety requirements in accordance with with the circular issued by the Director of Education dtd.01.03.2011and verified by the officer concerned of Fire Service on 24.2.2012 in the presence of Smt, Sarla Jain, Principal, of the school and that the building is fit for occupancy class B' Educational Building' with effect from .52./.03.//.2 for a period of three years , subject to conditions printed overleaf.

Issued on ______ at New Delhi by

Chief Fire Officer For Director Delhi Fire Service

To,

Principal
Nigam Pratibha Girls Vidayalaya no.1
Mandawali Extn.,Delhi-92
Copy:-

- The Director of Education MCD,Nigam Bhawan, Kashmiri Gate,Delhi.
- Principal
 Nigam Pratibha Boys Vidayalaya no.1
 Mandawali Extn., Delhi-92

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

MR

1.014

1:0 M

INSPECTION REPORT 1. Name & address of the building: NIgam fratibha Girls vidayalyon and awali Ertn. No. I, Type of Occupancy 2. Educational : New Case/ Renewal 3. Type of Case 4. Details of previous NOC 5. Fire Safety directives letter No: F16 Estate | cc | F5 | 2011 | 3298 to 3398 At 1.3.11 6. Date of inspection 24/02/12 7. Name of the Inspecting Officers: DO V/Bentra 8. Name and designation of officers Smt. Sarla Jain from the building side 9. Year of Construction 2009-10 10. Applicant's letter No. 14/11/11 del S. Minimum Standards on fire **NBC** Provided at site Remarks No. prevention and fire safety U/R 33 Requirement MR/NMR 1 Access to building 6. M Road width MR Gate width Width of internal road Number, Width, Type & Arrangement of Exits 2 a. Number of staircases 2 No.5. 2 25 MR Upper Floors 2 Nos 2 Nos. Basements b. Width of staircases 1.5 M 1.5 M MR Upper Floors 1.5 M 1.5 M MR Basements c. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terrace 1 No. 1 NO. 1 MR g. Width of Corridor 1.5 M 1.5 M MR h. Door Size

3	Compartmentation.	Tar A
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 	
4	Smoke Management System.	N.O
	BasementsUpper floors	30 a/c per hour 12 a/c per hour
5	Fire Extinguishers	
n 9 9	Total numbersTypes	6 NOS. 8 NOS. MR ABCL COZ MR
6	• IS marking	ISI marked 15/ marks ma
-	First-Aid Hose Reels.	NA
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m / / / / / / / / / / / / / / / / / /
7	Automatic fire detection and alarming	system. N
р п п	Type of detectorsLocation of Main Panel	
, š	Location of Repeater Panel	
•	Alternate source of power Hooters' Location	
8	MOEFA	NA
8	MOEFA Public Address System.	A A
	MOEFA Public Address System. Automatic Sprinkler System.	

:

	• Upper Floor	Α.
	Sprinkler above false ceiling	
11	Internal Hydrants	
	Size of riser/down-comer	
	Number of hydrants per floor	
	Hose Box	2 45
12	Yard Hydrants.	+
14	Total number of hydrants	
	Hose Box	
13	Pumping Arrangements.	
	Ground Level	
	> Discharge of main Pump	
	> Head of Main pump	
	> Number of main pumps	1
	> Jockey Pump out put	
	> Jockey pump head	
	> Standby Pump out put	
	> Standby Pump Head	
, "	> Auto Starting/ Manual	•
	stopping	
	> Pump House Access	
	Terrace level	
	> Discharge of pump	
	> Head of the pump	
ž	➤ Power Supply	
	> Auto Starting of pump	
14	Captive Water Storage for fire fighting.	:
	Underground tank capacity	
	> Draw-off connection	

	N f:	
	> Fire service inlet	
	> Access to tank	
	Overhead Tank capacity	
15	Exit Signage.	WA.
16	Provision of Lifts.	M.A.
	• Pressurization of Lift Shaft	
	Pressurization of Lift lobby	
	Communication In lift Car	
	 Fireman's Grounding Switch 	
	• Lift Signage	
17	Standby power supply	M. B.
18	Refuge Area.	MA harrist and harry
	> Total Area	
	> Location	
19	Fire Control Room	4.0
	Detector System Panel	
	Flow Switch Panel	
	PAi System Panel	
	Batter backup	
	Building Floor Plans	
20	Special Fire Protection Systems for	
	Protection of special Risks, if any:	

The fire protection systems provided in the building were test checked and found functional at the of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire so required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the I Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer Signature of the Inspecting Offi Virendra Singh Name Name Designation Designation