## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/MS/school/2012/853 Dated: 07/03/12

## FIRE SAFETY CERTIFICATE

Issued on 07/03/12 at New Delhi by

Chief Fire Officer For Director Delhi Fire Service

Principal Rajdhani Public School East Vinod Nagar,Delhi-91.

Copy:-

The Director of Education GNCT Of Delhi, Old Secretariat, Lucknow Road, Delhi -54.

## **CONDITIONS:**

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

1. Name & address of the building: Rajdhani Public School at East Vinod Nagar, Delhi -92.

2. Building is comprised of : Ground +1, upper floor.

3. Type of Occupancy

: Educational

4. Type of Case

: New Case

5. Details of Previous NOC letter :Nil

6. Fire Safety direction letter No : Circular Director of Education dated 1.3..11

7. Date of Inspection

: 12.1.12

8. Name of the Inspecting officers: DO Virendra Singh

9. Name and designation of Officer:

from the building side

: Smt. Kusam Sharma (Principal).

10. Year of Construction

-: 1984

11. Applicant's letter No : letter No.Nil dated 12.12.2011.

			- · · · · ·	<b>D</b> 1	
NO.	Minimum Standards on fire	Circular ~	Provided at	Remarks	
	prevention and fire safety U/R33	Requirement	Site	MR/NMR	
1	Access to building				
	Road width		20 Mtrs.	MR	
	Gate width		4 Mtrs.	MR	
	<ul> <li>Width of internal road</li> </ul>				
2	Number, Width, Type and Arrangement of Exits				
	a. Number of Staircases	02 Nos.	O2 Nos.	MR	
	Upper Floor	02 Nos	02 Nos.	MR	
	Basement				
	B. Width of Staircases	1.5 M	1.40m & 90 cm	MR	
	Upper Floor	1.5 M	1.40m & 90 cm	MR	
	Basement				
	c. Protection of exits				
	<ul><li>Fire check door</li><li>Pressurization</li></ul>				
	e. No. of continuous staircases to terrace		1No.	MR	
	a Midth of Couridor	1.5 mts.	1.5 mts	MR	
	g. Width of Corridor h. Door Size	1.0 Mtrs	1.0 Mtrs	MR	

2	Comportmentation				
3	Compartmentation.				
	Fire check door				
	Sealing of electrical shafts				
	Fire rating of shaft door		pays and		
	Water curtain				
	Fire Dampers				
4	Smoke Management System.				
	Basement				
	Upper floor				
5.	Fire Extinguishers				
	<ul> <li>Total numbers</li> </ul>	4 Nos.	4 Nos.	MR	
	• types	ABC & Co2	ABC & Co2	MR	
	IS marking	ISI marked	ISI marked	MR	
6	First-aid-Hose Reels.				
	Total numbers of each floor				
	<ul> <li>Length of hose reel hose</li> </ul>				
	Nozzle diameter		App. 400 100 100 100 100 100 100 100 100		
			and also dat dat day and day and day and the sale		
7	Automatic fire detection and alarming system.				
	Type of detectors				
	1 ypo or dotootoro				
	<ul> <li>Location of main panel</li> </ul>		was high table table table table paint plant plant steel steel		
	2 200ation of main pains.				
	<ul> <li>Location of repeater panel</li> </ul>			\ \	
	<ul> <li>Alternate source of power</li> </ul>				
	Hooter's location				
8	MOEFA				
9	Public address System.			CON 1920 CON 1920 TOTAL TOTAL TOTAL TOTAL TOTAL	
10	Automatic Sprinkler System.				
	Basement				
	upper floor				
	sprinkler above false ceiling				
11	Internal Hydrants				
' '	size of riser/down-comer		ages state state state state little little date state state state		
	Number of hydrants per floor	jan var sår sår sår sår sår sår sår sår til var			

	·			
	Hose Box			
40	Vard Hydrants			
12	Yard Hydrants.			
	Total number of hydrants			
	Hose Box			
13	Pumping Arrangements.			
	Ground Level		1	
	Discharge of main Pump			
	Head of Main Pump			
	Number of main pumps			
	Jockey pump out put			
	Jockey pump head			
	Standby pump out put			
	Standby pump Head			to be seen to the seen to be a
	> Auto Starting /Manual			
	stopping			
	> Pump House Access	Mark with this pair last state and tape and tape the tape the	No. and and the day the last two two two two	that also have been been used their state also
	Terrace Level			
			100 to 100 to 100 to 100 to 100 to 100 to	
	> Head of the Pump			
	Power supply	***		
	> Auto Starting of pump			
14	Captive Water Storage for Fire Fighting.			
	Underground tank capacity			
	➤ Draw-off connection	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~		
	> Fire service inlet			And died date have been been take take state along
	Overhead Tank capacity			
15	Exit Signage.			
16	Provision of Lifts.	1		
	<ul> <li>Pressurization of Lift Shaft</li> </ul>			
	<ul> <li>Pressurization of Lift lobby</li> </ul>			
	<ul> <li>Communication in lift car</li> </ul>	***		100 the life of th
	<ul> <li>Firemen's grounding</li> </ul>			
	switch			
-	Lift Signage		have been been toke about the date made and apply	
17	Standby power supply			
17				
18	Refuge Area.			
	Total area			
	Location			
19	Fire Control Room			

	Detector system panel	 	
	<ul> <li>Flow switch panel</li> </ul>	 Apr. 100. 100. 100. 100. 100. 100 100 100 1	year man man man man man man man man man
	<ul> <li>PA system panel</li> </ul>	 	
	Battery backup	 	and any loss (all the man and the test the
×	<ul> <li>Building Floor Plans</li> </ul>	 	
20	Special Fire Protection systems for protection of special Risks, if any:	 ,	

The fire extinguishers provided in the building were tested/ checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name Vinends Singh

Designation ADE