GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6 / DFS / MS / 2012 / $GH/I \sim \infty$

Dated 03/04/12

FIRE SAFETY CERTIFICATE

Chief Fire Officer
For Director
Delhi Fire Service

Copy to: -

- 1. The Addl. Comm. of Police (Lic) First Floor, Police Station, Defence Colony, New Delhi
- 2. The Manager, Punjab Guest house, at 669, Church Mission Road, Fateh Puri Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

Building covered under special area, L. No. F-6/ms/DBS/01/1795 dated 29-8-2001.

INSPECTION REPORT

1

1. Name & address of the building Run	njab Guest House	2,669, C.m. Road	1, Fatch Puri D
2. Type of Occupancy	esidencial		
3. Type of Case : N	ew Case/ Renewal		
4. Details of previous NOC : Le	etter No.F-6 ms DAsk	34/09/936 Date	ed: 6-4-2009
 5. Fire Safety directives letter No F. 6. Date of inspection : 5 	C/ms/DFS/GH/00	11999 Notel 2	11-7-200
6. Date of inspection : 5	13-3-2012	. F-6/ms/DI	PS/6/1/01/292/
7. Name of the Inspecting Officers:	ADO- SHYAM	1 LA2	19)
8 Name and designation of officers			
	h Suchaker S		
9. Year of Construction 19	48 Ground+3	Grito III raffe	or-73 Reoms
10. Applicant's letter No. 13	745-48/AddicP(L		3-2012
S. Minimum Standards on fire	Circularos Guest Hous		Remarks
No. prevention and fire safety U/R 3.	Requirement		MR/NMR
1 Access to building			
 Road width 		9 mty,	MIR
• Gate width		y mts.	MIR
 Width of internal road 		~	
Number, Width, Type & Arrangem	ent of Exits		
a. Number of staircases	2	2	MIR
 Upper Floors 	2	ス	MIR
 Basements 	1	1	MIR
b. Width of staircases			
 Upper Floors 	90cm	95 cm to loo cm 105 cm to 135 cm	MIR
• Basements	IM	105 cm to 138 cm	MIR
c. Protection of exits	1 1"	1,1	
• Fire check door		NR	
 Pressurization 		,	
e. No. of continuous staircases to terra	ce		20120
g. Width of Corridor		2	mje
h. Door Size	1	1 12	
III DOOL DIZE) m) m	miR

3	Compartmentation.		10			
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain 		MR			
	• Fire Dampers					
4	Smoke Management System.	Smoke Management System.				
	BasementsUpper floors	30 a/c per hour 12 a/c per hour	N/R			
5	Fire Extinguishers					
	Total numbersTypes		W.Coz, Coz, ABC	MIR MIR		
	 IS marking 	ISI marked	yes	MIR		
6	First-Aid Hose Reels.	8				
	Total numbers on each floor	one	one	MIR		
	Length of hose reel hoseNozzle diameter	30 m 5 mm	Provided	m)R m)R		
7	Automatic fire detection and alarming	g system.	10000001			
	• Type of detectors		NIK			
	Location of Main PanelLocation of Repeater Panel			3		
	Alternate source of powerHooters' Location	4				
0	MODEL	R	0:	1 2-10		
9	MOEFA Public Address Contact	R	Siron provided	mid		
10	Public Address System.		1000000	17/0		
10	Automatic Sprinkler System. Basement	R	Potrided	MIR		

	Upper Floor		NIR		
	Sprinkler above false ceiling		NR		
11	Internal Hydrants	W 8:		2	
	Size of riser/down-comer	100 mm	loo mm	mik	
	Number of hydrants per floor	NR	one atgrand	MIR	
	Hose Box		100 mm one atgrænnd floor Provided. N/R	MIR	
12	Yard Hydrants.		NIR		
	Total number of hydrants		14/1		
	Hose Box	,			
13	Pumping Arrangements.				
	• Ground Level		NR		
	Discharge of main Pump				
	Head of Main pump				
	Number of main pumps				
	Jockey Pump out put				
	Jockey pump head				
	Standby Pump out put				
	Standby Pump Head				
	Auto Starting/ Manual				
	stopping				
	Pump House Access				
	Terrace level	to - 1+8/mi	it licothin	54 mlR	
	Discharge of pump	450 Lts/minit 450 Lts/minit M/R			
	Head of the pump	yom	40 M	11/1/	
	Power Supply	R	Yom Provided Provided	MIK	
	Auto Starting of pump	R	Provided	MIR	
14	Captive Water Storage for fire fighting.	i			
	Underground tank capacity		NR		
TO NATIONAL PROPERTY AND ADMINISTRATION AND ADMINIS	Draw-off connection				

	 Fire service inlet Access to tank Overhead Tank capacity 			
15	Exit Signage.	R	Provided	MIR
16	Provision of Lifts.			
	Pressurization of Lift Shaft		NIR	
	Pressurization of Lift lobby		NR	
and a management of the state o	Communication In lift Car	R	Alarm prov.	mla
	• Fireman's Grounding Switch	R	Provided.	MIR
	Lift Signage	R	8 mvioled	
17	Standby power supply	R	50 KVA D.G. set	miR
18	Refuge Area.		2112	
	> Total Area		MA	
	➤ Location			
19	Fire Control Room		NIIA	
AN ENGLISH GENERAL TRANSPORT OF THE PROPERTY O	Detector System Panel		1411	
	• Flow Switch Panel			
	PA System Panel			
	Batter backup			
	 Building Floor Plans 			
20	Special Fire Protection Systems for Protection of special Risks, if any:		NiL	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

Shylaf 3/2012 Signature of the Inspecting Officer Signature of the Inspecting Officer Name SHYAM LAL Name Designation Assit. Divn. Officer. Designation