GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No F 6/DFS/MS/2012/9H/1174

Dated 29/03/12

FIRE SAFETY CERTIFICATE

Certified that the Yuvraj Deluxe Guest House, located at 38, Arakashan Road, Pahar Ganj, New Delhi comprised of Basement + Ground + Five upper floors having 37 guest rooms (Basement is used for storage purposes, Ground floor has Reception + office + 05 guest rooms, First to Fourth floor has 08 Guest rooms, at each floor, Fifth floor is sealed) was granted NOC by this department vide letter No F 6 / DFS / MS / GH / 2009 / 1080 dated 22.04.2009. The premise was re-inspected by the officer concerned of this department on 23.03.2012 in the presence of Mr. Ram je found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from 2.2.9 / 0.3 / /2. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .. 2. 3. / . 0. 3 / 1.4.... at New Delhi

Chief Fire Officer
For Director
Delhi Fire Service

Copy to: -

- 1. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.
- 2. The Owner, Yuvraj Deluxe Guest House, located at 38, Arakashan Road, Pahar Ganj, New Delhi

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

INSPECTION REPORT

1) Name & address of the building: Yuvraj Deluxe Guest House, 38, Arakashan Road,

Pahar Ganj, New Delhi

2) Type of Occupancy

: Residential

3) Type of Case

: Renewal

4) Details of previous NOC

: Letter No F6/DFS/MS/GH/2009/1080 Dated 24.04.2009

5) Fire Safety directives Letter No.: N/A

6) Date of inspection

: 23.03.2012

7) Name of the Inspecting Officer: ADO D.S. Yadav & DO Atul Garg

8) Name and designation of Officer

from the building side

: Mr. Ram je

9) Year of Construction

: N/A

10) Applicant's letter No. : Dated 12.03.2012 & Addl. C.P letter 8291/ Addl.C.P/Lic. (H)

New Delhi the dated 09.02.2012

| S | Minimum standards on fire | BBL | Provided at site | Remarks MR/NMR |
|----|--|--------------|------------------|----------------|
| No | prevention and fire safety U/R 33 | Requirements | | |
| 1. | Access of building | | | |
| | Road width | N/A | 06 m | MR |
| | Gate width | N/A | N/A | N/A |
| | Width of internal road | N/A | N/A | N/A |
| 2. | Number, width, Type & Arrangemen | nts of exits | | |
| | a. Number of staircases | | | |
| | Upper floors | 01 | 01 | MR |
| | Basements | 01 | 01 | MR |
| | b. Width of staircases | | | |
| | Upper floors | 1.25 | 1.25 | MR |
| | Basements | 1.25 | 1.25 | MR |
| | c. Protection of exits | | | |
| | Fire check door | N/A | N/A | N/A |
| | Pressurization | N/A | N/A | N/A |
| | d. No of continuous staircase | 01 | 01 | MR |
| | to terrace e. Width Of Corridor | N/A | N/A | N/A |
| | f. Door Size | N/A | N/A | N/A |
| 3. | Compartmentation | | | |
| | Fire check door | N/A | N/A | N/A |

| Т | Casting of cloatmost shafts | N/A | N/A | N/A | | |
|--|--|-----------------|-------------------------|------|--|--|
| | Sealing of electrical shafts Fig. Pating of shaft door. | N/A | N/A | N/A | | |
| | • Fire Rating of shaft door | N/A | N/A | N/A | | |
| | Water Curtain | N/A | N/A | N/A | | |
| | • Fire Dampers | IVA | 14/11 | 1772 | | |
| 4. | Smoke managements System | 20 -/ hour | N/A | N/A | | |
| | Basements | 30 a/c per hour | N/A N/A | N/A | | |
| | Upper floors | 12 a/c per hour | IN/A | IN/A | | |
| 5. | Fire Extinguishers | | 100 | MD | | |
| | Total numbers | | 20 | MR | | |
| | Types | | WT,CO ₂ ,DCP | MR | | |
| | IS marking | ISI marked | YES | MR | | |
| 6. | First – Aid Hose Reels | | | | | |
| | Total numbers on each floor | 01 | 01 | MR | | |
| | Length of hose reel hose | 30 m | YES | YES | | |
| | Nozzle diameter | 5 mm | YES | YES | | |
| 7. | Automatic fire detection and alarming system | | | | | |
| | Type of detectors | N/A | N/A | N/A | | |
| | Location of Main Panel | N/A | N/A | N/A | | |
| | Location of Repeater Panel | N/A | N/A | N/A | | |
| | Alternate source of power | N/A | N/A | N/A | | |
| > | Hooters' Location | N/A | N/A | N/A | | |
| 8. | MOEFA | YES | YES | MR | | |
| 9. | Public Address System | YES | YES | MR | | |
| 10. | Automatic Sprinkler System | | | | | |
| | - Decements | YES | YES | MR | | |
| | Basements Livery Flaces | N/A | N/A | N/A | | |
| | Upper Floor Grain land shows false spiling | | N/A | N/A | | |
| 11. | Sprinkler above false ceiling N/A N/A N/A Internal Hydrants | | | | | |
| | Size of riser/down- comer | 100 mm | YES | MR | | |
| Constitution of the Constitution of the Const | Number of hydrants per | 01 | YES | MR | | |
| | floor • Hose Box | 01 | YES | MR | | |
| 12. | Yard Hydrants | | | | | |
| | Total number of hydrants | N/A | N/A | N/A | | |
| | Hose Box | N/A | N/A | N/A | | |
| 13. | Pumping Arrangements | | | | | |
| | Ground Level | | | | | |
| | Discharge of main pump | N/A | N/A | N/A | | |
| | ➤ Head of main pump | N/A | N/A | N/A | | |
| | - | N/A | N/A | N/A | | |

| Head of main pump | TAT/A | T T / A | 3.T/A | | |
|--|---|---|--|--|--|
| | N/A | N/A | N/A | | |
| Number of main pumps | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| | N/A | N/A | N/A | | |
| | | | | | |
| Pump House Access | N/A | N/A | N/A | | |
| | | | | | |
| | 450 Lpm | YES | MR | | |
| | | | N/A | | |
| | | | MR | | |
| | | | MR | | |
| | | 120 | | | |
| | | | | | |
| | | | N/A | | |
| | | | MR | | |
| | | | MR | | |
| | | | MR | | |
| Overhead Tank capacity | | | MR | | |
| Exit Signage | YES | YES | MR | | |
| Provision of Lifts | | | | | |
| Pressurization of Lift Shaft | N/A | N/A | N/A | | |
| | | | | | |
| Pressurization of lift lobby | | | N/A | | |
| | | | N/A | | |
| | N/A | N/A | N/A | | |
| Switch | | | | | |
| | N/A | N/A | N/A | | |
| | | | * | | |
| Standby power supply | YES | YES | MR | | |
| Refuge Area | | | | | |
| | | | N/A | | |
| > Location | N/A | N/A | N/A | | |
| Fire control room | | | | | |
| Detector system panel | N/A | N/A | N/A | | |
| Flow Switch Panel | N/A | N/A | N/A | | |
| PA System Panel | N/A | N/A | N/A | | |
| Batter backup | N/A | N/A | N/A | | |
| Building Floor Plans | N/A | N/A | N/A | | |
| Special Fire Protection Systems for Protection of special Risks, if any: | N/A | N/A | N/A | | |
| | Jockey pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Under ground tank capacity Draw of connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage Provision of Lifts Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total area Location Fire control room Detector system panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans | ▶ Jockey pump out put ▶ Jockey pump head ▶ Standby Pump out put ▶ Standby Pump Head ▶ Auto Staring/Manual stopping ▶ Pump House Access ▶ Pump House Access ▶ Pump House Access ► Terrace level ▶ Discharge of pump ▶ Head of the pump ▶ Power supply ▶ Auto starting of pump Captive water Storage for fire fighting ● Under ground tank capacity ▶ Fire service inlet ▶ Fire service inlet ▶ Access to tank ♠ Overhead Tank capacity ▶ Pressurization of Lift Shaft ▶ Pressurization of Lift Shaft ▶ Pressurization of lift lobby ▶ Communication in lift Car ▶ Fireman's Grounding Switch ▶ Total area ▶ Location ▶ Total area ▶ Location ▶ PA System Panel ▶ PA System Panel ▶ Batter backup ▶ Building Floor Plans N/A | Jockey pump out put Jockey pump head N/A N/A<!--</td--> | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name AJUL GARS

Name SHARM VIA PINGH YADOV

Designation Activity Divisional