GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI - 110001

No: F 6/DFS/MS/2012/ School/1139

Dated: 28/03/12

FIRE SAFETY CERTIFICATE	
Certified that the Hans Rop Modell School (Recognised) (R	vide this office letter is re-inspected by the ved that all the fire bund in good working rement under Rule 33 for occupancy Class for a period of coner cancelled under
Issued on 28 / 03 / 12 at New Delhi.	1
at New Deini.	28/3
	Chief Fire Officer
Copy to:-	Delhi Fire Service
Copy to:- The Aidi sector of Echn. (ACT) Sout of NET of Delli ald Lectt. Dolli	ole.
2. The Man-fes Hans Rot Model School Ramesh Enclave	

1. All the means of escape shall be kept free of all type of obstruction all the time time.

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non - functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per MG

6. This NOC may not be treated in any case for regularizations of unauthorized.

construction, if any.

7 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1.	Name & address of the building Hansray Model School, Kamesh enclove, sect. 2)			
2.	Type of Occupancy Edmational Delhi-86			
3.	Type of Case : New Ca	the state of the s		
4.	Details of previous NOC : Letter No.F-6/ms/DFs/2005/2885 Dated: 27-9-0			: 27-9-06
5.	Fire Safety directives letter No : 262-	362 dt-17-	1-2005	23
6.	Date of inspection 28-2-2	2012		
7.				
8.	8. Name and designation of officers Sh. Bhupinder Kumar (Manager)			
	from the building side :			· .
	9. Year of Construction : 2006\$10.(G1+1) First floor = 2010.			
	Time temporal man man	12/011 dated	9-12-2011	
S.	Minimum Standards on fire	Dir-Edim.	Provided at site	Remar
No.	prevention and fire safety U/R 33	Requirement	•	MR/NN
1	Access to building	. , , ,		!
	Road width	Accessible	6 mts.	MIR
	Gate width	-w-	y mts.	MIR
	Width of internal road	-m-	h mts	MIR
2 -	Number, Width, Type & Arrangement of Exits			
	a. Number of staircases	2:	2	MIR
	Upper Floors	2	2	-11-
	• Basements	MIL	NiL	
	b. Width of staircases	1.5 m	1.60 m & 1.50 m	n MIR
	Upper Floors	1.5 m	1.6 mts 2.1.5 m	t -u-
	Basements	NiL	Nic	
	c. Protection of exits	NIO	MA	
	Fire check door	I I K		
3.	 Pressurization 	MR	MIN	
	e. No. of continuous staircases to terrace	2	2	MIR
	g. Width of Corridor		2.40 m	mR
	h. Door Size	mi	m	MIR
			-	

		- a	r Y	
3	Compartmentation.		NR	
	Fire check door		141.0	
	 Sealing of electrical shafts 			
2	 Fire Rating of shaft door 			
	 Water Curtain 			
	• Fire Dampers			
4	Smoke Management System.			
	• Basements	30 a/c per hour	1410	
	Upper floors	12 a/c per hour		
5	Fire Extinguishers	,		
	Total numbers	ABC/CO2 2.5 /	5	MIR
	• Types	200 M2 tor one.	ABC	4
	IS marking	ISI marked	Yes	~~
6	First-Aid Hose Reels.		NR	
	Total numbers on each floor		7412	
	Length of hose reel hose	30 m		
	Nozzle diameter	5 mm		
7	Automatic fire detection and alarming	system.	NR	1
	Type of detectors		14.1	
	Location of Main Panel		S	
	Location of Repeater Panel			
	Alternate source of power			
	Hooters' Location			
			1.0	
8	MOEFA		NK	
9	Public Address System.		MR	
10	Automatic Sprinkler System.	** *	7 AR	
	Basement			1

	• Upper Ele	
	• Upper Floor	
	Sprinkler above false ceiling	
11	Internal Hydrants	
	Size of riser/down-comer	I NK
	 Number of hydrants per floor 	
	• Hose Box	
12	Yard Hydrants.	n + O
	 Total number of hydrants 	N. P.
	Hose Box	
13	Pumping Arrangements.	N. P.
	Ground Level	NA .
	Discharge of main Pump	
	Head of Main pump	
	Number of main pumps	
	> Jockey Pump out put	
	> Jockey pump head	
	Standby Pump out put	
	and Itelli	
	➤ Auto Starting/ Manual	
	stopping	
	➤ Pump House Access	
	Terrace level	
	Discharge of pump	
	➤ Head of the pump	
	Power Supply	
	> Auto Starting of pump	
14	Captive Water Storage for fire fighting.	0
	Underground tank capacity	NK
	> Draw-off connection	

	> Fire service inlet	
	> Access to tank	
	Overhead Tank capacity	
15	Exit Signage.	GITI MR MIR
16	Provision of Lifts.), A
	Pressurization of Lift Shaft	N B
4	• Pressurization of Lift lobby	
	Communication In lift Car	
	• Fireman's Grounding Switch	
	• Lift Signage	
177		
17	Standby power supply	JY K
18	Refuge Area.	1011
	> Total Area	/ / / / / / / / / / / / / / / / / / / /
	> Location	
19	Fire Control Room	N/O
	Detector System Panel	
	Flow Switch Panel	
	PAi System Panel	A LOT TO A STORY OF THE STORY OF THE STORY
a (Batter backup	
	Building Floor Plans	
20	Special Fire Protection Systems for	
	Protection of special Risks, if any:	Ni

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safe required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the De Fire Service Rules 2010/ issue shortcomings as noted at serial numbers......

Signature of the Inspecting Officer

Name

Designation

o. (Nw)

29/2/2012

Signature of the Inspecting ()

ame SHYAM LAC

Designation A DO