GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

No: F 6/DFS/MS/2012/ school/ 1140

Dated: 29/03/12

FIRE SAFETY CERTIFICATE

Certified that the MCD Pratible School Sindhora	Kalan
Delli 1100 2	and upper floor
awned/accumied by MCD	tratibha school
requirement in accordance with Driection Edu. Cir Cular No f. 16 2011 3298-3388 alt 13 building/premises is fit for occupancy 17 du Cular No f. 16	evention and fire safety
requirement in accordance with Director Columbia f-16	that coffice stery
The presence of stand	and that the
effect from	building with
printed overleaf.	ompliance of the conditions
printed overlear.	· · · · · · · · · · · · · · · · · · ·
Issued on29.10.3/12 at New Delhi.	* a * \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	\mathcal{N}_{\bullet}
	Xlum
	(2A)3
	Chief Fire Officer
	Delhi Fire Service
Copy to:-	Delin rife Selvice
The Principal	SC Jan
MC i) Pratibha School	
Sinothora Kalan Delhi 110052	
2. The Director of Education (MCD)	a v
Nigam Bhacran Kashmere fate delhi	
o comprehensive and the second	, a

1. All the means of escape shall be kept free of all type of obstruction all the time is

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non — functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per MGC

6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any.

7 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPE	CTION REPORT		
1. Name & address of the building MCI		col Sidhorab	Kalan D
	ucational.	(V), some	Word of
	Case/ R enewal -		
	r No.	Dated	4.
5. Fire Safety directives letter No Elb/sst			The second secon
	12012	10000	
7. Name of the Inspecting Officers: A)	E STATE OF THE STA	n (4)	
		The second secon	
8. Name and designation of officers Sm from the building side :	+- Ses ver	is Gogal.	
	8 (G+1)		
	dated 6-2	-2012	
S. Minimum Standards on fire	Circular Dir. of Edm.	Provided at site	Remarks
No. prevention and fire safety U/R 33	Requirement,		MR/NMR
1 Access to building	1 3 2011		
Road width	Accessible	5 mbs.	mIR
• Gate width	~	3.30 mts.	-h
Width of internal road	n		
Number, Width, Type & Arrangemen	it of Exits	-	,
a. Number of staircases	2	2	MIR
Upper Floors	2(1.5 mts)	2 (1.9 mts)	MIR
Basements	NI'L	Ni' (MIR
b. Width of staircases	1. c- mts	1.90 mtre	min
Upper Floors	1.5 mts.		
Basements		- 1.90 mts.	
c. Protection of exits	Nic	141	
• Fire check door	NX	NR	~
Pressurization		NR	
e. No. of continuous staircases to terrace	2	ML	
g. Width of Corridor			
		7 m	mR

4				
3	Compartmentation.		NR	
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 			
4	Smoke Management System.		NR	
	BasementsUpper floors	30 a/c per hour 12 a/c per hour		
5	Fire Extinguishers			10.12
	Total numbersTypesIS marking	300 M Covered one one AB or Coz(2.5%) ISI marked	ABC - Yes	M/R
6	First-Aid Hose Reels.		NR	
	Total numbers on each floorLength of hose reel hoseNozzle diameter	30 m 5 mm	140	
7	Automatic fire detection and alarmin	ig system.	NR	
	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 			
8	MOEFA		NR	
9	Public Address System.	,	MR	
10	Automatic Sprinkler System. Basement	,	NR	

K	Upper Floor	
	Sprinkler above false ceiling	
11	Internal Hydrants	NR
	Size of riser/down-comer	, , , ,
	Number of hydrants per floor	
	Hose Box	
12	Yard Hydrants.	NR
	Total number of hydrants	
	Hose Box	
13	Pumping Arrangements.	NR
	Ground Level	
	Discharge of main Pump	
	Head of Main pump	
	Number of main pumps	
	> Jockey Pump out put	
	> Jockey pump head	
	➤ Standby Pump out put	
	> Standby Pump Head	
	Auto Starting/ Manual	
	stopping	
	➤ Pump House Access	
	Terrace level	
	Discharge of pump	
	Head of the pump	
	Power Supply	
	> Auto Starting of pump	
14	Captive Water Storage for fire fighting.	\ (\(\lambda \)
	Underground tank capacity	14 K
	> Draw-off connection	

Q	Fire service inlet			
	Access to tank			
	 Overhead Tank capacity 	8.		
15	Exit Signage.	GrI	MR	
16	Provision of Lifts.		NIA	1
	Pressurization of Lift Shaft		7 7 7 0 3	
	 Pressurization of Lift lobby 			
	Communication In lift Car			
	• Fireman's Grounding Switch			
	• Lift Signage			
17	Standby power supply		NR	
18	Refuge Area.		MIA	1
			11/1	-
	Total Area			
	Total AreaLocation			
19			NR	
19	> Location		NR	
19	➤ Location Fire Control Room		NR	
19	 Location Fire Control Room Detector System Panel 		NR	
19	 Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel 		NR	
19	 Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup 		NR	
20	 Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup 		NR Mil.	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of the Inspecting Officer Signature of the Inspecting Officer Name Designation