## FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/OS/GH/2012/1189

Dated: 30 / 03/2012

## FIRE SAFETY CERTIFICATE

Certified that the Swift Inn Guest House located at 397, Bhera Enclave, Paschim Vihar, New Delhi., have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concern of Fire Service on 20.03.2012 in presence of Sh. Subhash Chander Uppal of the Guest House Residential occupancy with that the premises is fit for Class-A-1 (i) renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 30/03/12 at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy to:

Addl. Commissioner of Police Licensing: Delhi 1st Floor, Ploce Station, Defence Colony, New Delhi

Sh. Subhash Chander Uppal 2. Swift Inn Guest House 397, Bhera Enclave, Paschim Vihar, New Delhi

Note:- For general fire safety directives please over leaf.

## Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided the in shall be maintained in good working g conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on <a href="www.dfs">www.dfs</a>. delhigovt. nic.in

Devender Ram Penterh Keilsh.

May Kindly peruse letter no.8835/Addl.CP/Lic(H) dated 14/02/2012 received from Addl. Commissioner of Police (Licensing), regarding of NOC in r/o Swift Inn Guest House located at 397, Bhera Enclave, Paschim Vihar, New Delhi. premises was inspected by the undersigned & the fire safety arrangements are put up on the prescribed Performa.

1. Name &address of the building : Swift Inn Guest House located at 397, Bhera Enclave, Paschim

Vihar, New Delhi.

2. Type of Occupancy : Class-A-1 (i) Residential

3. Type of Case : New

4. Details of previous NOC : Nil

5. Fire Safety directives letter No. : Nil

6. Date of inspection : 20.03-2012

7. Name of the Inspecting Officers : Division Officer Sunil Chawdhary

8. Name and designation of officers

From the building side : Sh. Subhash Chander Uppal

9. Year of Construction : 2011

10. Applicant's letter No. : 8835/Addl.CP/Lic(H) dated 14/02/2012

## **INSPECTION REPORT**

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building				
	Road width	06mtrs	9 mtr approx.	M.R.	
	Gate width	4.5 mtrs	Provided	M.R. abutting main road	
	Width of internal road	N.R.	N.R.	N.R.	
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	two	two	M.R.	
	Upper Floors	two	two	M.R.	

	• Basement	two	two	M/R
	b. Width of staircases			
	Upper Floors	1.5 mtr & 1.4 mtr	Provided Plot size 275.28 sq. mtr	M.R. As per BBL 83
	Basement	1.5 mtr & 1.4 mtr	Provided Covered area 166.65 sq.m.	M.R. As per BBL 83
	c. Protection of exits			
	Fire check door	Required	Provided	M.R.
	• Pressurization	N.R.	N.R.	Not applicable
	d. No. of continuous staircases to terrace	two	two	M.R.
	e. Width of Corridor	1.25 mtr	Provided	M.R.
	f. Door size	1 mtr	Provided	M.R.
3.	Compartmentation.		<u>.</u>	
	Fire check door	Required	Provided	M.R.
	Sealing of electrical shafts	N.A.	N.R	Not applicable
	Fire Rating of shaft door	N.A.	N.R	Not applicable
	Water Curtain	N.A.	N.R	Not applicable
	Fire Dampers	N.A.	N.R	Not applicable
4.	Smoke Management System.			
	Basements	Required	Provided	M.R.
	Upper floors	Natural	Provided	M.R.
5.	Fire Extinguishers	,	9	
	Total numbers	14	20	M.R.

	• Types	ABC & CO <sub>2</sub> type Required	ABC & CO <sub>2</sub> type	M.R.		
	IS marking	ISI marks Required	provided	M.R.		
6.	First-Aid Hose Rees.					
	Total numbers on each floor	1	one	M.R.		
	Length of hose reel hose	30 m	Provided	M.R.		
	Nozzle diameter	5 mm	provided	M.R.		
7.	Automatic fire detection and alarming system.					
	Type of detectors	Smoke & Heat	Provided	M.R.		
	Location of Main Panel	Ground Floor	Provided	M.R.		
	Location of Repeater Panel	At each floor	Provided	M.R.		
	Alternate source of power	Required	Provided	M.R.		
	Hooter's Location	Required	Provided	M.R		
8.	MOEFA	Required	Provided	M.R.		
9.	Public Address System.	Required	Provided	M.R.		
10.	Automatic Sprinkler system	-				
	Basement	Required	Provided	M.R.		
	Upper Floor	N.R.	N.R.	Not applicable		
	Sprinkler above false ceiling	N.R.	N.R.	Not applicable		
11.	Internal Hydrants	1				

	·			
	Size of riser/down-comer	100 m	Provided	M.R.
	Number of hydrants per floor	1	Provided	M.R.
	Hose Box	1	Provided	M.R.
12.	Yard Hydrants.			
	Total number of hydrants	N.R	N.R.	N.R.
	Hose Box	N.R	N.R.	N.R.
13.	Pumping Arrangements.	,		
	Ground Level			
	Discharge of main pump	N.R	N.R	Not applicable
	➤ Head of Main pump	N.R	N.R	Not applicable
	Number of main pumps	N.R	N.R	Not applicable
	➤ Jockey Pump out put	180 LPM	Provided	M.R.
	➤ Jockey pump head	50 mtr	Provided	M.R.
	> Standby pump out put	N.R	N.R	Not applicable
	> Standby pump Head	N.R	N.R	Not applicable
	Auto Starting/Manual stopping	Required	Provided	M.R.
	> Pump Hose Access	Required	Provided	M.R.
	Terrace level			
	Discharge of pump	900 LPM	provided	M.R.
	➤ Head of the pump	50 mtr	Provided	M.R.

	➤ Power supply	Required	Provided	M.R.
	> Auto Starting of pump	Required	Provided	M.R.
14.	Captive Water Storage for fire figh	ting.		
	Underground tank capacity			
	> Draw -off connection	N.R	N.R	N.R
	➤ Fire service inlet	N.R	N.R	N.R
	> Access to tank	N.R	N.R	N.R
	➤ Overhead Tank Capacity	10,000	Provided	M.R.
15	Exit Signage.	Required	Provided	M.R.
16.	Provision of Lifts			
	Pressurization of Lift Shaft	N.A	N.R	Not applicable
	Pressurization of Lift lobby	N.A	N.R	Not applicable
	Communication In lift Car	N.A	N.R	Not applicable
	Fireman's Grounding     Switch	N.A	N.R	Not applicable
	Lift Signage	N.A	N.R	Not applicable -
17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area			
	> Total Area	N.R.	N.R.	Not applicable.
	> Location	N.R.	N.R.	Not applicable

19.	Fire Control Room			
	Detector System Panel	Required	Provided	M.R.
	Detector System raner	Required	Provided	M.R.
	Flow Switch Panel		8	
	➤ PA system Panel	Required	Provided	M.R.
	➤ Batter backup	Required	Provided	M.R.
	> Building Floor plans	N.R.	N.R.	Not applicable
20.	Special Fire Protection Systems for  Protection of special Risks, if any:	N.R.	N.R.	Not applicable.

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

MMV

Signature of the Inspection Officer

Name SUNIL CHAWDOARLY

Name

Designation

Designation