## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

PARE SAFETY CERTIFICATE

Certified that the Bright Star Convent Public School, A-153 ShastriPARE Ext. Phoof bagh Road Buran completed of Ground to one
Convent School

complete with rule 33 of the Delhi Fire Service Rule 2010 and verified by the officer concerned of Fire Service on 2913. 12 in the presence of
Shish Shyam Ruman that the building/premises is fit for occupancy completed with rule 36 unless renewed under rule 37 or a period of in accordance with rule 36 unless renewed under rule 37 or a period of sulles, 2010.

Issued on 10104.12 at New Delhi.

Chief Fire Officer

Delhi Fire Service

Or You

Copy to:

Delhi Fire Service

Or You

Chief Fire Officer

Delhi Fire Service

Or You

Rugary Stars Convent Rubic 3chast

Phast Bagh Road, Burary, Deshi-

Note:-Guidelines overleaf may also be taken care of.

## INSPECTION REPORT

1	Name & address of the building Bright	T Star Conven	I hublic School,	A-153, Phoolbag
2	. Type of Occupancy Educa	tion.	-Road, Shastri Har	KENT , BUYON
3	The state of the s	ase/ Renewal -		
4	. Details of previous NOC : Letter 1	Vo	V'C Dated	d:
5	. Fire Safety directives letter No F-6/68	tat / F. Safety/	c/11/3298-3390a	ted 1/3/201)
6		3-2012	1 3/8	
7	. Name of the Inspecting Officers:	O-SHYA	n LAL	
8	. Name and designation of officers	A 1	( H m )	
	from the building side .	Ashweini Ku		
9	. Year of Construction ??co	3, Gran	nottone.	
1 (	). Applicant's letter No. : 01	dated 16	-2-2012	
S.	Minimum Standards on fire	Circulars	Provided at site	Remarks .
No.	prevention and fire safety U/R 33	Edd Director		MR/NMR
1	Access to building			
	Road width	Accessible	6 mbs.	miR
	• Gate width	1-	2.5 mts.	MIR
	Width of internal road	-h	NIA	MIR
2	Number, Width, Type & Arrangement	of Exits		
	a. Number of staircases	マ	2	MSR
	<ul> <li>Upper Floors</li> </ul>	2	2	miR
	Basements	145°C	Dit	,
	b. Width of staircases	1.5 mfs,	1.5 m 2.3.2 n	A MIR
	<ul> <li>Upper Floors</li> </ul>	The same of the sa	1-5 m & ner	
	<ul><li>Basements</li></ul>	M12	MY	
	c. Protection of exits		A 9 .1	
	Fire check door		NK	
	<ul> <li>Pressurization</li> </ul>			
	e. No. of continuous staircases to terrace	2	2	MIR
	g. Width of Corridor	1	1.15	MIR
	h. Door Size	1 m	1 m	MIR
			1	The second secon

3	Compartmentation.		NIR	
	<ul> <li>Fire check door</li> <li>Sealing of electrical shafts</li> <li>Fire Rating of shaft door</li> <li>Water Curtain</li> <li>Fire Dampers</li> </ul>			,
4	Smoke Management System.		NR	
	<ul><li>Basements</li><li>Upper floors</li></ul>	30 a/c per hour 12 a/c per hour	7 7 0 \	
5	Fire Extinguishers	2		
	<ul><li>Total numbers</li><li>Types</li><li>IS marking</li></ul>	BON M Covered over one of the or col (25kg.)  ISI marked	ABC type Yes	MIR MIR MIR
6	First-Aid Hose Reels.	\	NILO	
	<ul> <li>Total numbers on each floor</li> <li>Length of hose reel hose</li> <li>Nozzle diameter</li> </ul>	30 m 5 mm	N/R	
7	Automatic fire detection and alarmin	g system.	NIAD	
	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> <li>Hooters' Location</li> </ul>		TYTE	
8	MOEFA		N/R	
9	Public Address System.		NIR	
10	Automatic Sprinkler System.  • Basement		NIR	

	Upper Floor	
	Sprinkler above false ceiling	
11	Internal Hydrants	NIR
	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants per floor</li> <li>Hose Box</li> </ul>	
12	Yard Hydrants.	NIR
	<ul><li>Total number of hydrants</li><li>Hose Box</li></ul>	74)1
13	Pumping Arrangements.	NR
	<ul> <li>Ground Level</li> <li>Discharge of main Pump</li> <li>Head of Main pump</li> <li>Number of main pumps</li> <li>Jockey Pump out put</li> <li>Jockey pump head</li> <li>Standby Pump out put</li> <li>Standby Pump Head</li> <li>Auto Starting/ Manual stopping</li> </ul>	
	<ul> <li>Pump House Access</li> <li>Terrace level</li> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power Supply</li> <li>Auto Starting of pump</li> </ul>	
14	Captive Water Storage for fire fighting.	NIR
	<ul><li>Underground tank capacity</li><li>Draw-off connection</li></ul>	

/	1			
	Fire service inlet			
	Access to tank			
	<ul> <li>Overhead Tank capacity</li> </ul>	8		
15	Exit Signage.	Gitt	NID	
16		000	14)	
	Pressurization of Lift Shaft		NA	
	Pressurization of Lift lobby		,	
	Communication In lift Car			
	×			
	r Heman's Grounding Switch			
	Lift Signage			
17	Standby power supply		1110	
18	Refuge Area.		19/0	
	> Total Area			
	> Location			
19	Fire Control Room			
	Detector System Panel		NR	
	Flow Switch Panel			
	11 bystem i aner			
	Batter backup			
20	Building Floor Plans			
20	Special Fire Protection Systems for			
	Protection of special Risks, if any:		N51	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name SHYAM LAL

Name

Designation

Designation Assitt. Dim officer.