## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DF3/MS/212/4839

Dated:

31/12/11

## FIRE SAFETY CERTIFICATE

Certified that the Govt.Girls Sr.Sec School at Janta Flats, Nand Nagri, Delhi-93. Comprised of ground plus one upper floor owned/occupied by Govt.Girls Sr.Sec School have complied with the fire prevention and fire safety requirements in accordance with the circular issued by the Director of Education dtd.01.03.2011 and verified by the officer concerned of this department on 13.12.2012 in the presence of Smt.Sushma Sharma, Vice -Principal, of the school and that the building is fit for occupancy class B' Educational Building' with effect from ....... for a period of three years, subject to conditions printed overleaf.

Issued on......at New Delhi by

Chief Fire Officer Delhi Fire Service

To.

-

The Vice-Principal
Govt.Girls Sr.Sec School
Janta Flats,Nand Nagri,Delhi-93

Copy:-

The Joint Director of Education (Land & Estate)
 Directorate of Education,
 Lucknow Road.Delhi -54.

2. The Principal
Govt.Girls Sr.Sec School
Janta Flats,Nand Nagri,Delhi-93

## CONDITIONS:

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management

shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This NOC may not be treated in any case for regularizations of unauthorized

construction unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

## INSPECTION REPORT

1	Name & address of the building: G.G.	SS School.	Janta Flats, 1	land Nagri,D
2		cational C	group B)	
3	Type of Case : New Ca	se/ Renewal		
4	Details of previous NOC : Letter N	0. NA	Dated	l:
5	Fire Safety directives letter No :	ts ber cir	cular dat	red 01/03/1
6	. Date of inspection	24.11.11		
7	Name of the Inspecting Officers:	Visendra	Singly	-7 
8	. Name and designation of officers			
	from the building side :	Ars Sushr	ng charma	Q. Principal
9	Year of Construction :	1993		
. 1	O. Applicant's letter No.			
S.	Minimum Standards on fire	NBC	Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMR
1	Access to building			
	Road width	6 Mtos	lo Mtos.	MR
	Gate width		4 Mtrs	MR
	Width of internal road			· MR
2	Number, Width, Type & Arrangement of	of Exits		
	a. Number of staircases	51%	Five	NMR
	Upper Floors	SIX	Five	NMR
	Basements			
	b. Width of staircases	1.5 Mts	1.4 mbs	NMR
	Upper Floors	1.5 Mtos	1.45 Mts	NMR
	Basements			
	c. Protection of exits	/	7	1
	Fire check door			
	Pressurization			
	e. No. of continuous staircases to terrace	3 Nos.	3 Nos.	MR
	g. Width of Corridor	1-5 Mbs	1.5 Mbs	MR
	h. Door Size	1.0 mbs	1.0 Mtrs	MR

			T	
· 3	Composit			
	Compartmentation.			. )
	• Fire check door			
	• Sealing of electrical shafts			
8	Fire Rating of shaft door			
	Water Curtain			+
	Fire Dampers			1
4	Smoke Management System.			
	Basements	30 a/c per hour	Λ	
	Upper floors	12 a/c per hour		7
		J Pol Moun		
5	Fire Extinguishers			· V
R	Total numbers	18 Nos.	01. 0.1	24.0
	• Types	ABC e. co2	24 Nos	MR
	IS marking	ISI marked		MR
6	First-Aid Hose Reels.		131 Merky	MR
	Total numbers on each floor			Α.
	Length of hose reel hose	30 m		
	<ul><li>Length of hose reel hose</li><li>Nozzle diameter</li></ul>	30 m / 5 mm		
7	Nozzle diameter	5 mm /		
7	Nozzle diameter  Automatic fire detection and alarming:	5 mm /		
7	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming</li> <li>Type of detectors</li> </ul>	5 mm /		
7	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming:</li> <li>Type of detectors</li> <li>Location of Main Panel</li> </ul>	5 mm /		
7	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming</li> <li>Type of detectors</li> </ul>	5 mm /		
7	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming:</li> <li>Type of detectors</li> <li>Location of Main Panel</li> </ul>	5 mm /		
7	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming:</li> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> </ul>	5 mm /		
	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming:</li> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> </ul>	5 mm /		
7	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming:</li> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> </ul>	5 mm /		
	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming:</li> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> <li>Hooters' Location</li> </ul> MOEFA	5 mm /		
	<ul> <li>Nozzle diameter</li> <li>Automatic fire detection and alarming:</li> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> <li>Hooters' Location</li> </ul> MOEFA	5 mm /		

:

•	<ul><li>Upper Floor</li><li>Sprinkler above false ceiling</li></ul>		1
11	Internal Hydrants		
	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants per floor</li> <li>Hose Box</li> </ul>		
12	Yard Hydrants.	l - 2d a miles	
27	<ul><li>Total number of hydrants</li><li>Hose Box</li></ul>		
13	Pumping Arrangements.		
	<ul> <li>Ground Level</li> <li>Discharge of main Pump</li> <li>Head of Main pump</li> <li>Number of main pumps</li> </ul>		
	<ul> <li>Jockey Pump out put</li> <li>Jockey pump head</li> <li>Standby Pump out put</li> </ul>		
	<ul> <li>➤ Standby Pump Head</li> <li>➤ Auto Starting/ Manual</li> <li>stopping</li> <li>➤ Pump House Access</li> </ul>		
	<ul> <li>Terrace level</li> <li>Discharge of pump</li> <li>Head of the pump</li> <li>Power Supply</li> <li>Auto Starting of pump</li> </ul>		
14	Captive Water Storage for fire fighting.		
, 17	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>		

*;*;;;

•	> Fire service inlet	
	Access to tank	
	Overhead Tank capacity	
15	Exit Signage.	
16	Provision of Lifts.	
	Pressurization of Lift Shaft	
	Pressurization of Lift lobby	
	Communication In lift Car	
	• Fireman's Grounding Switch	
* * **********************************	Lift Signage	
17	Standby power supply	
18	Refuge Area.	
	> Total Area	
	> Location	
19		
17	Fire Control Room	
	Detector System Panel	
22	Flow Switch Panel	
	PAi System Panel	
	Batter backup	
	Building Floor Plans	
20	Special Fire Protection Systems for	
7.	Protection of special Risks, if any:	
a <sup>D</sup>		
- The state of the		

The fire protection systems provided in the building were test checked and found functional at the to of inspection.

Signature of the Inspecting Officer Signature of the Inspecting Officer Virendra Singh Name Name Designation Designation