## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

No: F 6/DFS/MS/2012/ School / 47 42

Dated:- 2 1 12 12

## FIRE SAFETY CERTIFICATE

A STATE OF THE STA	
Certified that the Mari Gold Public School VIII - Katewaola, Delhi-11 on 39	, Khasroi No: 55
by Marigald Educational wellow Social was	occupier
prevention and fire safety arrangements as provided in the	and observed that all the fire
Dir. of Solun. 17-1-2005 and the building/prep	the requirement Circular,
hree wave in accordance with rule 36 unless renewed unless	2.1.1.12.1.12 for a period o
Rule 40 and subject to compliance of the conditions under R Rules, 2010.	Rule 38 of the Delhi Fire Service
Issued on 21/12/12 at New Delhi.	0 —
	[5] <sub>1</sub>
•	Chief Fire Officer Delhi Fire Service
1. The Manager	(V
1 The Manager Marigafol Public School, Katewara, Delhi-39	
2	
· · · · · · · · · · · · · · · · · · ·	

4/N Renewal

## INSPECTION REPORT

	THE RESERVE OF THE PROPERTY OF		and the second second second second second	isthan hs student
h. Doo	or Size	1 m	1.10 m	MIR
g. Wio	Ith of Corridor	R	2.70 m	MIR
e. No.	of continuous staircases to terrac	AND ADDRESS AND ADDRESS OF THE AND ADDRESS OF THE A	Provided	mil
· ·	Pressurization	N/R	N/P	N/A
	Fire check door	. N/R	N/P	N/A
c. Prot	ection of exits	NIC	/ \/	141
	Basements	Nic	NiL	NiL
49	Upper Floors	1.5 m	1.18 m 2.1.8 m Ca	(dease) m) R
b. Wic	Ith of staircases			
(8)	Basements	Nic	NiL	NiL
9	Upper Floors	2	2 (	mIR
	nber of staircases	2	2	MIR
Numb	er, Width, Type & Arrangemen	nt of Exits	* , *	
	Width of internal road	-h-	6 m	mlk
@	Gate width	-h-	41.96 m	mil
. @	Road width	:Accessible	6	MIR
Access	s to building		Lold case	The state of the s
Drc	evention and fire safety U/R 33	Requirement		MR/NMR
	Minimum Standards on fire	Edin. 17-1-200	Provided at site	Remarks
Appli	cant's letter No.	MPS/DES/203/2	+/with adjoin	neipal Grr+2
. Year o	f Construction 200	Monaser	+ (with adicin	ting residence
from	the building side : 31	h. Bhal Singl	h - <del>)</del>	
	e and designation of officers			
		0-SHYAM	LAL	
	The state of the s	12-2012	Inn. No.262-362	at. 17-7-20
			rs/09/2479 Date	
			rel all by a pate	11-9-32-0
		Case/ Renewal		
1 (1)				

V.			y.	
3	Compartmentation.		0111	
	Fire check door		14/1	
	<ul> <li>Sealing of electrical shafts</li> </ul>			
	<ul> <li>Fire Rating of shaft door</li> </ul>			
	<ul> <li>Water Curtain</li> </ul>			
	• Fire Dampers		Į.	
4	Smoke Management System.		NIA	
	<ul> <li>Basements</li> </ul>	30 a/c per hour	79/1	
	<ul> <li>Upper floors</li> </ul>	12 a/c per hour		
5	Fire Extinguishers		Davidala	10
	<ul> <li>Total numbers</li> </ul>	10 4B1/202/254	Provided. ABC	m/R m/R
	<ul><li>Types</li></ul>	ABC/C02 (2.5 kg)		MIR
	IS marking	ISI marked	yes	11/10
6	First-Aid Hose Reels.		0	m10
	• Total numbers on each floor	one	Provided Provided	mIR mIR mIR
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	min
	Nozzle diameter	5 mm	Provided	111/2
7	Automatic fire detection and alarmin	g system.	1 0	
	• Type of detectors		NIK	
opin or disconnection of the control	<ul> <li>Location of Main Panel</li> </ul>		1	
	<ul> <li>Location of Repeater Panel</li> </ul>			
	Alternate source of power			2
	***			
	<ul> <li>Hooters' Location</li> </ul>			
8	MOEFA		MIR	
9	Public Address System.		NIR	
10	Automatic Sprinkler System.			
	<ul> <li>Basement</li> </ul>		MIR	
	Live a control of the second common and the control of the control			4

	Upper Floor		MIR	
	Sprinkler above false ceiling		NIK	
: 1	Internal Hydrants			alika kan dana menangan menangan berapa dan kenangan dan menangan berapa dan kenangan berapa dan berapa dan be
	<ul> <li>Size of riser/down-comer</li> </ul>		NIR	
	<ul> <li>Number of hydrants per floor</li> </ul>		NIR	
	<ul><li>Hose Box</li></ul>		NIR	
12	Yard Hydrants.		/1//	
	<ul> <li>Total number of hydrants</li> </ul>	TO THE PARTY OF TH	NIR	
	<ul> <li>Hose Box</li> </ul>		NIR	
13	Pumping Arrangements.			
	<ul> <li>Ground Level</li> </ul>		MIR	
	Discharge of main Pump		A	
	Head of Main pump			
	Number of main pumps			
	➢ Jockey Pump out put			
	Jockey pump head			
	Standby Pump out put			
	Standby Pump Head			uar antoniona (n. 1820 e antonio e antoni
	Auto Starting/ Manual			
	stopping		* 1	
	Pump House Access			
	Terrace level	(10)	Day 'all or	mil
	Discharge of pump	220 L95 /mino	Provided _	mil
	Head of the pump	30 M		
	Power Supply		NIR	
	Auto Starting of pump		NIR	
14	Captive Water Storage for fire fighting.			
	<ul> <li>Underground tank capacity</li> </ul>		NIR	
	Draw-off connection		NIR	

	<ul><li>Fire service inlet</li><li>Access to tank</li></ul>		NIR	
	Overhead Tank capacity	2500 243.	3000 Lts.	MIR -
15	Exit Signage.		NIR	
16	Provision of Lifts.			
	• Pressurization of Lift Shaft		N/A	8
e de la companya de l	<ul> <li>Pressurization of Lift lobby</li> </ul>		-h-	
	• Communication In lift Car		-h-	
and the second s	• Fireman's Grounding Switch			1
	• Lift Signage		-h -	
17	Standby power supply		MIR	
18	Refuge Area.			
10 mm	Total Area		NIA	
	> Location		-11-	
19	Fire Control Room			
	Detector System Panel		MIR	
(b) (b) (the set between present	<ul> <li>Flow Switch Panel</li> </ul>		_u _	III
Action of the first designation of the first d	<ul> <li>PA System Panel</li> </ul>		72-	
The state of the s	Batter backup		71-	
	Building Floor Plans		-h-	
	Special Fire Protection Systems for Protection of special Risks, if any:	Mı'c_	Nic	Mic

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

D.O. (NO) leme DCfo (O)

6 bentations

F.T. M.scelf

Shy(a) ADO (RN) 15/12/2015 (SHYAM LAZ)