GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/school/2012/4760

Dated: 26/12/2012

FIRE SAFETY CERTIFICATE

Certified that M.C.D. Primary Girls School located at Rouse Avenue-1, New Delhi comprised of ground floor only, having total 10 rooms and one hall owned/occupied by MCD was inspected by the officer concerned of this department on 10.12.2012 in presence of Mr. Natiq Abbas (Principal) and found that the MCD have complied with the fire prevention and fire safety requirements in accordance with the Circular No-F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01-03-2011issued by the Directorate of Education dated 01-03-2011 and that the school building is fit for occupancy class "Educational" with effect from the date of issue of this certificate for a period of three years, subject to compliance of the conditions printed overleaf.

Issued on -24+12-2012---- at New Delhi by.

Chief Fire Officer Delhi fire service

Copy to: -

1. The Principal, M.C.D. Primary girls school, Rouse Avenue-1, New Delhi

2. The Director of Education, MCD (North), Kashmere Gate, Nigam Bhawan, Delhi

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- **6.** The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

| 0 | INSPE | CTION REPORT | <u>C</u> | | |
|-------------------------|---|---|---|--|--|
| | Type of Case : New Details of previous NOC : Letter Fire Safety directives letter No : File Date of inspection : Ic Name of the Inspecting Officers : Now Name and designation of officers from the building side : Now Year of Construction : Ic | Case /renewal TNO Estale Cc fi 1.12.2012 1.K. Chatto Fa | Da ini Sufely/2011/3 Alyay, ADO (| ated: | |
| S | | NBC | | | |
| N | o. prevention and fire safety U/R 33 | Requirement | Provided at site | The state of the s | |
| 1 | Access to building | • | | MR/NMR | |
| | Road width | 06 mt. | 18 on t (approx | MR | |
| | • Gate width | _ | 4 m 1- | | |
| Sphalamage control | Width of internal road | MA | | MR | |
| 2 | Number, Width Type & Appropriate | | J. + | 22 | |
| a. Number of staircases | | | | | |
| | Upper Floors | MA | M. A. | 77 | |
| | Basements | Ground floor only | N A | 22 | |
| | b. Width of staircases | Mr. | 24 | N. V | |
| | • Upper Floors | - | - | | |
| | Basements | MA | mm | MA | |
| | c. Protection of exits | MA | MA | Mr | |
| | | m s | MA | Ma | |
| | • Fire check door | m a | MA | MM | |
| | Pressurization | ma | MA | m r | |
| | e. No. of continuous staircases to terrace | a ma | OMA | 70 | |
| | g. Width of Corridor | MA | W o | MA | |
| | h. Door Size | ma | MA | mm | |
| | | MA | MA | 27 | |
| 3 | Compartmentation. | | - | | |



| 1 | | | | |
|---|--|-----------------|----------|------|
| | • Fire check door | mm | MA | 4 |
| | Sealing of electrical shafts | MA | - | Mm |
| | Fire Rating of shaft door | | MA | MA |
| | Water Curtain | MY | MA | MA |
| | • Fire Dampers | MA | MV | MA |
| 4 | Smoke Management System. | MA | n) 4 | Ma |
| | • Basements | | | |
| | Upper floors | 30 a/c per hour | mb | |
| | 11 - 40013 | 12 a/c per hour | | NA |
| 5 | Fire Extinguishers | | MA | Mo |
| | • Total numbers | 6.0 | | V |
| | • Types | ABC The | provided | MR |
| | IS marking | | porude | MR |
| 6 | First-Aid Hose Reels. | ISI marked | privide | MR |
| | | | | |
| | • Total numbers on each floor | | ma | mm |
| | Length of hose reel hose | 30 m | MA | |
| 7 | Nozzle diameter Automotic re | 5 mm | MA | .0 |
| | Automatic fire detection and alarming | system. | 1 11 | MA |
| | • Type of detectors | MA | W w | |
| | Location of Main Panel | | MM | MA |
| | Location of Repeater Panel | MA | MA | my A |
| | | N T | MA | MA |
| | Alternate source of power | MA | Mr | |
| | Hooters' Location | | | Mu |
| | MOEFA | n) n | Mm | MA |
| | Public Address System. | MA | MA | Mr |
| | Automatic Sprinkler System. | m a | MA | Ma |
| | Basement | • | , | |
| | | MA | MA | Mm |
| | • Upper Floor • Sprinkler above 6 1 | MA | | m ~ |
| | Sprinkler above false ceiling | | 7 1 | Mm |
| I | nternal Hydrants | MA | MA | Mr |
| | Size of riser/down-comer | MA | | 8 |
| | | 10.0 | MA | |

| • | Number of hydrants per floor | Mr | MA | MA |
|---|--|----------|----------|------|
| | Hose Box | MA | MA | MA |
| 12 | Yard Hydrants. | | ı | |
| | • Total number of hydrants | MA | 44 | NA |
| | Hose Box | 74 | MA | ny o |
| 13 | Pumping Arrangements. | | | |
| | Ground Level | MA | MA | WA |
| | Discharge of main Pump | MA | MA | MA |
| | Head of Main pump | MA | MA | MA |
| | Number of main pumps | MA | MA | WA |
| | Jockey Pump out put | .0 | WA | MA |
| | Jockey pump head | N) A | MA | MA |
| | Standby Pump out put | N/ A | MA | MA |
| | Standby Pump Head | | MA | |
| | Auto Starting/ Manual | N) A | | N/A |
| | stopping | MA | MA | 74 |
| THE COLUMN TWO IS NOT | Pump House Access | MA | MA | 24 |
| | Terrace level | MA | 7 A | MA |
| | Discharge of pump | MA | 7 4 | MA |
| Organical Association | Head of the pump | MA | n In | MA |
| | Power Supply | MA | 50 | Mm |
| | Auto Starting of pump | (' | 10/m | |
| 14 | Captive Water Storage for fire fighting. | | · · | 0 |
| | Underground tank capacity | MA | MA | MA |
| | Draw-off connection | MA | 74 | MA |
| | Fire service inlet | MA | MA | MA |
| | Access to tank | MA | MA | MA |
| | Overhead Tank capacity | MA | m) m | Mr |
| 15 | Exit Signage. | Required | Provided | MR |
| 16 | Provision of Lifts. | | 4- | |
| | Pressurization of Lift Shaft | MA | MA | MA |
| | Pressurization of Lift lobby | yn | MA | MIA |

| | Communication In lift Car | 0 | | |
|---|---|----------|-----------------|------|
| | | MA | MA | MA |
| | Fireman's Grounding SwitchLift Signs | 7A | 75 | |
| 7 | • Lift Signage | MA | MA | ~h |
| 7 | Standby power supply | YA | | No |
| 8 | Refuge Area. | | MA | MA |
| | Total Area | N/A | N/A | |
| | Location | N/A | | N/A |
|) | Fire Control Room | 124/11 | N/A | N/A |
| | Detector System Panel | W/T | MA | h) a |
| | Flow Switch Panel | MA | MA | MA |
| - | PA System Panel | NA | 10 | MA |
| | Batter backup | MA | W M | MA |
| - | Building Floor Plans | MA | V 4- | 0 |
| | Special Fire Protection Systems for | lequira | One And lite | wla |
| | Protection of special Risks, if any: | 1 | fu extensustate | MR |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew/grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Note:- The school building is comprised of ground floor only having total 10 rooms & one hall. The Signature of the Inspecting Of Name M.K.CHATTOPAD Designation ADO (HO)

Signature of the Inspecting Officer M.K.CHATTOPADHYAY Designation ADO (HO)