GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001.

No. F6/DFS/MS/ EH/ 2012/ 4767

Dated 27/12/12

FIRE SAFETY CERTIFICATE

Issued on2.7. 1.12 1.2....... at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy to:

1. The Manager, Mc Donald's family restaurant, Showroom No. 17-24, Grindlays Cinema, New Friends Colony, New Delhi-110057

Conditions for the validity of Fire Safety Certificate

- a) All the Fire Safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b) Building Sanctioning Authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d) The Basement shall be used strictly as per the provisions of Building Bye Laws.
- e) The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1.	Name and address of the building	· Me I	CONALD'S FA	MILL PREPAU	PANT als	
1	rume and dadress of the building					
			com No: 17-2			
		A n	FRIENDS COLO	NY NEW DE	3CH1 - 57	
2.	Type of Occupancy	: - 471	US Home"			
3.	Type of Case	: Rene				
4.	Details of previous NOC	: FB/M3	DFS EH 2008/	1569 Dt	11.06.2008	
5.	Fire Safety Directives letter No	: NIL				
6.	Date of Inspection	: 09-09	5-2012		-	
7.	Name of the Inspecting Officer	: Rajan Wadehra, ADO/MRd.				
	Name and designation of the					
	Officers from the building side	: Why !	D.W Thaken	Manag	ei	
9.	Year of Construction	:				
10. Applicant's letter No. : Wil dr 04.04.2012						
S.	Minimum Standards on Fire Pro	evention	NBC	Provided at	Remarks	
No. 1	and Fire Safety U/R 33 Access to building		Requirement	site	MR/NMR	
	Road width	Υ.	20 001	5 101	10	
	Gate width		20 Mz	20 Mts NA	MIR	
8	Width of internal road		NA	NA	NA	
2	Number, Width, Type & Arranger	nent of Exit		_		
	Number of Staircase	NA (Ground flow only)				
	Upper floors				1	
	> Basement					
	Width of StaircaseUpper floors		NA			
	Basement					
	• Protection of Exits		NA			
	Upper floors				`	
	> Basement					
a	No of Continuous Staircases to	terrace	NA	WA	NA	
	Width of Corridor		NA	NA	NA	
	Door Size		NA	NA	NA	

3	Compartmentation					
+	Fire check door			,		
	 Sealing of electrical shafts 			1		
	Fire rating of shaft door					
	Water curtain			-		
	Fire Dampers	1				
4	Smoke Management System	MA				
	Basements	30 a/c Per hour				
The state of the s	Upper Floors	12 a/c Per hour				
5	Fire Extinguishers					
	Total Number	8 /300 m 2	8 Nos	MIR		
	• Types		60042ABC	mir		
	IS marking	ISI mark	VES	MIK		
6	First-Aid Hose Reels					
	Total Number on each floor	/Per Floor	~ 1	MIR		
	Length of hose reel hose	30 m	30m	MIR		
	Nozzle diameter	5mm	Smm	mir		
7	Automatic Fire Detection and Alarming System					
	Type of detectors	Required	Provoled	NIA		
	Location of Main Panel	4. P	48	MIR		
	Location of Repeater Panel	NA	NA	NA		
	Alternate source of power		3	100		
	Hooter's Location	NB	NA	NA		
8	MOEFA	Required	Proud	MIR		
9	Public Address System	Ma	MA	MA		
10	Automatic Sprinkler System					
	Basement	AM	NO	MA		
	Upper Floor	Required	Provided	NA		
	Sprinkler above false ceiling	No	MA	NA		
11	Internal Hydrant					
	Size of riser/down comer	100 mm	100 mm	MIR		
	Number of hydrants per floor	2	2	mik		
	Hose Box	2	. 2_	mir		
12	Yard Hydrant MA					
	Total Number of hydrants					
	Hose Box					
	1		1	1		

13	Pumping Arrangements			*		
	Ground Level					
	Number of main pump	2 My	2 Nus	MR		
	Discharge of main pump	28564PM	2850 cm	min		
	➤ Head of main pump	Famh	fort	MM		
	Jockey pump out put	950 LOM	950 cpm	min		
	Jockey pump Head	Fornh	tomh	min		
	Standby pump out put	2850 CM	2850 cm	min		
	Standby Pump Head	Fort	Forms	MIR		
	Auto Starting/Manual stopping	Auto.	Artu	MIR		
	➤ Pump House Access	Regard	Pron.l.	MIR		
	Terrace level					
	Discharge of pump		/			
	➤ Head of the pump					
	> Power Supply					
	Auto starting /Manual stopping	X	-			
14	Captive Water Storage for Fire Fighting					
	Underground tank capacity	2,000,004	2,00,000 y	MW		
	> Draw-off connection	Recessed	, Promot	m		
	➤ Fire service inlet	Le Cost	Small.	MIN.		
	Access to tank	Lesink	man le	nln		
	Overhead tank capacity	351050 ch	25,000 ds	MX		
15	Exit Signage	Required	brouded	MA		
16	Provision of Lifts	V	MA			
	Pressurization of Lift Shaft		_ /			
	 Pressurization of Lift lobby 					
	 Communication in lift Car 					
	 Fireman's Grounding Switch 					
	Lift Signage		/			
17	Standby Power Supply		3			
18	Refuge Area	H	Λ			
	Total Area		h	,		
	 Location 					
19	Fire Control Room	K.	ΛQ			
19		<u> </u>	1A	1		
19	Detector System Panel	<u> </u>	1 ft			
19	Detector System PanelFlow Switch Panel	<u> </u>	1A			
19	 Detector System Panel Flow Switch Panel 	N	I A			

20 Special Fire Protection System for Protection of special risk, if any

4 My ABC

4 mosasse

MIR

The Fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules , It is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 / issue shortcomings as noted at serial Number.

Harbarant &

Signature of Inspecting Officer

Name :

RAJAN WADEHRA

Designation: ASST. DIV. OFFICER

DO (South)

wisth-