GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2012/ 47 62

Dated: 28/12/2012

FIRE SAFETY CERTIFICATE

Certified that M/s Noor Guest House located at 420-21 &25, Gali Matia Mahal, Jama Masjid, Delhi comprised of ground floor (Commercial use), first floor (11 guest rooms + reception), second floor (15 guest rooms), third floor(15 rooms) and fourth floor(07 rooms) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2009/3930 dated 31-12-2009. The premises was re-inspected by the officer concerned of this department on 10-12-2012 in the presence of Mazhar Ahmed, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 26/12/26/L for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 26/12/2012 at New Delhi by.

Chief Fire Officer Delhi fire service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi w.r.t. your letter No. 57986/Addl.C.P./Lic(H) dated 03-10-2012

2. The Owner, M/s Noor Guest House, 420-21 & 25, Gali Matia Mahal, Jama Masjid, Delhi

Conditions for the validity of fire safety certificate

a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.

b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.

c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1	. Name & address of the building:	Guest Home, 4	120-21 L25, Malia	Makel, Jama
2	2. Type of Occupancy : Lodgin	House / Club Masji	d, Delhe-	
		al / New ease	U	
4	Details of previous NOC : Letter I	No. FE/DFS/MS/GA	-/2009/3930 Date	ed: 31/12/2009
5	5. Fire Safety directives letter No :			
6	Date of inspection :	10-12-2012		Manager H) duli 03/10/2012 vided at site Remarks MR/NMR MP Hy acceptable Me Mm Mm Mm Mm Mm Mm Mm Mm Mm
7	Name of the Inspecting Officers: M.K.C	Chattopadhyay, AD	OO(HQ)	
8	2. Name and designation of officers	0 . 0		
	from the building side : $\underline{\hspace{1cm}}$	azhar Ahmu	ed, Manager	
9	. Year of Construction :	1985		
10	O. Applicant's letter No. : 57	4986/Addl-CP	(4°CCH) dals 03	110/2012
S.	Minimum Standards on fire	NBC	Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMR
1	Access to building	/		
	Road width	spl area	(5mt (45mt)	MR
	• Gate width	-	Scirectly accessible from the round	MR
	 Width of internal road 	Mn		MA
2	Number, Width, Type & Arrangement	of Exits	1	
	a. Number of staircases			
	• Upper Floors	01	02	me
	 Basements 	MA	MA	ma
	b. Width of staircases		_	-
	• Upper Floors	0.80mt	1.14mt, 1.14mt	mr
	 Basements 	7 2	mm	MA
	c. Protection of exits	N/A	N/A	
	 Fire check door 	N/A	N/A	
	 Pressurization 	N/A	N/A	
	e. No. of continuous staircases to terrace	01		me
	g. Width of Corridor	N/A	N/A	
	h. Door Size	N/A	N/A	
		N/A	N/A	
2		A 1/ A X	1.7/1.8	
3	Compartmentation.			
	Fire check door	N/A	N/A	Min. Now have you have your may you care also any

9

The state of the s	 Sealing of electrical shafts 	N/A	N/A			
	Fire Rating of shaft door	N/A	N/A			
	Water Curtain	N/A	N/A			
	• Fire Dampers	N/A	N/A	No. 200 500 500 500 500 500 500 500 500		
4	Smoke Management System.					
	• Basements	30 a/c per hour		M		
	 Upper floors 	12 a/c per hour	1 A	70		
5			MA	no		
<u>J</u>	Fire Extinguishers					
	 Total numbers 	17 M3.	provided	me		
	• Types	walef co12 co as	Provided	ma		
_	• IS marking	ISI marked	provided	MR		
6	First-Aid Hose Reels.					
	 Total numbers on each floor 	01	provides	MR		
	 Length of hose reel hose 	30 m	pourde	MR		
	Nozzle diameter	5 mm	provided	MR		
	Automatic fire detection and alarming system.					
	 Type of detectors 	N/A	N/A			
	 Location of Main Panel 	N/A	N/A			
	 Location of Repeater Panel 					
	Alternate source of power	N/A	N/A			
	Hooters' Location	N/A	N/A			
	130ters Location	N/A	N/A			
	MOEFA	Required	povided	mn		
	Public Address System.	Required	provided	Me		
	Automatic Sprinkler System.	1				
	Basement Upper Flori	را ل	MA	MA		
-	 Upper Floor Sprinkler above false ceiling	Mn	Mr	Mr		
-		MA	MA	MA		
	Internal Hydrants			1"		
	• Size of riser/down-comer		(word more or)	Me		
	• Number of hydrants per floor		01			
The second second	• Hose Box			m2		
			01	MP		

() 1	Vand Hydrants			
12	Yard Hydrants.	NI/A	N/A	
	Total number of hydrants	N/A		40 40 50 50 50 50 50 50 50 50 50 50 50 50 50
	Hose Box	N/A	N/A	
3	Pumping Arrangements.	27/4	NT/A	
	Ground Level	N/A	N/A	
	Discharge of main Pump	N/A	N/A	
	Head of Main pump	N/A	N/A	
	Number of main pumps	N/A	N/A	
	Jockey Pump out put	N/A	N/A	and the first too and the set and the set and
	Jockey pump head	N/A	N/A	
	Standby Pump out put	N/A	N/A	
	Standby Pump Head	N/A	N/A	
	Auto Starting/ Manual	N/A	N/A	
	stopping	N/A	N/A	
	Pump House AccessTerrace level	N/A	N/A	
	Terrace levelDischarge of pump	225 LPM	450 LPM	MR
	Head of the pump	30 mm	· provido	May 12
	Power Supply	Required	pnndw	MR
	 Auto Starting of pump 	_	Starting Switch provided meer G. flr	MR
14	Captive Water Storage for fire fighting	ıg.		
	 Underground tank capacity 	N/A	N/A	
	 Draw-off connection 	N/A	N/A	
	Fire service inlet	N/A	N/A	
			NT/ A	
	Access to tank	N/A	N/A	the time age age that the time time to the time
	Access to tankOverhead Tank capacity	N/A 2500 lh	lo, on th	MR
				MR
15	Overhead Tank capacity	2500 lh	lo, on th	
15	Overhead Tank capacity Exit Signage.	2500 lh	lo, on th	
15	Overhead Tank capacity Exit Signage. Provision of Lifts.	2 Soo 1h Required	lo, on th Provided	MR
15	 Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft 	2 Soo Ih Required	Provided MA	MR MA

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant / renew Fire Safety Certificate under rule DCF-N 2000. 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation :- Asstt. Div. Officer(HQ)