GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2012/ 4769

Dated: 26/12/2012

FIRE SAFETY CERTIFICATE

Certified that M/s Shri Sai International guest house located at 7969, Arakashan road, Paharganj, New Delhi comprised of ground floor (Reception + 01 guest rooms), first floor (03 guest rooms), second floor (03 guest rooms), third floor (03 guest rooms) and fourth floor (03 guest rooms) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2009/2654 dated 27-08-2009. The premises was re-inspected by the officer concerned of this department on 14-12-2012 in the presence of Mr. Santosh Kumar, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 26/12/2014 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules, 2010.

Issued on 26/12/2012 at New Delhi by.

Chief Fire Officer Delhi fire service

Copy to: -

- 1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi w.r.t. 57491-92/Addl.C.P./Lic(H) dated 01-10-2012
- 2. The Manager, M/s Shri Sai International guest house, 7969, Arakashan road, Paharganj, New Delhi

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT : Renewal / New case : Letter No. F6 | D & /MS | GH | 2009 | 2654 Dated: 27/8 | 2009 3. Type of Case 4. Details of previous NOC 5. Fire Safety directives letter No : 14-12-2012 6. Date of inspection 7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(HQ) 8. Name and designation of officers Shri Santosh Kumar, Manager 2003 57491-92 Addl. C.P / Lic(14) deta 01/10/2012 from the building side 9. Year of Construction 10. Applicant's letter No. Remarks Provided at site Minimum Standards on fire S. MR/NMR Requirement prevention and fire safety U/R 33 No. 12 ft (3.6mt) Access to building m 12 1 Spl area from the rand Road width MR Gate width N/A Width of internal road N/A Number, Width, Type & Arrangement of Exits 2 a. Number of staircases MR 01 01 Upper Floors N/A N/A Basements b. Width of staircases mr 1.3321 0.80mt Upper Floors ______ N/A N/A Basements ----N/A c. Protection of exits N/A Fire check door N/A N/A -----N/A Pressurization N/A MP 01 e. No. of continuous staircases to terrace 01 N/A g. Width of Corridor N/A N/A N/A h. Door Size N/A N/A

7

3	Compartmentation.	Not required		3		
	Fire check door	N/A	N/A			
	 Sealing of electrical shafts 	N/A	N/A			
	• Fire Rating of shaft door	N/A	N/A			
	Water Curtain	N/A	N/A			
	• Fire Dampers	N/A	N/A	00 000 000 000 000 000 000 000 000 000		
4	Smoke Management System.					
	Basements	30 a/c per hour	N/A	N/A		
	• Upper floors	12 a/c per hour	<u> </u>			
-		2	N/A	N/A		
5	Fire Extinguishers					
	 Total numbers 	08 M3	pomodo	MR		
	• Types	ABC, MET COL	provida	MR		
	IS marking	ISI marked	poonds	Ma		
6	First-Aid Hose Reels.					
	 Total numbers on each floor 	01	provide	MR		
	• Length of hose reel hose	-30 m	provide	MR		
	Nozzle diameter	5 mm	provider	MR		
7	Automatic fire detection and alarming system.					
	• Type of detectors	N/A	N/A			
	Location of Main Panel	N/A	N/A			
	Location of Repeater Panel	N/A	N/A			
	Alternate source of power	N/A	N/A	100 MP FM TO TO TO TO TO TO TO TO TO		
9	Hooters' Location	N/A	N/A	100 M		
8	MOEFA	Required	provided	MR		
9	Public Address System.	Required	provided	Me		
10	Automatic Sprinkler System.					
	Basement	N/A	N/A			
	 Upper Floor Sprinkler above false ceiling	N/A	N/A			
	opinister above raise centing	N/A	N/A			

11	Internal Hydrants					
	• Size of riser/down-comer	N/A	N/A			
ū	Number of hydrants per floor	N/A	N/A			
	• Hose Box	N/A	N/A			
12	Yard Hydrants.					
	 Total number of hydrants 	N/A	N/A			
	Hose Box	N/A	N/A			
13	Pumping Arrangements.		·			
	Ground Level	N/A	N/A			
	Discharge of main Pump	N/A	N/A			
	Head of Main pump	N/A	N/£.			
	Number of main pumps	N/A	N/A			
	Jockey Pump out put	N/A	N/A			
	Jockey pump head	N/A	N/A			
	Standby Pump out put	N/A	N/A			
	Standby Pump Head	N/A	N/A			
	Auto Starting/ Manual	N/A	N/A			
	stopping	N/A	N/A			
	 Pump House Access Terrace level 	- 100 h	_			
	Discharge of pump	225 LPM	provided	MR		
	➤ Head of the pump	30mr	(Dourse)	MR		
	Power Supply	_	-	_		
	Auto Starting of pump	Requeired	starting Switch provide	D MR		
14	Captive Water Storage for fire fighting.					
	Underground tank capacity	N/A	N/A			
	Draw-off connection	N/A	N/A			
	Fire service inlet	N/A	N/A			
	Access to tank	N/A	N/A			
	Overhead Tank capacity	2500 14	woo the	mrz		
15	Exit Signage.	Required	Provided	MR		



16	Provision of Lifts.					
		N/A	NI/A	and the second		
	Pressurization of Lift Shaft	IN/A	N/A			
	 Pressurization of Lift lobby 	N/A	N/A			
	Communication In lift Car	N/A	N/A			
	• Fireman's Grounding Switch	N/A	N/A			
	Lift Signage	N/A	N/A			
17	Standby power supply	Mr	Mo	20		
18	Refuge Area.					
	Total Area	N/A	N/A	NO		
	> Location	N/A	N/A			
19	Fire Control Room					
	 Detector System Panel 	N/A	N/A	***************************************		
	• Flow Switch Panel	N/A	N/A			
	 PA System Panel 	N/A	N/A			
	Batter backup	N/A	N/A	WM COL COL COL COL COL COL COL COL COL		
	Building Floor Plans	N/A	N/A			
0	Special Fire Protection Systems for Protection of special Risks, if any:	Required	or Ase type fue ex ten fusha prossed new Elect panel	MR		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant/ renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

of the Delhi Fire Service Rules 2010.

Forwalded he godin 12-12

According to the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer
Name (M.K. CHATTOPADHYAY)
Designation: - Assistant Divisional Officer