GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No.F6/DFS/MS/School/2013/ / 44

Dated: $-\frac{9}{1}/\frac{1}{13}$

FIRE SAFETY CERTIFICATE

Issued on ---- at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to:- (1) Sarvodaya Co-Ed Sr. Secondary School, Moti Bagh-II,Nanak Pura,New Delhi.

90

(2) Director of Education, Old Secretariat, Delhi. Conditions for the validity of fire safety certificate

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire protections measures shall be maintained in perfect conditions all the time as seen during inspection.

3. All the staff members must know the correct method of operation of fire fighting system.

4. Any lapse rendering fire fighting system/equipment non-functional shall be the risk and responsibility of the management.

5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.

6. The owner/occupier shall submit a declaration every year in form 'K'provided in the first schedule of Delhi Fire Service Rules 2010.the form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

- 1. Name & address of the building:- Sarvodaya Co-Ed Sr. Secondary School, Moti Bagh-II, Nanak Pura, New Delhi.
- 2. Type of occupancy:-Group-B Education Building Schools up to Sr. Sec. Level.
- 3. Type of case:- New.
- 4. Details of previous NOC:- No
- 5. Fire safety directives No.- N/A as per education circular
- 6. Date of inspection: 19/12/12
- 7. Name of the inspecting officer:- A.D.O. S.S. Kaushik
- 8. Name & designation of officer:-
 - From the building side:- Mrs. Poonam Tandon (Principal).
- 9. Year of construction:- 1959.
- 10. Applicant's letter No:- 6649 dated 19/12/12 Ground + 1 Upper floors

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	As per Education Circular	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	Required	Approachable	MR		
	2) Gate width	Required	4 mtr.	MR		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangem	ent of Exits				
	A. Number of staircases					
47	1. Upper floors	Required	1 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
-	1. Upper floors	1.50 mtr.	1.55 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits	-				
• .	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase	Yes	one	MR		
	to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1_mtr.	1 mtr.	MR		
	Compartmentation					
No.	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
•	Smoke Management System					
	1) Basements	30 a/c per hour	N/A	N/A		
	2) Upper floors	12 a/c per hour	Open corridor	MR		
5.	Fire Extinguishers	\$ 1				
	1) Total numbers	ISI Marked	15 Nos.	MR		
	2) Types		ABC & co2	MR		
	3) ISI marking		Yes	MR		
	First-Aid Hose Reel	-				

	1) Total number of each floor			
	1) Total number of each floor	N/A	N/A	N/A
	2) Length of hose reel hose	30 m	27/4	
tr .	3) Nozzle diameter	5 mm	N/A	N/A
7.	Automatic Fire Detection & Alarm		N/A	N/A
	1) Type of detectors			
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
9, 10	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System	N/A	N/A	N/A
	1) Basement	DI/A		
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants	N/A	N/A	N/A
	1) Size of riser/down-comer	127/	2	
~	2) Number of hydrants per floor	N/A	N/A	N/A
	3) Hose box	N/A	N/A	N/A
12.	Vand Hadaa	N/A	N/A	N/A
	1) Total number of hydrants		Y.	
	2) Hose box	N/A	N/A	N/A
) 55 CON	N/A	N/A	N/A
13.	Pumping Arrangement			
	Ground level		H	
	a) Discharge of main pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
2 C	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	- y pamp output	N/A	N/A	N/A
	5 T many media	N/A	N/A	N/A
	h) Auto starting/Manual stopping2) Terrace level	N/A	N/A	N/A
		N/A	N/A	N/A
	- St of pump	N/A	N/A	N/A
	, and a paintp	N/A	N/A	N/A
		N/A	N/A	N/A
14.	, starting of build	N/A	N/A	N/A
	Captive Water Storage for Fire Fightin	g		17/11
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
15.	d) Over head tank capacity	N/A	N/A	N/A
16.	Exit Signage.	N/A	N/A	N/A N/A
10.	Provision of Lifts.	N/A	N/A	
	a) Pressurization of lift shaft	N/A		N/A
	b) Pressurization of lift lobby		N/A	N/A
	2) C	N/A	N/A	N/A
	III III VIII	N/A	N/A	N/A

	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	N/A	N/A	N/A
			-	1
18.	Refuge Area	N/A	N/A	N/A
10.	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	C D / / C of mariel Diely if any			

The fire protection system provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010/-----

Accordingly DFA is put up please.

Signature of the inspecting officer

Signature of the inspecting officer

Name:-

Name: - S.S.Kaushik

Designation:-

Designation:- Assistant Divisional Officer

DBouth 1