GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

No: F 6/DFS/MS/2013/5chcol/283

Dated:- 17/01/13

FIRE SAFETY CERTIFICATE

		111.10/11/2		
safety requirement in a verified by the officer should be be beared. Educational Three years in accordance	r concerned of Fire Stand that the	Complied with to of Education circles on 3.11.19 building/premises from	he fire prevention he fire prevention ular Dated:-01/03/ in the pre is fit for o	and fire 2011 and sence of occupancy period of
	w	. 8		
Issued on1.7.	.o.//at New D	elhi.		
	A		Chief	Fire Officer
Copy to:-			Delhi	Fire Service
1 The bring	4 Salvarol			of ghy
*	2-Block hewre deli 1108			
2 The Adol. North McD. Minton Rol	Civic Cuire		i eta	v v

Note:-This fire safety certificate is subject to compliance of the condition printed over leaf.

1. All the means of escape shall be kept free of all type of obstruction all the time is

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non - functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per MG

6. This NOC may not be treated in any case for regularizations of unauthorized. construction, if any,

7 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1/11/12

Primary Sch	_			
10:10		Gherra, Delhi-g		
Type of Case New Case/ Renewal				
4. Details of previous NOC : Letter No Dated:				
lar, Director	of Edun. 1-3	3-2011.		
20)2				
0-SHYAM	LAL			
Madan Bho	rod wai (Prin	(ipal)		
7, (5 No's S	heds.)			
Cinco On a Di				
Edno 1-2-11	Provided at site	Remarks		
Requirement		MISIN		
Accessible	9 m /	MIR		
-do-	3.80 M	MIR		
MA	NIA	NIA		
t of Exits				
NIR	NIP	NIA		
-) ~	-11-	-15-		
-11-	-n-	-h-		
•				
-11-	->> -	-)1 -		
	—J1~	-h		
		The second to		
NI/D	NI/D	NI/A		
		N/A N/A		
	1:71 m	miR		
	1 Moith down	P.U. MIR		
	No	No		

Compartmentation.					
 Fire check door 	N/R	N/P	N/A		
 Sealing of electrical shafts 	N/R	N/P	N/A		
 Fire Rating of shaft door 	N/R	N/P	N/A		
• Water Curtain	N/R	N/P	N/A		
• Fire Dampers	N/R	N/P	N/A		
Smoke Management System.					
 Basements 	30 a/c per hour	N/R	N/A		
Upper floors	12 a/c per hour				
		N/R	N/A		
Rire Extinguishers					
 Total numbers 	02	02	MIR		
Types	ABC or Co 2		MIR		
 IS marking 	ISI marked	yes	101)82		
First-Aid Hose Reels.					
 Total numbers on each floor 	N/R	N/R	N/A		
 Length of hose reel hose 	30 m N/R	N/R	N/A		
 Nozzle diameter 	5 mm N/R	N/R	N/A		
Automatic fire detection and alarming system.					
 Type of detectors 	N/R	N/P	N/A		
 Location of Main Panel 	N/R	N/P	N/A		
• Location of Repeater Panel	N/R	N/P	N/A		
 Alternate source of power 	N/R	N/P	N/A		
 Hooters' Location 	N/R	N/P	N/A		
MOEFA	N/R	N/P	N/A		
Public Address System.	N/R	N/P	N/A		
Automatic Sprinkler System.					
 Basement 	N/R	N/P	N/A		

F	• Upper Floor	N/R	N/P	N/A		
	 Sprinkler above false ceiling 	N/R	N/P	N/A		
y constant	Internal Hydrants					
	 Size of riser/down-comer 	N/R	N/P	N/A		
	Number of hydrants per floor	N/R	N/P	N/A		
	Hose Box	N/R	N/P	N/A		
	Yard Hydrants.					
	 Total number of hydrants 	N/R	N/P	N/A		
	 Hose Box 	N/R	N/P	N/A		
	Pumping Arrangements.					
	 Ground Level 	N/R	N/P	N/A		
	Discharge of main Pump	N/R	N/P	N/A		
	Head of Main pump	N/R	N/P	N/A		
	Number of main pumps	N/R	N/P	N/A		
	Jockey Pump out put	N/R	N/P	N/A		
	Jockey pump head	N/R	N/P	N/A		
	Standby Pump out put	N/R	N/P	N/A		
	Standby Pump HeadAuto Starting/ Manualstopping	N/R	N/P	N/A		
	Pump House Access	N/R	N/P	N/A		
	 Terrace level 	NIR	NIR	MIA		
	Discharge of pump	NIR	NIR			
	Head of the pump			NIA		
	Power Supply	N/R	N/P	N/A		
	Auto Starting of pump	NIR	NIR	NIA		
Brown and the second	Captive Water Storage for fire fighting.					
	 Underground tank capacity 	N/R	N/P	N/A		
	Draw-off connection	N/R	N/P	N/A		

	➤ Fire service inlet	N/R	N/P	N/A		
	Access to tank	N/R	N/P	N/A		
	 Overhead Tank capacity 	NIR	NIP	NIA		
15	Exit Signage.	NIR	NIP	NIA		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/R	N/P	N/A		
	 Pressurization of Lift lobby 	N/R	N/P	N/A		
	Communication In lift Car	N/R	N/P	N/A		
	* Fireman's Grounding Switch	N/R	N/P	N/A		
	Lift Signage	N/R	N/P	N/A		
17	Standby power supply		4			
18	Refuge Area.					
	> Total Area	N/R	N/P	N/P		
	Location	N/R	N/P	N/P		
19	Fire Control Room					
	 Detector System Panel 	N/R	N/P	N/A		
	 Flow Switch Panel 	N/R	N/P	N/A		
	 PA System Panel 	N/R	N/P	N/A		
	Batter backup	N/R	N/P	N/A		
	Building Floor Plans	N/R	N/P	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	NIL	NIL	N/A		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Recping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

D.O.(m)

Shylal