## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

NO. F6/DFS/MS/Ind./2013/ 3 8 4

DATED: 2 4 | 01 | 13

## FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

90

## Copy to,

- 1. The Executive Engineer (Bldg) HQ, Building Department, SDMC, 8<sup>th</sup> floor, Civic Centre, Minto Road, New Delhi110002
- 2. The Authorized Signatory, M/s Munna lal Ram Dayal Plot No. A-188, Okhla Industrial Area Phase I, New Delhi

## Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The basement shall be used strictly as per the provisions of Building Bye laws.
- e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules-2010. The form is available on www.dfs.delhigovt.nic.in

	IN	SPECTION	REPORT			
1	Name & address of the building	M/s Munna lal Ram Dayal at Plot No. A-188, Okhla Ind. Area Phasel, New Delhi				
2	Type of Occupancy	Industrial "G	Industrial "G"			
3	Type of case	New				
4	Details of previous NOC	No				
5	Fire safety directives letter No		y .			
6	Date of inspection	F.6/DFS/MS/BP/2010/1038 Dated 12.04.2010				
7	Name of the inspecting Officers :	24.12.2012				
8	Name and designation of officers	D.O. (South) D.P. Bhardwaj,				
0		Mr Gourav Khandelwal (Owner)				
	from the building side					
9	Year of construction	2005				
10	Applicant's letter No.	N.C.		P CAREFORM		t, Ground plus one
S. NO.	Minimum Standards on fire prevention	NII NBC Rec	Dt. 23.11.20 quirement		led at site	pper floor)
	and fire safety U/R 33	NDO KEK	quirement	Provid	ied at site	Remarks MR / NMR
1	Access to building					
	1) Road width	Accessible		15 Mtr Prov	ided	MR
	2) Gate width	5mtrs		Provided		MR
	3) Width of internal road	N/A		N/A		N/A
2	Number, width Type & arrangement of	exits				
	a. Number of staircases					Na.
	1. Upper floors	Two		Provided		MR
	2. basements b. Width of staircase	Two		Provided		MR
	b. Width of Staircase					
	1. Upper floors	1.5 mtrs		1.5 Mtr Prov	ided each	MR
	2. basements	1.5 mtrs		1.5 Mtr Prov	ided each	MR
	c. Protection of exits			-3		
	1. Fire check door	Required		Provided		MR
	2 Pressurization	N/A		N/A		N/A
	d. No. of continuous staircase to terrace	Two		Two Provide	d	MR
	e. Width of corridor	N/A	N/A		n 8 8	N/A
	f. Door size	N/A		N/A N/A	* .	N/A
3	Compartmentation.				A 19	
		Required		Provided		MR
	lo =: =	Required		Provided		MR
	I.	Required		Provided		MR
	l	N/A		N/A		N/A
4		Required		Provided		MR
*	Smoke Management system.	30 a/c per hou	ır 40			
		a/c per not a/c per hour	ai 12	Exhust Fans	Provided	MR
	upper floors	,		Mech. Ventila	ation	_    MR
5	Fire Extinguishers		2			
E N	Total numbers			15 Nos		MR
	Types		,	ABC, Co2,		MR
	ISI marking	ISI		Yes		MR

6	First-Aid Hose Reels.		4					
	Total numbers on each floor	One	Provided	MR				
	Length of Hose reel hose	30 m	Provided	MR				
	Nozzle Diameter	5 mm	Provided	MR				
7	Automatic fire detection and alarming system							
	Type of detectors	Required	Provided (Smoke)	MR				
	location of Main Panel	Required	Provided (Ground)	MR				
	location of Repeater panel	N/A	N/A	N/A				
	Alternate source of power	Required	Battary Backup	MR				
	hooter's location	Required	Staircase Provided	MR				
8	MOEFA	Required	Provided	MR				
9	Public Address System.	N/A	N/A	N/A				
10	Automatic Sprinkler System.							
	basement	Required	Provided	MR				
	upper floors	Required	Provided	MR				
	sprinkler above false ceiling	Required	Provided	MR				
11	Internal Hydrants		•					
	Size of riser/down-corner	150 mm	Provided	MR				
	Number of Hydrants per floor	One	Provided	MR				
	hose Box	One	Porvided	MR				
12	Yard Hydrants.							
	total number of hydrants	Required	Provided (4 Nos)	MR				
	hose box	Required	Provided (4 Nos)	MR				
13	Pumping arrangements	·						
	1. Ground level							
	a. Discharge of main Pump	2280 LPM	2280 LPM Provided	MR				
	b.Head of main pump	70 Mtr	70 Mtr Provided	MR				
	c.Number of main pumps	One	One	MR				
	d.jockey pump out put	180 LPM	180 LPM Provided	MR				
	e.jockey pump head	70 Mtr	70 Mtr Provided	MR				
	f. Standby Pump output	2280 LPM	2280 LPM Provided	MR				
	g.Stanby Pump head	70 Mtr	70 Mtr Provided	MR				
	h.Auto Starting/Manual stopping	Required	Provided (Both)	MR				
	pump house access	Required	Provided	MR				
	2.Terrace level	required						
	a. Discharge of pump	900 LPM	900 LPM Provided	MR				
	b. head of the pump	40 mtr	40 Mtr Provided	MR				
	c. Power supply	Required	Provided	MR				
	d. Auto starting of pump	Required	Provided	MR				
14	Captive water storage for fire fight			v.,				
2	Underground tank capacity	1,00,000 ltr	1,00,000 ltr Provided	MR				
	a. Draw-off connection	Required	Provided	MR				
	b. fire service inlet	Required	Provided	MR				
	c.Access to tank	Required	Provided	MR				
	Over head tank Capacity	20,000 ltr	20,000 ltr Provided	MR				
15	Exit Signage.	Required	Provided	MR				
16	Provision of lifts.			V.				
	a. Pressurization of lift shaft	N/A	N/A	N/A				
	b. pressurization of lift lobby	N/A	N/A	N/A				
	c. communication in lift car	N/A	N/A	N/A				
	d. Fireman's grounding switch	N/A	N/A	N/A				
	e. Lift signage	N/A	N/A	N/A				
17	Standby power supply	Required	Provided	MR				

18	Refuge Area.		Not Required	
	total area			
	location			
19	Fire control room			
	a. Detector system Panel	Required	Provided	MR
	b. Flow switch Panel	N/A	N/A	N/A
	c. PA system Panel	N/A	N/A	N/A
	d. Batter backup	Required	Provided	MR
	e. Building floor plans	N/A	N/A	N/A
20	Special Fire Protection systems	for protection of special	risks, if any:	

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010

Accordingly DFA is put up for your approval and signature please.

Signature of the inspecting officer

Name D. P. Bhardwaj

Designation: Divisional Officer (South)

111