GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI - 110001

No: F 6/DFS/MS/2013/ school / 392

Dated: 24/01/13

FIRE SAFETY CERTIFICATE

ho
Certified that the MCD brimary Co-Ed-School SecT-B-4 PKT-7 Narela Delin comprised of Good + one
PKt-7 Narela Delin comprised of Ground + one
owned/occupied by M CD
comprised of word to the fire prevention and fire safety requirement in accordance with filments of files.
surely requirement in detailed with hipportor of Education circular Datad, 04/03/2044
VEHILLED DV The Officer concerned of Fine C
Shaper kma (see a) and that the building/premises is fit for occupancy building with effect from 24/01/13 for a period of Purse years in accordance with rule 36 unless renewed and hard here as in accordance with rule 36 unless renewed and here he as in accordance with rule 36 unless renewed and here he as a period of
Public was in a period of
minimi accordance with rule 50 utiless renewed under rule 37 or sooner cancelled under
Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.
19.40, 20.10.
Issued on 21/10//12

Copy to:-

1 The brincipel

MCD PS. Co-Ed School

Sect- B-4 PKt-7 Narele Delhi

2 The Addl-Disesson (Edn.) North Med Civic Cenise Minioto Road N-Delli

Delhi Fire Service

Note:-This fire safety certificate is subject to compliance of the condition printed over leaf.

1. All the means of escape shall be kept free of all type of obstruction all the time

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non — functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per FBC

6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any

construction, If any,
The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

			1.2 M Two door each	
h. Door Size		9 m	1.2m	mle
g. Width of Corridor		R	2.7 m	mld
e. No. of continuous staircas	es to terrace	L 1/ L L	17/1	1.4/1.7
 Pressurization 		N/R	N/P	N/A
 Fire check door 		N/R	N/P	N/A
c. Protection of exits		, ,, .	(5):	
 Basements 		Nic	Nº L	N.'L
 Upper Floors 		1.5 m	1.8m	MIR
b. Width of staircases				
 Basements 		N.C	NiL	NIL
 Upper Floors)	1/	mse
a. Number of staircases		1	10	MIR
Number, Width, Type & A	Arrangement	of Exits		
 Width of internal roa 	ad	-11-	open grown	d mik
 Gate width 		-h-	ym	mil
 Road width 		Accessible	6 m	mik
Access to building		2 1 1		
o. prevention and fire safe	ety U/R 33	Requirement	91/	MR/NMR
. Minimum Standards			Provided at site	Remarks
10. Applicant's letter No.	: 1		7-11-2012	
9. Year of Construction:	200	4 (Gir.+1)	le Portacabi	n 8 Rooms
from the building side	2		mar (Teacher	
8. Name and designation of o	ec			
7. Name of the Inspecting O			m 1 1 1	
5. Fire Safety directives lette6. Date of inspection:	1 NO : 470	2017 Dar. 07	Edun. 1/3/2	01)
4 Details of previous NOC		No. No.		
3. Type of Case		ase/ Renewal -		
2. Type of Occupancy:	Educatio	onal		Narela, De
1. Name & address of the bu	ilding: MCJ	Primary C	o. Ed. School,	Sect-B-4, P

3	Compartmentation.					
	Fire check door	N/R	N/P	N/A		
	 Sealing of electrical shafts 	N/R	N/P	N/A		
	• Fire Rating of shaft door	N/R	N/P	N/A		
	Water Curtain	N/R	N/P	N/A		
	• Fire Dampers	N/R	N/P	N/A		
4	Smoke Management System.	2				
	Basements	30 a/c per hour	N/R	N/A		
	• Upper floors	12 a/c per hour				
	10000000000000000000000000000000000000	- ,- Etc.,	N/R	N/A		
5	Fire Extinguishers					
	 Total numbers 	03	03/	mik ms R msR		
	Types	ABC/Co2/2.5	X ABC	msR		
	IS marking	ISI marked	Provide of	Men		
6	First-Aid Hose Reels.					
	• Total numbers on each floor	N/R	N/R	N/A		
	 Length of hose reel hose 	30 m N/R	N/R	N/A		
	Length of hose reel hoseNozzle diameter	30 m N/R 5 mm N/R	N/R N/R	N/A N/A		
7		5 mm N/R				
7	Nozzle diameter Automatic fire detection and alarming s	5 mm N/R				
7	 Nozzle diameter Automatic fire detection and alarming Type of detectors 	5 mm N/R system. N/R N/R	N/R	N/A		
7	 Nozzle diameter Automatic fire detection and alarming Type of detectors Location of Main Panel 	5 mm N/R system. N/R	N/R N/P	N/A		
7	 Nozzle diameter Automatic fire detection and alarming: Type of detectors Location of Main Panel 	5 mm N/R system. N/R N/R	N/R N/P N/P	N/A N/A N/A		
7	 Nozzle diameter Automatic fire detection and alarming: Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	5 mm N/R system. N/R N/R N/R	N/R N/P N/P N/P	N/A N/A N/A		
	 Nozzle diameter Automatic fire detection and alarming Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	5 mm N/R system. N/R N/R N/R N/R N/R	N/R N/P N/P N/P N/P	N/A N/A N/A N/A		
8	 Nozzle diameter Automatic fire detection and alarming: Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	5 mm N/R system. N/R N/R N/R N/R N/R N/R	N/R N/P N/P N/P N/P N/P	N/A N/A N/A N/A N/A		
7	 Nozzle diameter Automatic fire detection and alarming: Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA	5 mm N/R system. N/R N/R N/R N/R N/R N/R N/R	N/R N/P N/P N/P N/P N/P N/P	N/A N/A N/A N/A N/A N/A		

	Upper Floor	N/R	N/P	N/A		
	Sprinkler above false ceiling	N/R	N/P	N/A		
V-m-rand V-m-rand	Internal Hydrants					
	Size of riser/down-comer	N/R	N/P	N/A		
	 Number of hydrants per floor 	N/R	N/P	N/A.		
 Hose Box 	Hose Box	N/R	N/P	N/A		
12	Yard Hydrants.					
	Total number of hydrants	N/R	N/P	N/A		
	 Hose Box 	N/R	N/P	N/A		
13	Pumping Arrangements.					
	Ground Level	N/R	N/P	N/A		
	> Discharge of main Pump	N/R	N/P	N/A		
	Head of Main pump	N/R	N/P	N/A		
	Number of main pumps	N/R	N/P	N/A		
	Jockey Pump out put	N/R	N/P	N/A		
	Jockey pump head	N/R	N/P	N/A		
	> Standby Pump out put	N/R	N/P	N/A		
	> Standby Pump Head	N/R	N/P	N/A		
	Auto Starting/ Manual stopping					
	Pump House Access	N/R	N/P	N/A		
	Terrace level		NIR			
	Discharge of pumpHead of the pump		NIR			
	Power Supply	N/R	N/P	N/A		
	Auto Starting of pump		NIR			
14	Captive Water Storage for fire fighting	•				
	Underground tank capacity	N/R	N/P	N/A		
	Draw-off connection	N/R	N/P	N/A		

	Fire service inlet	N/R	N/P	N/A	
	Access to tank	N/R	N/P	N/A	
	 Overhead Tank capacity 	1\/1\	NIR	14//	
15	Exit Signage.		MIR		
16	6 Provision of Lifts.				
	Pressurization of Lift Shaft	N/R	N/P	N/A	
	 Pressurization of Lift lobby 	N/R	N/P	N/A	
	Communication In lift Car	N/R	N/P	N/A	
	• Fireman's Grounding Switch	N/R	N/P	N/A	
	• Lift Signage	N/R	N/P	N/A	
17	Standby power supply		MIR		
18 Refuge Area.					
	> Total Area	N/R	N/P	N/P	
	> Location	N/R	N/P	N/P	
19	Fire Control Room				
	 Detector System Panel 	N/R	N/P	N/A	
	 Flow Switch Panel 	N/R	N/P	N/A	
	PA System Panel	N/R	N/P	N/A	
	Batter backup	N/R	N/P	N/A	
	 Building Floor Plans 	N/R	N/P	N/A	
20	Special Fire Protection Systems for	NIL	NIL	N/A	
	Protection of special Risks, if any:		2		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

Dofting Deformings as

Dofting

Deform

29/12/2012 ADO(RN) (SHYAMLAZ)