GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No.

F6/DFS/ms/scholl2013/417

Dated: 3°/ °/ /2013

FIRE SAFETY CERTIFICATE

Certified that the St. Martin's Public School located at A-2, Paschim Vihar, New Delhi comprised of Ground + Three upper floors occupied by St. Martin's Public School was issued NOC vide this office letter no. F.6/DFS/MS/09/349 Dated 05/2/2009. The premises was re-inspected by the officers concerned of this department on 24/01/2013 and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have therefore, deemed complied with the Director of Education circular Dated 01/03/2011 and the building/ premises is fit for occupancy Class Educational with effect from 30 41/2013 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 3001 13 at New Delhi.

CHIEF FIRE OFFICER
DELHI FIRE SERVICE

Copy to:

- 1. The Chair Person, St. Martin's Public School, A-2, Paschim Vihar, NewDelhi.
- 2. The Director (Education), Govt. of NCT of Delhi, Old Sectt. Delhi.

Following fire safety directives must be adhered to

- 1. All the Means of escape shall be kept free of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation with regards to construction, electrical installation etc. may be got verified from the concerned authorities.
- 5. Basement shall be used as per NBC.
- 6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

	INSPEC	TION REPORT							
	1. Name & address of the building: St - N	Postin's Rebl	ic School						
,		cational							
3. Type of Case : New Case/ Renewal									
4. Details of previous NOC : Letter No. F-6 DFS ms 09 349 Dated: 05 02 2009 5. Fire Safety directives letter No : 6. Date of inspection : 24 1 2013 7. Name of the Inspecting Officers : ADO (WP)									
						8. Name and designation of officers			
						from the building side : Mr.	Ipender Kur	nar, Caretale	u
					9	from the building side : Mr. (2. Year of Construction : 200 S 0. Applicant's letter No. : SMPS	,)		
1	0. Applicant's letter No. : รูกกุร	18743/01/20	o13 dt: 19/1/2	013					
5. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks					
	·	Acquirement		MR/NMR					
	Access to building			V					
	Road width	6 mtr.	Provided	MR					
	Gate width	4.5 mits	Privided	MR					
	Width of internal road	MR	NIA						
	Number, Width, Type & Arrangement of E		77 1)						
	a. Number of staircases	0							
	Upper Floors	3	3	mR					
	Basements	3	3	mR					
	b. Width of staircases	N/A		·					
	of conservation of contractions	0.0							
	Upper Floors Passaments		& Provided (3	m R					
	Basements Drotaction of acits	NIA							
	c. Protection of exits		_						
	Fire check door	NR	NP						
- 1	 Pressurization 	NR	NP						
) T								
	e. No. of continuous staircases to terrace	03	03	MR					
	e. No. of continuous staircases to terraceg. Width of Corridorh. Door Size	03 1.5 mtr.	borided	MR					

3	Compartmentation.			
<i>J</i>	•			
	Fire check door	NI		
	 Sealing of electrical shafts 		· sed	
	• Fire Rating of shaft door		Required	
	Water Curtain	Mex	The Y	
	• Fire Dampers	,		
4	Smoke Management System.			
	Basements	30 a/c per hour	NIR	
	Upper floors	12 a/c per hour	Opentosby	MR
5	Fire Extinguishers		0/0///-0//	1111
	Total numbers	16	18	MR
	• Types ARC			MR
	• Types • IS marking	ISI marked	Provided	
6	First-Aid Hose Reels.	1719,	Prinicled	mR
	Total numbers on each floor	09		20.8
	THE STATE OF STATE OF THE STATE	02	Burided	me
	• Length of hose reel hose	30 m	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
7	Automatic fire detection and alarming sys	stem.		
	Type of detectors		3	
	Location of Main Panel		1	
	Location of Repeater Panel		Reguised	
	Alternate source of power	Mal	V	
	Hooters' Location			
8	MOEFA	NR	NP	40
9	Public Address System.	NR	Provided	MR
10	Automatic Sprinkler System.		,,,,	
	Basement			
	Upper Floor		Lot Repuire	d
	Sprinkler above false ceiling		NOT ICEPA	
11	Internal Hydrants			
	Size of riser/down-comer	1-2 2000	0(1-1	D (2
		100 mm	Provided	MR

Hose Box 12 Yard Hydrants.		Number of hydrants per floor	0.0	0	
13 Pumping Arrangements. • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Standby Pump lead > Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump (Captive Water Storage for fire fighting.) 14 Captive Water Storage for fire fighting. • Underground tank capacity > Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity • Pressurization of Lifts. • Pressurization of Lift Shaft				0	mR
• Total number of hydrants • Hose Box 13 Pumping Arrangements. • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey Pump out put > Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Head of the pump > Power Supply > Auto Starting of pump Captive Water Storage for fire fighting. • Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft	12	Yard Hydrants.	02	Provided	MR
Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Head of the pump Power Supply Auto Starting of Pump Provided MR Pequired Branded MR Captive Water Storage for fire fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Sport to make the puire of the provided MR Required Provided MR Required Provided MR Required Provided MR Provision of Lifts.				0	*
Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Head of the pump Power Supply Auto Starting of pump Power Supply Auto Starting of fump Provided mr Required Branded mr It Captive Water Storage for fire fighting. Underground tank capacity Traveled mr Required Branded mr Required Fronded mr Special formation mr Special formation mr Required Fronded mr			05	monded	me
• Ground Level • Discharge of main Pump • Head of Main pump • Number of main pumps • Jockey Pump out put • Standby Pump bead • Standby Pump Head • Auto Starting/ Manual stopping • Pump House Access • Terrace level • Discharge of pump • Head of the pump • Power Supply • Auto Starting of pump • Head of the pump • Power Supply • Auto Starting of pump • Underground tank capacity • Draw-off connection • Fire service inlet • Access to tank • Overhead Tank capacity 5, see Ut 10, one Uts Required Provided MR	13		05	Provided	me
> Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump Dut put > Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Pequired Provided MR Lequired Provided MR	13		,		
Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Pequired Required Transled MR Captive Water Storage for fire fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Standby Pump Head Leguired Required Required Required MR Required Required MR Required Provided MR Required Required Required Required Required MR Required Provided MR					
> Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump out put > Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Power Supply Provided MR					
> Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump out put > Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Provided MR Required Provided MR Captive Water Storage for fire fighting. • Underground tank capacity > Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity Spood to be provided on the pump of					
> Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Power Supply Captive Water Storage for fire fighting. Underground tank capacity Draw-off connection Provided MR Access to tank Provided MR Overhead Tank capacity Spoot Use S					
> Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Captive Water Storage for fire fighting.					
> Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Power Supply Captive Water Storage for fire fighting.				Dogwise	
> Auto Starting/ Manual stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Captive Water Storage for fire fighting.				The last	
Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity S, soo Ut 10, oro Uts. MR Provision of Lifts. Pressurization of Lift Shaft		Standby Pump Head		Mo.	
• Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump 14 Captive Water Storage for fire fighting. • Underground tank capacity > Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity 5,000 Ut 10,000 Uts MR 15 Exit Signage. Provision of Lifts. • Pressurization of Lift Shaft		Auto Starting/ Manual stoppingPump House Access			
Head of the pump Power Supply Auto Starting of pump 14 Captive Water Storage for fire fighting. 15 Underground tank capacity Provided MR Required Provided MR Provision of Lifts. Pressurization of Lift Shaft					
Power Supply Auto Starting of pump 14 Captive Water Storage for fire fighting. 15 Underground tank capacity Access to tank Overhead Tank capacity 16 Provision of Lifts. Pressurization of Lift Shaft Provided Pro			2 2		
Auto Starting of pump Required Provided MR Lequired Provided MR Lequired Provided MR Lequired Provided MR Outhor Storage for fire fighting. Lequired Provided MR Required Provided MR Required Provided MR Lequired Provided MR Required Provided MR Exit Signage. Required Provided MR Provision of Lifts. Pressurization of Lift Shaft		• •		Provided	MR
Auto Starting of pump Captive Water Storage for fire fighting.			40 MTr.		MR
14 Captive Water Storage for fire fighting. • Underground tank capacity > Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity 15 Exit Signage. 16 Provision of Lifts. • Pressurization of Lift Shaft		Auto Starting of pump	Required		
Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity S,000 W 10,000 W MR Exit Signage. Required Provided MR Forded MR Required Provided MR Provision of Lifts.			lepuised	()	
Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Required Provided MR Required Provided MR 10,000 Uts. MR Required Provided MR	14	Captive Water Storage for fire fighting.			
Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Provision Required Provided MR Required Provided MR Fronded MR Required Provided MR		Underground tank capacity		54 E	
Access to tank Overhead Tank capacity Sooo W Sooo W Sooo W	,		0	0	
Overhead Tank capacity 5,000 W 10,000 Us MR Exit Signage. Repuired Provided MR Pressurization of Lift Shaft		Fire service inlet	Kepuined	Provided	MR
5,000 th 10,000 ths MR 15 Exit Signage. Repaired Provided MR Pressurization of Lift Shaft		> Access to tank	Required	Provided	MR
15 Exit Signage. Repuired Provided MR 16 Provision of Lifts. • Pressurization of Lift Shaft		 Overhead Tank capacity 	V	·-	
16 Provision of Lifts. • Pressurization of Lift Shaft	15	F '4 G'	5,000 lt.	10,000 Us.	MR
Provision of Lifts. Pressurization of Lift Shaft			Repaired	Browded	MR
	10				, ,
Pressurization of Lift lobby		 Pressurization of Lift Shaft 			
Not extend to the second secon		Pressurization of Lift lobby	Ne	of Repuise	2

	Communication In lift Car			
	Fireman's Grounding Switch			
	Lift Signage	Not	Required	
17	Standby power supply		Provided	MR
18	Refuge Area.			
	> Total Area		A Repuise	d
	> Location	N	of refus	
19	Fire Control Room	+		
	Detector System Panel	NR	MP	
	Flow Switch Panel	NR	NP	,
	 PA System Panel 	Required	morrided	MR
	Batter backup	Required	Bronded	MR
	 Building Floor Plans 	NE	NP	
20	Special Fire Protection Systems for Protection of special Risks, if any:	No	_	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers...

Signature of the Inspecting Officer

Name

Signature of the Inspecting Officer

Designation

Name S. K. Dua

Designation ADO (WP)