GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110 001

No. F.6/DFS/MS/School/2013/ 443

Dated 31 01 13

FIRE SAFETY CERTIFICATE

Certified that the — Sarvodaya Bal Vidyalaya, at Ashok Nagar, New Delhi Comprised of - ground floor plus one upper floor, owned/occupied by Director of Education, Govt. of N.C.T of Delhi have complied with the fire prevention and fire safety requirements in accordance with the Director of Education letter No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.02011 and verified by the officer concerned of fire Service on 02.01.2013 in the presence of Sh. Balram Meena, Lab. Asstt. and that the building/premises is fit for occupancy class — group-B (educational) with effect from the date of issue of this certificate for a period of - three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Chief Fire Officer Delhi Fire Service

Copy to:

- The Principal, Sarvodaya Bal Vidyalaya, Ashok Nagar New Delhi
- 2. The Director of Education Govt. of NCT of Delhi Old Secretariat, Delhi.

Note * :- For general fire safety directives please see overleaf

Following fire safety directives must be adhered to -

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The staff should be trained available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.

INSPECTION REPORT

Name & address of the building : <u>Sarre</u>	days Bal Vide	egalys, Althole 1	Jaggy H'D		
	ucational	J U .			
3. Type of Case : New Ca	: New Case/ Renewal				
4. Details of previous NOC : Letter N	To. MIC	Dated: _	34		
5. Fire Safety directives letter No :	MIC	* * * * * * * * * * * * * * * * * * * *			
6. Date of inspection :	02/01/13				
7. Name of the Inspecting Officers:	L. AMEJA				
8. Name and designation of officers		, i			
	Balran Meon	a lab Assell.			
	- 1952-				
	MIL				
Minimum Standards on fire	NBC	Provided at site	Remarks		
o. prevention and fire safety U/R 33	Requirement		MR/NMR		
Access to building		1			
Road width	R	18 mts	MR		
Gate width	R	3.70 m/ss	me		
Width of internal road					
Number, Width, Type & Arrangemen	it of Exits				
a. Number of staircases	R	2 Mus	MR		
• Upper Floors	- 4	ч .	_ N -		
• Basements	HIC				
b. Width of staircases	R	153 cms each	me		
• Upper Floors	- 4	9	-u -i		
Basements	MIC				
c. Protection of exits	MR				
Fire check door					
Pressurization					
e. No. of continuous staircases to terra	ice R	P	me		
g. Width of Corridor	R	210 cms	- ¥ -		
h. Door Size	R	100 Cms	<u>u</u> –		

	Compartmentation.			
	Fire check door	MR		× ×
	 Sealing of electrical shafts 			
	• Fire Rating of shaft door			
	• Water Curtain			
	Fire Dampers			
1	Smoke Management System.	NR		
	Basements	30 a/c per hour		
	• Upper floors	12 a/c per hour		
5	Fire Extinguishers		1, 1	-
	• Total numbers	R	P.	MR
	• Types		- 25-	- 4-
	• IS marking	ISI marked	Co2 + Dep	<u> </u>
6	First-Aid Hose Reels.		70	-4-
	Total numbers on each floor	NR		
	Length of hose reel hose	30 m		
	Nozzle diameter	5 mm		
7	Automatic fire detection and alarming	2 13 V		
	Type of detectors	system. MR		
	Location of Main Panel			
, a	Location of Repeater Panel			
	Alternate source of power		1	
	Hooters' Location			
8	MOEFA	410		
9	Public Address System.	-MR-		
10	Automatic Sprinkler System.	1-MR-		
	Basement	MR		

	Upper FloorSprinkler above false ceiling		
1	Internal Hydrants	MR	
	Size of riser/down-comer	MK	
	Number of hydrants per floorHose Box		
2			
	Yard Hydrants.	MR	
	Total number of hydrantsHose Box		
3	Pumping Arrangements.		
	Ground Level	MR	
	Discharge of main Pump		
	Head of Main pump		
	> Number of main pumps		
	> Jockey Pump out put		
	> Jockey pump head		
	Standby Pump out putStandby Pump Head		
	> Auto Starting/ Manual		
	stopping,		
	> Pump House Access		
	 Terrace level Discharge of pump 		
	> Head of the pump		
	> Power Supply		
1.4	➤ Auto Starting of pump		
14	Captive Water Storage for fire fightin	g. HR	
	Underground tank capacityDraw-off connection		

1	>	Fire service inlet		
	>			
		Overhead Tank capacity		
15		ignage.	MR	
16	Provis	sion of Lifts.	TIR	
	•	Pressurization of Lift Shaft		
		Pressurization of Lift lobby		
	•	Communication In lift Car		
i in '				
1		Fireman's Grounding Switch		
		Lift Signage	7	
17	Stand			
18	Dofue	by power supply	HR	
		e Area.	MR	
	Α .	Total Area		
	A	Location		
19	Fire (ontrol Room	MP	
		Detector System Panel		
		Flow Switch Panel		
		PA System Panel		
		Batter backup		
-	•	Building Floor Plans		
20	Specia	al Fire Protection Systems for		
	Protec	tion of special Risks, if any:	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

3

Signature of the Inspecting Officer

Name H. L. AN ETA

Designation Dir Hicer

Signature of the Inspecting Officer

Name

Designation