GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110 001

No. F.6/DFS/MS/School/2013/ 42

Dated 31 01 13

FIRE SAFETY CERTIFICATE

Certified that the — Sarvodaya Bal Vidyalaya, at Subash Nagar, New Delhi Comprised of - ground floor, owned/occupied by Director of Education, Govt. of N.C.T of Delhi have complied with the fire prevention and fire safety requirements in accordance with the Director of Education letter No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.02011 and verified by the officer concerned of fire Service on 02.01.2013 in the presence of Sh. Jugraj Lal, Principal and that the building/premises is fit for occupancy class — group-B (educational) with effect from the date of issue of this certificate for a period of three years in accordance with rule*36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules,2010 printed overleaf.

Chief Fire Officer Delhi Fire Service

Copy to:

- The Principal, Sarvodaya Bal Vidyalaya, Subash Nagar New Delhi
- 2. The Director of Education Govt. of NCT of Delhi Old Secretariat, Delhi.

Note * :- For general fire safety directives please see overleaf

Following fire safety directives must be adhered to -

- 1. All the fire safety arrangements provided therein shall be maintained in good working
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The staff should be trained available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.

	INSPECT	ION REPORT		
4. 5. 6. 7. 8.	Name & address of the building: Type of Occupancy Ege Type of Case Details of previous NOC Fire Safety directives letter No Date of inspection Name of the Inspecting Officers: Name and designation of officers from the building side Year of Construction	claya Bal Vid Uccohon al sel Renewal	Dated	
S.	The brieff Inc.	MIL		
No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks
1	Access to building			MR/NMR
	Road width	R	9 mtrs	
	• Gate width	R	4 somb	mR
	Width of internal road		9 30 MTS	-4-
2	Number, Width, Type & Arrangement o	CTE-14		
	a. Number of staircases			
	• Upper Floor's	MR		
	• Basements			
	b. Width of staircases			
	Upper Floors	MR		
	• Basements			
9 4 7 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	c. Protection of exits			
	• Fire check door	MR		
	Pressurization			
	e. No. of continuous staircases to terrace			
	g. Width of Corridor			
	h. Door Size			
		R	115×20smb	MR

3	Compartmentation.				
	Fire check door	MR			
	• Sealing of electrical shafts				
	• Fire Rating of shaft door				
	• Water Curtain				
	• Fire Dampers				
4	Smoke Management System.	410			
	Basements	11R			
e de Bolton	• Upper floors	30 a/c per hour			
٠,		12 a/c per hour			
5	Fire Extinguishers				
	• Total numbers	R	p p	MR	
	• Types		24 NVS	- u -	
	• IS marking	TOT	Co2+DCP	- u -	
5	First-Aid Hose Reels.	ISI marked	10	- 11	
	Total numbers on each floor	NR NR			
	• Length of hose reel hose				
	• Nozzle diameter	30 m			
7		5 mm			
	Automatic fire detection and alarming system.				
	Type of detectors				
	Location of Main Panel				
	Location of Repeater Panel				
۲.	Alternate source of power				
	Hooters' Location				
}	MOEFA				
)	Public Address System.	MR			
0	Automatic Sprinkler System.	I MR			
	Basement	MR			
	L. H. C.	MIC			

	Upper FloorSprinkler above false ceiling	
1	Internal Hydrants	NR -
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	
2	Yard Hydrants.	MR = -
	Total number of hydrantsHose Box	
13	Pumping Arrangements.	HR -
	 Ground Level Discharge of main Pump → Head of Main pump → Number of main pumps → Jockey Pump out put → Jockey pump head → Standby Pump out put → Standby Pump Head → Auto Starting/ Manual stopping 	
1	 Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighti Underground tank capacity Draw-off connection 	ing.

	> Fire service inlet	
	A MO BOLVICO IIIICI	
	Trocop to tails	
	Overhead Tank capacity	
5	Exit Signage.	HIR -
16	Provision of Lifts.	NR
	Pressurization of Lift Shaft	
	Pressurization of Lift lobby	
	Communication In lift Car	
	• Fireman's Grounding Switch	
	• Lift Signage	
17	Standby power supply	MR
18	Refuge Area.	NR
	> Total Area > Location	
19	Fire Control Room	NR
	Detector System Panel	
	• Fldw Switch Panel	
	PAl System Panel	
	Batter backup	
	Building Floor Plans	
20	Special Fire Protection Systems for Protection of special Risks, if any:	NR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ ssue shortcomings as noted at serial numbers.

\$

Signature of the Inspecting Officer

Name HIL-AMEJA

Designation Dir Africer

Signature of the Inspecting Officer

Name

Designation