## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/MS/HOSpital/2013/568

Dated: 12/02/13

## FIRE SAFETY CERTIFICATE

Issued on 12/02/13 at New Delhi by

Chief Fire Officer Delhi Fire Service

To,

The Medical Superintendent GTB Hospital, Shahdara, Delhi-95.

Copy to:-

- a) The Executive Engineer (E), B-243, PWD, GTB Hospital Complex, Shahdara, Delhi-95.
- b) The Executive Engineer (B), EDMC Building Department Shahdara, Delhi.

## **CONDITIONS:**

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. Internal access road of 6 mtrs wide all around building blocks must be kept clear all the time for free movement of fire engines in case of fire.

6. Basement shall not used for any type of storage & occupancy.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

8. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction/ unauthorized use of land if any & also not for other buildings of GTB hospital complex.

Do East

## **INSPECTION REPORT**

1. Name & address of the building

: 500 bedded New Ward Block at G.T.B. Hospital, Shahdara, Delhi.

2.Building Comprised of

:B+Ground plus seven upper floos

2. Type of Occupancy

: Institutional (Hospital Building)

3. Type of Case

: New Case

4. Details of Previous NOC

: Nil

5. Fire Safety directives No

: F6/DFS/MS/BP/Hospital/2004/1275 dtd. 16.06.2004

6. Date of Inspection

: 16.01.2013 & 24.01.13

7. Name of the Inspecting Officer

: DO Virendra Singh & ADO Gurmukh Singh

8. Name of the designation of Officer: Sh. T.Paul(AE-E), Sh.Tejbir Singh (AE-C) & Sh.Deepak Kumar

From the building side

with other supported staff.

9. Year of Construction

: 2009-12

10. Applicant's letter No.

:54(NWB-III)/EE(E)/B-243 (N)/893 dated 20.12.12

		D-III)/ EE(E)/ B-243	(N)/893 dated 20	1.12.12
S.NO.	The prevention	As per	Provided at Site	Remarks
	and fire safety U/R33	directives		
10		requirement		
1	Access to building			-
	<ul> <li>Road width</li> </ul>	12 Mtrs.	26 Mtrs.	MR
	• Gate width	4.5 Mtrs.	6 Mtrs.	MR
	Width of internal road	6 Mtrs.	6 Mtrs.	MR
2	Number, Width, Type and Arrangement o	f Exits		
	a. Number of Staircases			
	Upper Floor	08 Nos.	O8 Nos.+09 Lift	MR
	Basement	04 nos.	04 Nos.	MR
:a	b. Width of Staircases			
	Upper Floor	2.0 Mtrs.	2.0 Mtrs.	MR
	<ul> <li>Basement</li> </ul>	2.0 Mtrs.	2.0 Mtrs.	MR
	c. Protection of exits			
	Fire check door	Required	Provided	MR
	<ul> <li>Pressurization</li> </ul>	Required	Provided	MR
	e. No. of continuous staircases to terrace	3 nos.	4 nos.	MR
	g. Width of Corridor	2 .0 M	2.75 M	MR
	h. Door Size	2.0 M	Provided	MR
3	Compartmentation.	Required	Provided	
	Fire check door	Required	Provided	MR
	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	Sealed	MR
	<ul> <li>Fire rating of shaft door</li> </ul>	1 hrs.	1 hrs.	MR
	<ul> <li>Water curtain</li> </ul>	Not Required	Not Provided	MR
	<ul> <li>Fire Dampers</li> </ul>	Not Required	Not Provided	MR
	Smoke Management System.	•		
	Basement	N/A		
	<ul> <li>Upper floor</li> </ul>	12 a/c per hour	Provided	MR

500 bedded New Ward Block at G.T.B. Hospital, Shahdara, Delhi

5.	Fire Extinguisher	100 Nos.	324 Nos.	MR
	Total Humbers	Water	Provided	MR
	l • lypes	Type,ABC &Co2	11001000	Swells W. S.
		ISI marked	Provided	MR
	IS marking  First-aid-Hose Reels.	151 THAT NOW	3 5 7 5 1 A GARAGE	
6		04 nos.	Provided	MR
	Total numbers of each floor     Length of hose reel hose	30 m	Provided	MR
	Length of nose reel nose     Nozzle diameter	20 mm	Provided	MR
<del></del>	Automatic fire detection and alarming system			
7	- Cl. 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	Heat & smoke	Provided	MR
		Ground floor	Provided	MR
	Location of main panel     Location of repeater panel	1,3,5 &7 <sup>th</sup> floor	Provided	MR
	Location of repeater paner	near lift lobby	466 000 000	
	Alternate source of power	Battery & DG	Provided	MR
	Alternate source of power	Set		
	Hooters's location	Near Staircase	Provided	MR
8	MOEFA	Required	Provided	MR
9	Public address System.	Required	Provided	MR
10	Automatic Sprinkler System.	Required	Provided	MR
	basement	N/A		
	, saserment	~		
	upper floor	Required	Provided	MR
	sprinkler above false ceiling	Required	Provided	MR
11	Internal Hydrants			
	size of riser/down-comer	150 mm	Provided	MR
	Number of hydrants per floor	04 Nos.	Provided	MR
	Hose Box	04 Nos	Provided	MR
12	Yard Hydrants.		6	
	Total number of hydrants	06 Nos.	provided	MR
	Hose Box	06 Nos.	provided	MR
13	Pumping Arrangements.	п		
	Ground Level	2850 LPM	2850 LPM	MR
	Discharge of main Pump	2850 LPM	Provided	MR
	➤ Head of Main Pump	70 Mtrs.	Provided	MR
	Number of main pumps	02 Nos.	Provided	MR
	> Jockey pump out put	180 LPM	Two 180 LPM	MR
	> Jockey pump head	70 Mtrs.	Provided	MR
	> Standby pump out put	2850 LPM	2850 LPM	MR
	Standby pump Head	70 Mtrs	Provided	MR
	Auto Starting / Manual stopping	Auto	Provided	MR
	Pump House Access	Required	Provided	MR
	Terrace Level	8		
	Discharge of pump	900 lpm	Provided	MR
	➤ Head of the Pump	35 mtrs,	35 Mtrs.	MR

500 bedded New Ward Block at G.T.B. Hospital, Shahdara, Delhi

39)10

500 Bedded Hosp. GTB. Blove.

	> Power supply	Required	Provided	MR
	> Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for Fire Fighting.			
	Underground tank capacity	2,00,000 Ltrs.	3,50,000 Ltrs.	MR
	Draw-off connection	Required	Provided	MR
	Fire service inlet	Required	Provided	MR
	Access to tank	Required	Provided	MR
	Overhead Tank capacity	50,000 Ltrs.	50,000 Ltrs.	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	Pressurization of Lift Shaft	Required	Provided	MR
	Pressurization of Lift lobby	Not Required	Not Provided	MR
	Communication in lift car	Required	Provided	MR
	Firemen's grounding switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	750 KVA	MR
18	Refuge Area.	Required	Provided	MR
	Total area	248 Sq Mtrs.	Provided	MR
	• Location	5 <sup>th</sup> floor	Provided	MR
19	Fire Control Room			
	Detector system panel	Required	Provided	MR
	Flow switch panel	Required	Provided	MR
	PA system panel	Required	Provided	MR
	Battery backup	Required	Provided	MR
	Building Floor Plans	Required	Provided	MR
20	Special Fire Protection systems for protection of special Risks, if any:	Required for HT/LT panels	Provided	MR
	processor or opposite mana, in any	,		

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name:-Gurmukh Singh Designation:-ADO (LN) Signature of the inspecting Officer

Name!-Virendra Singh Designation:-DO (East)