GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/OFS/MS/CH/2013/619

Dated: /3 /02 /2013

FIRE SAFETY CERTIFICATE

Certified that the Hotel Aman Palace located at A-40, Vishal Enclave, New Delhi comprised of Basement, Ground + three upper floors occupied by Hotel Aman Palace was issued NOC vide this office letter no. F.6/DFS/MS/GH/10/1515 Dated 23/2/2010. The premises was re-inspected by the officer concerned of this department on 29/12/2012 and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition and that the building/premises is fit for occupancy Class A, Residential with effect from 13 102 12013 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 subject to conditions printed below.

Issued on 13/02/13 at New Delhi.

CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to:

1. The Addl. Commissioner of Police (Lic.), 1st floor, P.S. Defence Colony

2. The Proprietor, Hotel Aman Palace, A-40, Vishal Enclave, New Delhi.

Following fire safety directives must be adhered to

1. All the Means of escape shall be kept free of obstruction all the time.

- 2. All the employees shall be acquainted with the use and maintenance of fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation with regards to construction, electrical installation etc. may be got verified from the concerned authorities.
- 5. Basement shall be used as per NBC.
- 6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/OFS/MS/CH/2013/619

Dated: /3 /02 /2013

FIRE SAFETY CERTIFICATE

Certified that the <u>Hotel Aman Palace</u> located at <u>A-40</u>, <u>Vishal Enclave</u>, <u>New Delhi</u> comprised of <u>Basement</u>, <u>Ground + three upper floors</u> occupied by <u>Hotel Aman Palace</u> was issued NOC vide this office letter no. F.6/DFS/MS/GH/10/1515 Dated 23/2/2010. The premises was re-inspected by the officer concerned of this department on 29/12/2012 and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition and that the building/premises is fit for occupancy <u>Class A</u>, <u>Residential</u> with effect from 13 102 12013 for a period of <u>three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 subject to conditions printed below.</u>

Issued on 13/02/13 at New Delhi.

CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to:

1. The Addl. Commissioner of Police (Lic.), 1st floor, P.S. Defence Colony

2. The Proprietor, Hotel Aman Palace, A-40, Vishal Enclave, New Delhi.

Following fire safety directives must be adhered to

- 1. All the Means of escape shall be kept free of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation with regards to construction, electrical installation etc. may be got verified from the concerned authorities.
- 5. Basement shall be used as per NBC.
- 6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

Premise- B+ G+ Three upper Hoors.

- Mg -

	INSPECTION REPORT					
Name & address of the building: Aman Palore, A-40 Vishal Enclave						
2.	1. Name & address of the building: Aman Palace, A-40, Vishal Enclove 2. Type of Occupancy: Residential - A (B, G+ Three Hurs)					
3.	NI O ID					
4.	- W C (NG) MIC (NG) MIC (NG) MIC Doted: 28/3/10					
5.						
6.	90/12/2.10					
7.	ADDIANA CA DUA					
8						
	from the building side : Mr. Aman (Director)					
9.	9. Year of Construction : 2003					
10	Applicant's letter No. : 64991	Addl. C.P. L	ic (H) dated 12	(11)12		
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC RAL	Provided at site	Remarks MR/NMR		
1	A Lailding					
1	Access to building		4	016		
	 Road width 	6.0 mtr.	24.0 mitr.	MR		
	Gate width	6.0 mtr. Reprired	on main Road	MR		
	Width of internal road	NIR				
2	2 Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	0,2	02	MR		
	Upper Floors	02	Browded	Me		
	Basements	02	Provided	MR		
	b. Width of staircases					
	Upper Floors	Old Case	1.20 mts.	Old Case		
	Basements	old Case	1.20 mits.	Old case		
	c. Protection of exits					
	Fire check door	Reprired	Provided	MR		
	Pressurization	NR	NA	_		
	e. No. of continuous staircases to terrace	01	Provided	on R		
	g. Width of Corridor	Old case	1.40 mtr.	Old case		
	h. Door Size	1.0 mitr.	Provided	MR		

3	Compartmentation.				
	Fire check door	Repuired	Brided	MR	
	Sealing of electrical shafts	NR	NP		
	Fire Rating of shaft door	NR	NP		
	Water Curtain			-	
	Fire Dampers	NR	NP	-	
4	G 1 24	NR	NP	*	
4	Smoke Management System.				
	Basements	30 a/c per hour	Fronded (Extraus)	MR	
	Upper floors	12 a/c per hour	NR (open)	MR	
5	Fire Extinguishers				
	• Total numbers	12 4516 & ABC-SK ISI marked	14	MR	
		ISI marked		MR	
	IS marking		Provided	MR	
6	First-Aid Hose Reels.				
	Total numbers on each floor	01	mided	MR	
	Length of hose reel hose	30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	NR	NP		
	Location of Main Panel	on GIFloor	Provided Not Reprised	MR	
	Location of Repeater Panel		Refired		
	Alternate source of power		1/01		
	Hooters' Location		C 50	•	
8	MOEFA	Required	Provided	mR	
9	Public Address System.	Repuired	Borided	MR	
10	Automatic Sprinkler System.	repure	1, 900,		
	Basement	Required	Provided	MR	
	Upper Floor	NR	NP	1117	
	 Sprinkler above false ceiling 	NR			
11	Internal Hydrants	INK	NP		
	Size of riser/down-comer	1201 00000	2-21-2	000	
	olzo of fisch down-comer	100 mm	Bronded	MR	

•	Number of hydrants per floor	01	Provided	MR	
	• Hose Box	01	Provided	MR	
12	Yard Hydrants.				
	Total number of hydrants		louixed -		
	Hose Box	No	Required -		
13	Pumping Arrangements.				
	Ground Level			/	
	Discharge of main Pump				
	Head of Main pump				
	Number of main pumps				
	Jockey Pump out put				
	Jockey pump head		O onised		
	Standby Pump out put		Not Required		
	Standby Pump Head		No		
	Auto Starting/ Manual stopping				
	Pump House Access				
	Terrace levelDischarge of pump		-	-	
	Head of the pump	450 LPM)	monded	MR	
	➤ Power Supply	40 MAR. Ca	of Browded	MR	
	➤ Auto Starting of pump	Required	Provided	MR	
		Repuired	Provided	MR	
14	Captive Water Storage for fire fighting.				
	Underground tank capacity		123		
	> Draw-off connection		red		
	Fire service inlet		Not Required		
	Access to tank		(40	1.0	
	Overhead Tank capacity				
	S (Cinical Faint Supers)	10,000 lts.	Provided	me	
15	Exit Signage.	Required	Provided	me	
16	Provision of Lifts.				
	Pressurization of Lift Shaft				
	Pressurization of Lift lobby		- Not Repuise	9	

	Communication In lift Car	Repuircel	Provided	mR
	Fireman's Grounding Switch	Required	Pronded	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required Required Required	Provided	MR
18	Refuge Area.			1
	> Total Area		Not Repuise	d
	Location			
19	Fire Control Room			
	Detector System Panel	NR	M	-
	 Flow Switch Panel 	Nok	NP	_
	PA System Panel	Required	Provided	mR
	Batter backup	Repuirced	Provided	MR
	Building Floor Plans	NOR	NP	_
20	Special Fire Protection Systems for Protection of special Risks, if any:	No		_

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers......

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name S.R. Dua

Name

Designation ADO (WP)

Designation