## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2013/ 587

Dated: 12/02/13

## FIRE SAFETY CERTIFICATE

Issued on 12/62/13 at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Manager, M/s Poonam International Guest House, 3129,3169,3170,3171 Gali Sangatrashan, Pahar Ganj, New Delhi-55

## Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

]	Name & address of the building:	ram Internation	al Guest House, 31	29,3169,3170,317	
	2. Type of Occupancy : Lodgir	: Lodging House / Eating House / Club Gali Sangal Rasan, palarga			
	3. Type of Case : Renew	val / New case	216WJ	Selm	
4	Details of previous NOC : Letter	No	Date	d:	
5	5. Fire Safety directives letter No :				
	Date of inspection :	2/2/2013			
7	7. Name of the Inspecting Officers: Do	Dharamvir Sing	sh yadar, ADO M.K	. Chattopadhyg	
	3. Name and designation of officers	V		( 0 0	
	from the building side : _ St	hri Suresh	Vij, Owner		
		ctobes 2004			
1	0. Applicant's letter No. : 6	2811-15/Addl	1.c.p./Lic(H) day	led 26/10/12	
S.	Minimum Standards on fire	NBC	Provided at site	Remarks	
No.	prevention and fire safety U/R 33	Requirement		MR/NMR	
1	Access to building				
	Road width	spl area	5.60 mt	MR	
	• Gate width	~	Directly a ceepsible from the road	MR	
	Width of internal road	MA	m m	non	
2	Number, Width, Type & Arrangement	of Exits			
	a. Number of staircases	_	←	-	
	Upper Floors	02	02	MR	
	• Basements	MA	m n	MA	
	b. Width of staircases			_	
	<ul> <li>Upper Floors</li> </ul>	0.80 mt	1.55mt, 1.42mm	MR	
	• Basements	Mn	MA	72	
	c. Protection of exits	N/A	N/A		
	<ul> <li>Fire check door</li> </ul>	N/A	N/A		
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	444 GM AM	
	e. No. of continuous staircases to terrace	02	02	70) 12	
	g. Width of Corridor	N/A	N/A		
	h. Door Size	N/A	N/A		
		N/A	N/A		
3	Compartmentation.				
	Fire check door	N/A	N/A		



	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A		
	• Fire Rating of shaft door	N/A	N/A		
	• Water Curtain	N/A	N/A		
	Fire Dampers	N/A	N/A		
4	Smoke Management System.				
	<ul><li>Basements</li><li>Upper floors</li></ul>	30 a/c per hour 12 a/c per hour	ma	70	
	apper moons	r	MA	Ma	
5	Fire Extinguishers				
	Total numbers	10	provida	ME	
	<ul><li>Types</li></ul>	ABC, Wales Co2	provided	MR	
	<ul> <li>IS marking</li> </ul>	ISI marked	provided	MR	
5	First-Aid Hose Reels.		*		
	<ul> <li>Total numbers on each floor</li> </ul>	01	prinded	MR	
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	provided	MR	
	Nozzle diameter	5 mm	pourded	MP	
7	Automatic fire detection and alarming system.				
	• Type of detectors	N/A	N/A		
	Location of Main Panel	N/A	N/A	*	
	• Location of Repeater Panel	N/A	N/A		
	Alternate source of power	N/A	N/A		
	Hooters' Location	N/A	N/A	AND NOT THE REP HAT MAD NOT HER MAD NOT	
3	MOEFA	Required	provida	MR	
)	Public Address System.	Required	provides	MR	
	Automatic Sprinkler System.				
10	Automatic Sprinkler System.				
10	Basement	MA	MA	MA	
10	<ul><li>Basement</li><li>Upper Floor</li></ul>	N/A	M/A	M/4	
10	Basement			M 15	
	<ul><li>Basement</li><li>Upper Floor</li></ul>	N/A	N/A	M/4	
10	<ul><li>Basement</li><li>Upper Floor</li><li>Sprinkler above false ceiling</li></ul>	N/A	N/A		
	<ul> <li>Basement</li> <li>Upper Floor</li> <li>Sprinkler above false ceiling</li> </ul> Internal Hydrants	N/A N/A	N/A N/A	MA 	

	Hose Box	N/A	N/A	
	,	IN/M	19/74	
12	Yard Hydrants.			
	Total number of hydrants	N/A	N/A	
	Hose Box	N/A	N/A	
13	Pumping Arrangements.			
	Ground Level	N/A	N/A	
	Discharge of main Pump	N/A	N/A	
	Head of Main pump	N/A	N/A	
	Number of main pumps	N/A	N/A	
	Jockey Pump out put	N/A	N/A	
V	> Jockey pump head	N/A	N/A	
	Standby Pump out put	N/A	N/A	
	<ul><li>Standby Pump Head</li><li>Auto Starting/ Manual</li></ul>	N/A	N/A	
	stopping stopping	N/A	N/A	
	<ul><li>Pump House Access</li></ul>	N/A	N/A	
	Terrace level	N/A	N/A	
	Discharge of pump	450 LPM	provided	MR
	➤ Head of the pump	40 mt	provides	MR
	Power Supply	Requisio	provida	MR
	Auto Starting of pump	Required	provide	MR
14	Captive Water Storage for fire fighting	g.		5
	Underground tank capacity	N/A	N/A	
	Draw-off connection	N/A	N/A	So-
	> Fire service inlet	N/A	N/A	
	Access to tank	N/A	N/A	<u> </u>
	Overhead Tank capacity	10,000 (13.	Provided	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	Pressurization of Lift Shaft	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	
	Communication In lift Car	N/A	N/A	

	<ul> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> </ul>	N/A N/A	N/A N/A		
17	Standby power supply	Require	30 KNA provides	MR	
18	Refuge Area.				
	> Total Area	N/A	N/A		
	Location	N/A	N/A		
19	Fire Control Room				
	Detector System Panel	N/A	N/A		
	Flow Switch Panel	N/A	N/A		
	PA System Panel	N/A	N/A		
	Batter backup	N/A	N/A		
	Building Floor Plans	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC lyter fire extension has provided was Elect panel	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant / renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

(M.K.CHATTOPADHYAY)

ADO(CC)

(DHARAMVIR SINGH YADAV)

DO(CD)