GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2013/690

Dated: 18/02/13

FIRE SAFETY CERTIFICATE

Certified that Rehmani Guest House located at 903, Chatta Sheikh Mangloo, Jama Masjid, Delhi comprised of ground floor (Reception + 03 guest rooms + Dormitory for 27 beds), first floor (owner's residence) & terrace (mamty + water tanks) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2010/642 dated 05-03-2010. The premises was re-inspected by the officer concerned of this department on 07-02-2013 in the presence of Mr. M.N. Khan, manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 18/02/13 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules, 2010.

Issued on 18/02/13 at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi w.r.t. your letter No.4124/Addl.C.P./Lic(H) dated 24-01-13
- 2. The Manager, Rehmani Guest House 903, Chatta Sheikh Mangloo, Jama Masjid, Delhi.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1	Name & address of the building: Kehman Gust House, 903, Chatta Sheeth Ma Type of Occupancy: Lodging House Jama Marid, Della				
2	2. Type of Occupancy : Lodg	ging House	Jama Mary	d, Dellu	
3	. Iteme was a reason				
4	Details of previous NOC : Letter No. Fold B/14s/44/2010/642 Dated: 05/03/2010				
5	. Fire Safety directives letter No :				
6					
7	7. Name of the Inspecting Officers:				
8	8. Name and designation of officers				
	from the building side : M. N. Kham, Manager				
9	. Year of Construction :	1930			
10	0. Applicant's letter No. :	4124 / Boldl. C.	Pluc (H) delea	24/1/2013	
S.	Minimum Standards on fire	NBC	Provided at site	Remarks	
No.	prevention and fire safety U/R 33	Requirement		MR/NMR	
1	Access to building				
	Road width	Spl. area	4.60mt	me	
	• Gate width	+	Derectly accombine	MR	
	 Width of internal road 	MA	MA	n	
2	Number, Width, Type & Arrangemen		3		
	a. Number of staircases	_		400	
	• Upper Floors	Guest house en	7 1	72	
	 Basements 	MA	MA	MA	
	b. Width of staircases			-	
	• Upper Floors	MA	79 4	70	
	 Basements 	MA	w) n	N m	
	c. Protection of exits	N/A	N/A		
	• Fire check door	N/A	N/A		
	 Pressurization 	N/A	N/A		
	e. No. of continuous staircases to terrace	,	dimension	Character	
	g. Width of Corridor	N/A	N/A		
	h. Door Size	N/A	N/A		
		N/A	N/A		
3	Compartmentation.				

	3				
	Fire check door	N/A	N/A		
	Sealing of electrical shafts	N/A	N/A		
7	Fire Rating of shaft door	N/A	N/A		
	Water Curtain	N/A	N/A		
	Fire Dampers	N/A	N/A		
4	Smoke Management System.				
	BasementsUpper floors	30 a/c per hour 12 a/c per hour	M 4	MA	
	opper moors	12 are per mour	N/A	N/A	
5	Fire Extinguishers			2) 2)	
	Total numbers	04	Provided	MR	
	• Types	watercoz, coz	Provided	MR	
	IS marking	ISI marked	Provided	MR	
6	First-Aid Hose Reels.		•	α = -	
	Total numbers on each floor	Olat GF	Provided	MR	
	• Length of hose reel hose	30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	N/A	N/A		
	Location of Main Panel	N/A	N/A		
	Location of Repeater Panel	N/A	N/A		
	Alternate source of power	N/A	N/A		
	Hooters' Location	N/A	N/A		
8	MOEFA	N/A	7 1	H/A	
9	Public Address System.	N/A	N/A	N/r	
10	Automatic Sprinkler System.				
	• Basement	N/A	N/A		
	Upper Floor Secial leads of 1 and 11.	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A		
11	Internal Hydrants				
	Size of riser/down-comer	N/A	N/A		
	Number of hydrants per floor	N/A	N/A		

		- II D			
1	*	Hose Box	N/A	N/A	
	12	Yard Hydrants.			
		 Total number of hydrants 	N/A	N/A	
	1.2	Hose Box	N/A	N/A	
	3 Pumping Arrangements.				
		• Ground Level	N/A	N/A	
		Discharge of main Pump	N/A	N/A	
		Head of Main pump	N/A	N/A	
22		Number of main pumps	N/A	N/A	
		Jockey Pump out put	N/A	N/A	
		Jockey pump head	N/A	N/A	
		Standby Pump out put	N/A	N/A	
		Standby Pump Head	N/A	N/A	
		Auto Starting/ Manual	N/A		
		stopping	11 200 000	N/A	
		Pump House Access	N/A	N/A	
		• Terrace level	N/A	N/A	
		Discharge of pump	225 Lpm	provided	MR
		Head of the pump	30 m	provided	Me
		Power Supply	-	Provided	MR
1.4		Auto Starting of pump		Starting Switch provided at GF	Me
14	C	aptive Water Storage for fire fighting			
		 Underground tank capacity 	N/A	N/A	
		Draw-off connection	N/A	N/A	
		Fire service inlet	N/A	N/A	
		Access to tank Overhead Tonk and the	N/A	N/A	
		Overhead Tank capacity	2500 lb	Provided	MR
15	1	it Signage.	Required	Provided	MR
16	Pr	ovision of Lifts.			IVIK
	•	Pressurization of Lift Shaft	N/A	N/A	
	•	Pressurization of Lift lobby	N/A	N/A	
	•	Communication In lift Car	N/A	N/A	
				11/71	



_			The state of the s	
6	Fireman's Grounding Switch	N/A	N/A	
	Lift Signage	N/A	N/A	
17	Standby power supply	· ·	5 KVA	MR
18	Refuge Area.			
	> Total Area	N/A	N/A	
	> Location	N/A	N/A	
19	Fire Control Room			
20	Detector System Panel	N/A	N/A	
	Flow Switch Panel	N/A	N/A	
	PA System Panel	N/A	N/A	
	Batter backup	N/A	N/A	
	Building Floor Plans	N/A	N/A	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	O1 CO, Tylze tire extenguisher provided near sted panel	Me

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant / renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation: - Asstt. Div. Officer (CC)

DO(CD) Forwarded pl.

Do(CD)

13,2-13-