GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No.F.6/DFS/MS/2013/ 8 20

Dated:

26/02/2013

FIRE SAFETY CERTIFICATE

Issued on 26/2/13 at New Delhi.

Copy to:

- (1) The Prinicpal Sant Nirankari Public School Nirankari Colony, Delhi-9.
- (2) The Director of Education Old Secretariat, Delhi.

Chief Fire Officer Delhi Fire Service 1. All the means of escape shall be kept free of all type of obstruction all the time time

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non – functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per MGG

000

6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any,

4 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

| | Name & address of the building Sant Nire | ankari Public Se | chool, Nivankari | Colony, Della-9 | |
|-----|--|------------------|------------------|---|--|
| | Type of Occupancy: Educational | | | | |
| 1 | · New Cas | e/ Renewal | | | |
| 4 | 1 Letter No. f- 4 DFC) ms los 1119 9 Dated: 25-4-2008 | | | | |
| 5. | Fire Safety directives letter No: Circular, Director of Edin: 17-1-2005. | | | | |
| (1. | Date of inspection: $26-10-2$ | 012 | | | |
| 7. | Name of the Inspecting Officers: ADC | - SHYAM | LAZ | 4.2 | |
| 8. | Name and designation of officers Smt. | Poonam Sy | al (Principa | | |
| | | | 10 (two room a | | |
| | The sales of the s | (G+2) 20 | 3 7 - 13 | | |
| 10 | . Applicant's letter No. : N'2 | dated 18 - | la ideal et eite | Remarks | |
| | | chin 17-1-05 | Provided at Site | MIZ/NMIZ | |
| 11. | prevention and fire safety U/R 33 | Requirement | | TARACLI CLARA | |
| | Access to building | (Old | (Case) | 110 | |
| | Road width | Accessible | 9m/ | | |
| | Gate width | -do- | 4.68m | and the second second | |
| | Width of internal road | MIA | MIA | MIX | |
| | Number, Width, Type & Arrangement of Exits | | | | |
| | a. Number of staircases | 2 | 2 | m)R | |
| | Upper Floors | 2 | 2 | miR | |
| | Basements | Nic | Nic | NiL | |
| | b. Width of staircases | | (| | |
| | • Upper Floors | 1.5 m | 1.27m2. 1.30m | ololcase | |
| | Basements | NiL | Nic | MiL | |
| | c. Protection of exits | 14,16 | | 74, | |
| | • Fire check door | N/D | N/P | N/A | |
| | Pressurization | N/R | N/P | N/A | |
| | e. No. of continuous staircases to terrace | N/R | 7 | MIR | |
| | | R | 2.32 M | MR | |
| | g. Width of Corridor | 1 m | 1:15 m | MIR | |
| | h. Door Size | 1 / / · | | A second | |

| * | | | | | |
|----|--|-----------------|-------------------|-----------|--|
| 3 | Compartmentation. | | | | |
| | Fire check door | N/R | N/P | N/A | |
| | Sealing of electrical shafts | N/R | N/P | N/A | |
| | Fire Rating of shaft door | N/R | N/P | N/A | |
| | Water Curtain | N/R | N/P | N/A | |
| | • Fire Dampers | N/R | N/P | N/A | |
| 10 | Smoke Management System. | | | | |
| | Basements | 30 a/c per hour | N/R | N/A | |
| | Upper floors | 12 a/c per hour | | | |
| | | | N/R | N/A | |
| | Fire Extinguishers | | | | |
| | Total numbers | 09 | 09 | MIR | |
| | • Types | ABC Dr Cortas | B) ABC | MR | |
| | IS marking | ISI marked | yes | MIR | |
| 0 | First-Aid Hose Reels. | | | | |
| | Total numbers on each floor | Two : W | Two M | m)RM | |
| | Length of hose reel hose | 30 m | Provided Provided | MSR | |
| | Nozzle diameter | 5 mm | . Provided | my posper | |
| | Automatic fire detection and alarming system. | | | | |
| | Type of detectors | N/R | N/P | N/A | |
| | Location of Main Panel | N/R | N/P | N/A | |
| | Location of Repeater Panel | N/R | N/P | N/Λ | |
| | Alternate source of power | N/R | N/P | N/A | |
| | Hooters' Location | | | | |
| | ** | N/R | N/P | N/A | |
| | Trooters froution | 11/11 | | | |
| 8 | MOEFA | N/R | N/P | N/A | |
| 8 | | | | | |
| | MOEFA | N/R | N/P | N/A | |

| / | | | | | |
|----------------|---|-----------------|--|-------|--|
| 2 | Upper Floor | N/R | N/P | N/A | |
| | Sprinkler above false ceiling | N/R | N/P | N/A | |
| in the same of | 1.47.4 | | | | |
| | Size of riser/down-comer | 100 mm | 100 mm | MIR | |
| | Number of hydrants per floorHose Box | one | one | MIR | |
| | a Hose Box | one | one | MIR | |
| 12 | Yard Hydrants. | | | | |
| | Total number of hydrants | N/R | N/P | N/A | |
| | Hose Box | N/R | N/P | N/A | |
| 13 | Pumping Arrangements. | | | | |
| | Ground Level | N/R | N/P | N/A | |
| | Discharge of main Pump | N/R | N/P | N/A | |
| | Head of Main pump | N/R | N/P | N/A | |
| | Number of main pumps | N/R | N/P | N/A | |
| | Jockey Pump out put | N/R | N/P | N/A | |
| | Jockey pump head | N/R | N/P | | |
| | Standby Pump out put | N/R | | N/A | |
| | Standby Pump Head | | N/P | N/A | |
| | Auto Starting/ Manual | N/R | N/P | N/A | |
| | stopping | | | | |
| | Pump House Access | N/R | N/P | N/A | |
| | • Terrace level | | | | |
| | Discharge of pump | 1150 Lts. / min | it boorsded. | 17/18 | |
| | Head of the pump | | | MIR | |
| | Power Supply | N/R | N/P | N/A | |
| | Auto Starting of pump | R | Provided | m)R | |
| 1 | Captive Water Storage for fire fighting | • | | | |
| | Underground tank capacity | N/R | N/P | N/A | |
| | Draw-off connection | N/R | N/P | N/A | |
| | | | The second secon | | |

| Dr. | Fire service inlet | N/R | N/P | N/A |
|-----|--|---------|----------|-------------|
| | Access to tank | N/R | N/P | N/A |
| | Overhead Tank capacity | 500014. | 5000 H | MIR (old ca |
| | Exit Signage. | R | Porvided | mse |
| 16 | Provision of Lifts. | | | |
| | Pressurization of Lift Shaft | N/R | N/P | N/A |
| | Pressurization of Lift lobby | N/R | N/P | N/A |
| | Communication In lift Car | N/R | N/P | N/A |
| | Fireman's Grounding Switch | N/R | N/P | N/A |
| | Lift Signage | N/R | N/P | N/A |
| 17 | Standby power supply | | | |
| 2 | Refuge Area. | | | |
| | > Total Area | N/R | N/P | N/P |
| | > Location | N/R | N/P | N/P |
| 19 | Fire Control Room | | | |
| | Detector System Panel | N/R | N/P | N/A |
| | Flow Switch Panel | N/R | N/P | N/A |
| | PA System Panel | N/R | N/P | N/A |
| | Batter backup | N/R | N/P | N/A |
| | Building Floor Plans | N/R | N/P | N/A |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | NIL | NIL | N/A |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.