GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2013/ 1/

Dated: 05/03/2013

FIRE SAFETY CERTIFICATE

Mandi, Paharganj, New Delhi comprised of basement (storage), ground floor (09 guest rooms + reception), first floor (10 guest rooms), second floor (13 guest rooms), third floor (15 guest rooms), forth floor (15 guest rooms) & terrace floor (tin shed- sealed) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/08/2183 dated 29-07-2008. The premises was reinspected by the officer concerned of this department on 19-02-2013 in presence of Shri Vinod Kumar Babeja, owner of the guest house and found that the party has altered few guest rooms as basement (storage), ground floor (03 guest rooms + reception + 01 office + 01 staff kitchen), first floor (10 guest rooms) second floor (10 guest rooms), third floor (10 guest rooms) & fourth floor (04 guest rooms). The said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 65/03/13 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules, 2010.

Issued on 05/03/13 at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi w.r.t. letter No.1428/Addl.C.P./Lic(H) dated 08-01-2013.

2. The Manager, Natraj Yes Please, 1665 & 1750, Chuna Mandi, Paharganj, New Delhi.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Natraj Yes Please guest house, 1665, 1750, Chuna Mandi,

Paharganj, New Delhi

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No.F.6/DFS/MS/GH/2008/2183 Dated: 29/07/2008

5. Fire Safety directives letter No

: N/A

6. Date of inspection

: 19-02-2013

7. Name of the Inspecting Officers

: M.K.Chattopadhyay, ADO(CC)

8. Name and designation of officers

from the building side

: Shri Vinod Kumar Babeja, Owner

9. Year of Construction

: 1976

: 1427-30/Addl.C.P./Lic(H) dated 08-01-2013

1(J. Applicant 5 letter 1 to.		Provided at site	Remarks	
5.	Minimum Standards on fire	NBC	1 Toylded at site	MR/NMR	
No.	prevention and fire safety U/R 33	Requirement	1	TVIIV I VIVII	
	Access to building				
	Road width	06 mts	12 mts	MR	
	Gate width		Directly accessible	MR	
			from the road		
	Width of internal road	N/A	N/A	N/A	
	Number, Width, Type & Arrangement of Exits				
2			*		
	a. Number of staircases	01	01	MR	
	• Upper Floors		01	MR	
	Basements	01	01	17212	
	b. Width of staircases				
	Upper Floors	0.80 mts	1.27 mts	MR	
	Basements	0.80 mts	1.27 mts	MR	
	c. Protection of exits				
	Fire check door	N/A	N/A	N/A	
	 Pressurization 	N/A	N/A	N/A	
	e. No. of continuous staircases to terrace	01	01	MR	
	g. Width of Corridor	N/A	N/A	N/A	
	h. Door Size	N/A	N/A	N/A	
		N/A	N/A	N/A	

3	Compartmentation.			V-1646		
	Fire check door	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	 Fire Rating of shaft door 	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	• Fire Dampers	N/A	N/A	N/A		
4						
	BasementsUpper floors	30 a/c per hour 12 a/c per hour	Exhaust fan provided	MR		
			N/A	N/A		
5	Fire Extinguishers					
	 Total numbers 	12	Provided	MR		
	• Types	CO ₂ , W.CO ₂	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6		First-Aid Hose Reels.				
	Total numbers on each floor	01 at each floor	Provided	MR		
	• Length of hose reel hose	30 m	Provided	MR		
ALLEY S.	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarmin		T			
	• Type of detectors	N/A	N/A	N/A		
	• Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	Required	Provided	MR		
	 Upper Floor Sprinkler above false ceiling	N/A	N/A	N/A		
	Springer above false centing	N/A	N/A	N/A		
11	Internal Hydrants					
	 Size of riser/down-comer 	N/A	N/A	N/A		

	NII CI I CI	NI/A	NI/A	N/A	
4	Number of hydrants per floor Hage Bay	N/A	N/A		
	Hose Box	N/A	N/A	N/A	
12	Yard Hydrants.				
	Total number of hydrants	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
13	Pumping Arrangements.				
	Ground Level	N/A	N/A	N/A	
	Discharge of main Pump	N/A	N/A	N/A	
	Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put	N/A	N/A	N/A	
	Jockey pump head	N/A	N/A	N/A	
	> Standby Pump out put	N/A	N/A	N/A	
	> Standby Pump Head	N/A	N/A	N/A	
	Auto Starting/ Manual	N/A	N/A	N/A	
	stopping	N/A	N/A	N/A	
	Pump House AccessTerrace level				
	Discharge of pump	450 LPM	Provided	MR	
5	> Head of the pump	40 mts	Provided	MR	
	Power Supply	Required	82.5 KVA	MR	
	➤ Auto Starting of pump	Required	Provided	MR	
14	Captive Water Storage for fire fightin		20		
	Underground tank capacity	N/A	N/A	N/A	
	Draw-off connection	N/A	N/A	N/A	
	> Fire service inlet	N/A	N/A	N/A	
	Access to tank	N/A	N/A	N/A	
	Overhead Tank capacity	5,000 lts	10,000 lts Provided	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	

	Communication In lift Car	Required	Provided	MR J
	Fireman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	82.5 KVA	MR
18	Refuge Area.			9
	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	• Flow Switch Panel	N/A	N/A	N/A
	 PA System Panel 	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	 Building Floor Plans 	N/A	N/A	N/A
20	Special Fire Protection Systems for	Required	One ABC type fire	MR
	Protection of special Risks, if any:		extinguisher provided	
			near elect. panel	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Note:- Previously, this department was issued NOC (**62 guest rooms**) from fire safety and means of escape point of view for basement (storage), ground (09 guest rooms +reception), 1st floor (10 guest rooms), 2nd floor(13 guest rooms), 3rd floor(15 guest rooms), 4th floor (15 guest rooms) & terrace floor (Tin shaded sealed). Now, the details of rooms /occupancy floorwise is basement(storage), (03 guest rooms +reception+ 01 office +01 staff kitchen), 1st floor (10 guest rooms), 2nd floor(10 guest rooms), 3rd floor(10 guest rooms) & 4th floor (04 guest rooms) i.e. total **37 guest rooms** is recommended for renewal.

Signature of the Inspecting Officer
Name M.K.CHATTOPADHYAY
Designation: - Asstt. Div. Officer (HQ)