GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

NO. F6/DFS/MS/Ind./ 2013/ 34

DATED: 06/03/2013

FIRE SAFETY CERTIFICATE

Certified that the M/s P R Apparels Pvt. Ltd. Industrial building at Plot No C-67/1, Okhla Industrial Area, Phase-II New Delhi-110020 comprised of basement, ground, mezzanine floor, first floor owned/occupied by M/s P R Apparels Pvt. Ltd have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of Fire Service on 28.02.2013 in the presence of Mr. S K Jain (G. Manager), of the Industrial and that the building is fit for occupancy class G "Industrial building" with effect from 61/03/13... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rule, 2010, subject to condition as mentioned below.

Issued on .06/03 /2013 at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy to,

- 1. The Executive Engineer (Bldg) HQ, Building Department, SDMC, 8th floor, Civic Centre, Minto Road, New Delhi110002.
- 2. The Director, M/s P R Apparels Pvt. Ltd. at Plot No C-67/1, Okhla Industrial Area, Phase-II, New Delhi-110020

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The basement shall be used strictly as per the provisions of Building Bye laws.
- e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules-2010. The form is available on www.dfs.delhigovt.nic.in

*	INSI	PECTION	REPORT			
1	Name & address of the building	M/S P R Apparels Pvt. Ltd at Plot no.C-67/1, Okhla Industrial Area, Phase II, New Delhi-110020				
2	Type of Occupancy	Industrial "G"				
3		New				
4		No				
	Fire safety directives letter No	F6/DFS/MS/BP/2013/766 Dated 22/02/2013				
5	The salety directives letter 115	28.02.2013				
6	Date of inspection	D.O. (South) D.P. Bhardwaj, ADO (SJ/BCP) S.S. Kaushik				
7	Name of the inspecting Officers :	Mr. S. K. Jain (G. Manager)				
8	Name and designation of officers	Mr. S. K. Ja	ain (G. Manager)		
	from the building side					
9	Year of construction	1985			(Rasem	ent, Ground,
10	Applicant's letter No.	Nil	23.02.2013		Mezzanin	e floor and one per floor)
10	Аррисант з тепет то.		•			Old Building
S. NO.	Minimum Standards on fire prevention and fire safety U/R 33		-1983/NBC quirement	Provid	ded at site	Remarks MR / NMR
1	Access to building					
	1) Road width	Accessible	Э	12 Mtr Prov		MR
	2) Gate width	Required		4.5 Mtr Provided		MR
	3) Width of internal road	N/A		N/A		N/A
2	Number, width Type & arrangement of	exits	V.			
,	a. Number of staircases					MD
	1. Upper floors	Two		Provided		MR MR
	2. basements	Two		Provided		IVIE
	b. Width of staircase				L D Side d	MD
	1. Upper floors	1.25 mtrs		1.25 Mtr e	ach Provided	MR
	2. basements	1.25 mtrs		1.25 Mtr e	ach Provided	MR A
	c. Protection of exits					\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	1. Fire check door	Required		Provided		MR N/A
	2. Pressurization	N/A		N/A Two Provided		N/A MR
×	d. No. of continuous staircase t terrace	Required		9		* §
	e. Width of corridor	N/A		N/A		N/A N/A
	f. Door size	N/A		N/A		IN/A
3	Compartmentation.	-	1	Provided		MR
	1. Fire check door	Required		Provided		MR
	2. Sealing of electrical shafts	Required	(10)	Provided		MR
	3. Fire Rating of shaft door	N/A		N/A		N/A
	4. Water curtain	N/A		N/A		N/A
	5. Fire dampers	IN/A		1		
4	Smoke Management system.	30 a/c pe	er hour	Exhust Fa	an Provided	MR
	basement	12 a/c p				
	upper floors			Natural V	entinational	MR
5	Fire Extinguishers					
5	total numbers		8	12 Nos		MR
				Co2, Wa	ter Co2, ABC	MR
	Types					MR

)

6	First-Aid Hose Reels.	Required	One Provided	MR		
	total numbers on each floor	30 m	36 Mtr Provided	MR		
	Length of Hose reel hose	5 mm	Provided	MR		
	Nozzle Diameter Stim					
7	Automatic fire detection and alarmin	Required	Provided (Smoke)	MR		
	Type of Detectors	Required	Provided (Ground)	MR		
	location of Main Panel	N/A	N/A	N/A		
	location of Repeater panel	Required	Battary Backup	MR		
	Alternate source of power	Staircase	Provided	MR		
	hooter's location		Provided	MR		
8	MOEFA	Required N/A	Provided	MR		
9	Public Address System.	IN/A				
10	Automatic Sprinkler System.	Deguired	Provided	MR		
	basement	Required	Provided	MR		
	upper floors	Required	N/A	N/A		
	sprinkler above false ceiling	N/A	14// (
11	Internal Hydrants	150	Provided	MR		
	Size of riser/down-corner	150 mm	One Provided	MR		
	Number of Hydrants per floor	Required	One Porvided	MR		
	hose Box	One	OHE FORMACA	1000000		
12	Yard Hydrants.	D. i.d.	Provided (2 Nos)	MR		
	total number of hydrants	Required	Provided (2 Nos)	MR		
	hose box	Required	Flovided (2 Noc)			
13	Pumping arrangements		-			
	1. Ground level		2280 LPM Provided	MR		
	a. Discharge of main Pump	2280 LPM	60 Mtr Provided	MR		
	b.Head of main pump	60 Mtr	One Provided	MR		
	c.Number of main pumps	One	180 LPM Provided	MR		
	d.jockey pump out put	180 LPM	60 Mtr Provided	MR		
	e.jockey pump head	60 Mtr	2280 LPM Provided	MR		
	f. Standby Pump output	2280 LPM		MR		
	g.Stanby Pump head	60 Mtr	60 Mtr Provided	MR		
	h.Auto Starting/Manual stopping	Required	Provided (Both)	MR		
	pump house access	Required	Provided	IIVIT		
	2.Terrace level		least number of the	MR		
	a. Discharge of pump	900 LPM	900 LPM Provided	MR		
	b. head of the pump	40 mtr	40 Mtr Provided			
	c. Power supply	Required	Provided	MR		
	d. Auto starting of pump	Required	Provided	MR		
14	Captive water storage for fire figh	ting		IMP		
11	Underground tank capacity	75,000 ltr	75,000 Itr Provided	MR		
	a. Draw-off connection	Required	Provided	MR		
	b. fire service inlet	Required	Provided	MR		
	c.Access to tank	Required	Provided	MR		
	Over head tank Capacity	20,000 ltr	20,000 ltr Provided	MR		
15	Exit Signage.	Required	Provided	MR		
16						
17	a. Pressurization of lift shaft	N/A	N/A	N/A		
	b. pressurization of lift lobby	N/A	N/A	N/A		
	c. communication in lift car	N/A	N/A	N/A		
	d. Fireman's grounding switch	N/A	N/A	N/A		
		N/A	N/A	N/A		
	e. Lift signage Standby power supply	Required	Provided	MR		

18	Refuge Area.	Not Required			
	total area				
	location				
19	Fire control room				
	a. Detector system Panel	Required	Provided	MR	
	b. Flow switch Panel	N/A	N/A	N/A	
	c. PA system Panel	Required	Provided	MR	
	d. Batter backup	Required	Provided	MR	
	e. Building floor plans	N/A	N/A	N/A	
20	Special Fire Protection systems for protection of special risks, if any: No				

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010

Accordingly DFA is put up for your approval and signature please.

Signature of the inspecting officer

Name D. P. Bhardwaj

Designation : Divisional Officer (South)

Signature of the inspecting Officer

Name S.S. Kaushik

Designation ADO (SJ/BCP)