GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No. F6/DFS/MS/School/2013/ 75

Dated: 14/03/13

FIRE SAFETY CERTIFICATE

Issued on ----- at New Delhi by

CHIEF FIRE OFFICER DELHI FIRE SERVICE

%N

Copy To: -

- 1. The Directorate of Education, Govt. of NCTD, Old Secretariat, New Delhi.
- 2. The Principal, Govt. Girls Sr. Sec. School No-2, Molar Band, New Delhi

Conditions for the validity of Fire Safety Certificate

- a) All the Fire Safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- b) Building Sanctioning Authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d) The Basement shall be used strictly as per the provisions of Building Bye Lawse) The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

| 1. | Name & address of the building | : Gout. Gr : Molar Ra | inh Senier See and, New Dell | hi. 11 no 44 | hoof No. 2 |
|-----------|--|-------------------------------------|---------------------------------|---|-------------------|
| 2. | Type of Occupancy | : Edneski | mal | | |
| 3. | Type of Case | : New | | 8 | 2 |
| 4. | | : NiL | | Dt | |
| 5. | | : Dre of Edn eisentar Dt. 01/3/2011 | | | |
| 6. | Date of Inspection | 26-02-2013 | | | |
| 7. | Name of the Inspecting Officer | | | DO (| Couth |
| 8. | Name and designation of the | : Dhorampel Bhordway, Do (Couth) | | | |
| 0. | • | M. Git | ika, Te | ocher | |
| 9. | Year of Construction | 1998 | (Two Blocks , | Comprised of | Gd blus one L |
| | Applicant's letter No | : GGSSSI | (Two Blocks, No-2/MB du | r 26/2/21 | 013 |
| S. No. | Minimum Standards on Fire I and Fire Safety U/R 33 | | NBC Requirement | Provided at site | Remarks MR/NMR |
| 1 | Access to building | | | | |
| | Road width | 9 | Accessible | 9 mts | MR |
| | Gate width | | NA | 2 wtz | MR |
| | Width of internal road | | NA | NA | NA |
| 2 | Number, Width, Type & Arrai | | | 1 | |
| | Trained, Witch, Type Communication | igement of Lx | its | | |
| | Number of Staircase | igement of LA | | | |
| | | igement of Ex | 3+1 | 4+1 | MR |
| | Number of Staircase Upper floors Basement | igement of Ex | | 4+1 NA | MR |
| | Number of Staircase Upper floors Basement Width of Staircase | 8 | 3+1 NA | NA | NA |
| | Number of Staircase Upper floors Basement Width of Staircase Upper floors | 8 | 3+1 NA | NA 4-5/2-1-45 1-5/2-150 | NA MAS MR |
| | Number of Staircase Upper floors Basement Width of Staircase | 8 | 3+1 NA ach 1.50 Mts | NA | NA |
| | Number of Staircase Upper floors Basement Width of Staircase Upper floors Basement | 8 | 3+1 NA ach 1.50 Mts | NA 4.5/L - 1.45 1.5/L + 150 NA | NA MAS MR |
| | Number of Staircase Upper floors Basement Width of Staircase Upper floors Basement Protection of Exits | 8 | 3+1 NA ach 1.50 Mts | NA 4.5/L - 1.45 1.5/L + 150 NA | NA MAS MR |
| | Number of Staircase Upper floors Basement Width of Staircase Upper floors Basement Protection of Exits Upper floors | . & | 3+1 NA ach 1.50 Mts | NA 4.5/L - 1.45 1.5/L + 150 NA | NA MAS MR |
| | Number of Staircase Upper floors Basement Width of Staircase Upper floors Basement Protection of Exits Upper floors Basement | . & | 3+1 NA NA NA | NA 45/2-1.45 18/2-150 NA NA | NA NA NA |

| 3 | Compartmentation | | NA | |
|--|--|------------|---------|-----|
| | Fire check door | | 1 | |
| | Sealing of electrical shafts | | | |
| | Fire rating of shaft door | | | |
| | Water curtain | | | |
| Annual An | Fire Dampers | | | / |
| 4 | Smoke Management System | | NA | |
| | Basements | | | |
| | Upper Floors | | | |
| 5 | Fire Extinguishers | | | |
| | Total Number | On 1 300m2 | 8 Nos | NOR |
| | • Types | ABC / CO2 | ABL | MR |
| | IS marking | ISI mark | yes | MR |
| 6. | First-Aid Hose Reels | | NA | |
| | Total Number on each floor | /Per Floor | | / |
| | Length of hose reel hose | 30 m | | |
| | Nozzle diameter | 5mm | | |
| 7 | 7 Automatic Fire Detection and Alarming System | | NA | |
| | Type of detectors | / | | |
| | Location of Main Panel | | | |
| | Location of Repeater Panel | | | |
| | Alternate source of power | | / | / |
| Property of the Control of the Contr | Hooter's Location | | / | / |
| 8 | MOEFA | Required | Bovided | MR |
| 9 | Public Address System | NA | NA | NA |
| 10 | Automatic Sprinkler System | | NA | |
| | Basement | / | | / |
| | Upper Floor | | | |
| Andrew Transporter | Sprinkler above false ceiling | | | |
| 11 | Internal Hydrant | | NA | / |
| | Size of riser/down comer | | | / |
| | Number of hydrants per floor | | | |
| | Hose Box | | | // |
| | | | | |
| 12 | Yard Hydrant | | NA | |
| | Total Number of hydrants | | | |
| | Hose Box | | | |
| | | | | / |

| | Pumping Arrangements | | | |
|--|--|----|--|--|
| | Ground Level | NA | | |
| | Number of main pump | | | |
| die der versieren der versiere | Discharge of main pump | | | |
| and designed on the second of | Head of main pump | | | |
| | Jockey pump out put | | | |
| **** | Jockey pump Head | | | |
| | Standby pump out put | | | |
| | Standby Pump Head | | | |
| | Auto Starting/Manual stopping | | | |
| | Pump House Access | | | |
| | Terrace level | NA | | |
| | Discharge of pump | | | |
| | ➢ Head of the pump | | | |
| | Power Supply | | | |
| | Auto starting /Manual stopping | | | |
| 14 | Captive Water Storage for Fire Fighting | | | |
| | Underground tank capacity | | | |
| | Draw-off connection | | | |
| | Fire service inlet | | | |
| | Access to tank | | | |
| | Overhead tank capacity | | | |
| 15 | Exit Signage | NA | | |
| 16 | Provision of Lifts | NA | | |
| 4 | Pressurization of Lift Shaft | | | |
| į | Pressurization of Lift lobby | | | |
| | Communication in lift Car | | | |
| | Fireman's Grounding Switch | | | |
| | Lift Signage | | | |
| 17 | Standby Power Supply | NA | | |
| 18 | Refuge Area NA | | | |
| | Total Area | | | |
| | • Location | | | |
| 19 | Fire Control Room | NA | | |
| | Detector System Panel | | | |
| | Flow Switch Panel | | | |
| | PA System Panel | | | |
| | Battery back up | | | |
| | Building Floor Plans | | | |

N/4

Special Fire Protection System for Protection of special risk, if any

NA

NA

NA

The Fire protection systems provided in the building were test checked and found functional / non-functional at the time of inspection.

Keeping in view the substantial / insubstantial compliance of the minimum standards on fire prevention and fire safety required under the rules, It is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 / issue shortcomings as noted at serial Number....

Accordingly, DFA / FT letter is put up for perusal & approval please.

Signature of Inspecting Officer
Name: Dharampal Bharadwaj

Designation: DIV. OFFICER

Decto South