GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2013/ 8 3

Dated: 18/03/13

FIRE SAFETY CERTIFICATE

Certified that Gold Inn Guest House located at 4653/54, Gali Ram Prashad, Shora Kothi, Paharganj, New Dehli-55 comprised of ground floor (04 guest rooms), first floor (07 guest rooms) + Reception + office + lobby), second floor (07 guest rooms), third floor (07 guest rooms) & fourth floor (02 staff rooms + 01 store) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2010/900 dated 25-03-2010. The premises was re-inspected by the officer concerned of this department on 15-02-2013 in the presence of Mr. Alam, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 18/03/13 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 18/03/13 at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi w.r.t. your letter No.70103/Addl.C.P./Lic(H) dated 12-12-12.
- 2. The Manager, Gold Inn Guest House, 4653/54, Gali Ram Prashad, Shora Kothi, Paharganj, New Dehli-55.
- 3. Dy. Commissioner MCD, Sadar Paharganj zone, Idgah Road, Delhi.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Gold Inn, 4653/54, Gali Ram Prasad, Shora Kothi, Paharganj,

New Delhi

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F.6/DFS/MS/GH/2010/900

Dated: 25/03/2010

5. Fire Safety directives letter No

: N/A

6. Date of inspection

: 15.02.2013

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(HQ)

8. Name and designation of officers

from the building side

: Mr. Alam, Manager

9. Year of Construction

: 2007

70103/Addl C P/Lic(H)

dated 12/12/2012

10	Applicant's letter No. :70103/	Addl.C.P/Lic(H)	dated 12/12/2012				
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR			
	Access to building						
	Road width	PSS Area	3 mts	MR			
	 Gate width Width of internal road	PSS Area	Directly accessible from the road	MR			
	Width of internal road	N/A	N/A	N/A			
2	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases	-		_			
	Upper Floors	01	01	MR			
	Basements	N/A	N/A	N/A			
	b. Width of staircases	20	भी, ते शरी हैं।	9			
	Upper Floors	0.80 mt	1.25 mts	MR			
	Basements c. Protection of exits	N/A	N/A	N/A			
		N/A	N/A				
	Fire check door	N/A	N/A				
	Pressurization	N/A	N/A				
	e. No. of continuous staircases to terrace	01	01	MR			
	The state of the s	N/A	N/A				
	g. Width of Corridor	N/A	N/A				
	h. Door Size	N/A	N/A				
		14/11	- 11				



Mos 3 Compartmentation. Fire check door N/A N/A Sealing of electrical shafts N/A N/A Fire Rating of shaft door N/A N/A Water Curtain N/A N/A Fire Dampers N/A N/A 4 Smoke Management System. N/A N/A Basements 30 a/c per hour 12 a/c per hour Upper floors N/A N/A 5 Fire Extinguishers Total numbers 08 Provided MR Types Water CO₂, CO₂ Provided MR ISI marked IS marking Provided MR 6 First-Aid Hose Reels. 01 Total numbers on each floor Provided MR Length of hose reel hose 30 m Provided MR 5 mm Nozzle diameter Provided MR 7 Automatic fire detection and alarming system. N/A N/A Type of detectors N/A N/A Location of Main Panel Location of Repeater Panel N/A N/A Alternate source of power N/A N/A Hooters' Location N/A N/A ----8 Required Provided **MOEFA** MR 9 Public Address System. Required Provided MR Automatic Sprinkler System. 10

N/A

N/A

N/A

N/A

N/A

N/A

N/A

N/A

Basement

Internal Hydrants

11

Upper Floor

Sprinkler above false ceiling

Size of riser/down-comer

7

7		M6	9 1 8	a		
	Number of hydrants per floor	N/A	N/A			
	Hose Box	N/A	N/A			
12						
	• Total number of hydrants	N/A	N/A			
	Hose Box	N/A	N/A			
13	Pumping Arrangements.					
	Ground Level	N/A	N/A			
	Discharge of main Pump	N/A	N/A	Table Tabl		
	Head of Main pump	N/A	N/A			
	Number of main pumps	N/A	N/A			
	Jockey Pump out put	N/A	N/A			
	Jockey pump head	N/A	N/A	500 Std. 500 Std. 500 Std. 500 Std. 500 Std.		
	Standby Pump out put	N/A	N/A	~ ~ ~ ~ ~ ~ ~ ~ ~		
	Standby Pump Head	N/A	N/A			
	➤ Auto Starting/ Manual	N/A	N/A			
	stopping	N/A	N/A	AND AND THE SEC SEC SEC SEC SEC SEC SEC		
	Pump House AccessTerrace level	N/A	N/A			
	Discharge of pump	225 LPM	Provided	MR		
	➤ Head of the pump	30 mts	Provided	MR		
	Power SupplyAuto Starting of pump	Required	Provided	MR		
			Starting switch provided at ground floor	MR		
14	Captive Water Storage for fire fighting.					
	Underground tank capacity	N/A	N/A			
	Draw-off connection	N/A	N/A			
	Fire service inlet	N/A	N/A			
	Access to tankOverhead Tank capacity	N/A	N/A			
		2500 liters	Provided	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A			

		73		
	Pressurization of Lift lobby	N/A	N/A	
¥	Communication In lift Car	N/A	N/A	
	Fireman's Grounding Switch	N/A	N/A	
	Lift Signage	N/A	N/A	
17	Standby power supply	Required	Provided	MR
18	Refuge Area.			
	> Total Area	N/A	N/A	
	> Location	N/A	N/A	
19	Fire Control Room			
	Detector System Panel	N/A	N/A	
	• Flow Switch Panel	N/A	N/A	
	PA System Panel	N/A	N/A	
	Batter backup	N/A	N/A	
	Building Floor Plans	N/A	N/A	
20	Special Fire Protection Systems for	Required	One CO ₂ fire	MR
	Protection of special Risks, if any:		extinguisher provided	
			near elect. Panel.	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Forwarded please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation: - Asstt. Div. Officer (CC)