## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No F 6 / DFS / MS / 2013 / 8 /

Dated 15/03/13

## FIRE SAFETY CERTIFICATE

Issued 1.5/6.3/13 at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to:-

- The Executive Engineer (Bldg.)
   MCD, Building Department, Civic Centre, Minto Road, New Delhi.
- M/s Lally Automobiles Pvt. Ltd.
   D-160, Okhla Industrial Area Phase I, New Delhi

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be uses as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in



## **INSPECTION REPORT**

1. Name & address of the building: M/s Lally Automobile (P) Ltd. D-160, Okhla Industrial

Area, Ph-I, New Delhi -110020.

2. Type of Occupancy

: Industrial

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/2006/3394 Dated 17.11.2006

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/2006/762 Dated 28.06.2006

6. Date of inspection

: 02.03.2013

7. Name of the Inspecting Officer: Dy. CFO Atul Garg

8. Name and designation of Officer

from the building side

Mr. Deepak Kapoor (DGM/ Sales)

9. Year of Construction

: 2006 (Basement+ Ground floor)

10. Applicant's letter No.: Nil dated 04.02.13

S	Minimum standards on fire	BBL	Provided at	Remarks MR/NMR
No	prevention and fire safety U/R 33	Requirements	site	a 8
1.	Access of building	and the second s		
	Road width	09 mtr	13.71 mtr.	MR
	<ul> <li>Gate width</li> </ul>	4.5 m	5 m	MR
	<ul> <li>Width of internal road</li> </ul>	N/A	N/A	N/A
2.	Number, width, Type & Arrangements of exits			
	a. Number of staircases			
	Upper floors	02	02	MR
	Basements	02	02	MR
	b. Width of staircases			
	Upper floors	N/A	1.30 M	MR (old case)
	Basements	COLUMN TOUR TOUR TOUR TOUR TOUR TOUR TOUR	1.46 m	MR (old case)
		1	1. 20 m	
	c. Protection of exits			
	Fire check door	Required	Provided	MR
=	<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A

ATUL SARS

11/5

	d. No of continuous staircase	02	100		9 e
	to terrace	02	02		MR
-	e. Width Of Corridor	N/A	N/A		77/4
	f. Door Size	1 m	1.25 m		N/A
3.	Compartmentation		1.23 III		MR
	<ul> <li>Fire check door</li> </ul>	N/A	N/A		N/A
	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A		N/A
	<ul> <li>Fire Rating of shaft door</li> </ul>	N/A	N/A		N/A
	Water Curtain	N/A	N/A		N/A
	Fire Dampers	N/A	N/A	:	N/A
4.	Smoke managements System				1771
	Basements	Required	Provided		MD
	<ul> <li>Upper floors</li> </ul>	N/A	N/A		MR N/A
5.	Fire Extinguishers		IVA		N/A
2	Total numbers	10	Provided		100
	<ul> <li>Types</li> </ul>	ABC/ CO <sub>2</sub>	Provided		MR
	IS marking	120,002	Provided		MR
		ISI marked	YES	and the state of t	MD
6.	First – Aid Hose Reels		TLS		MR
	<ul> <li>Total numbers on each floor</li> </ul>	01	Provided		MR
	<ul> <li>Length of hose reel hose</li> </ul>	30 mtr	Provided		MR
	Nozzle diameter	5 mm	Provided		MR
7.	Automatic fire detection and alarmi	ng system			
	Type of detectors	YES	Smoke/Heat	MR	
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/A	
	<ul> <li>Location of Repeater</li> </ul>	N/A	N/A	N/A	V A
	Panel	TIEC			8 22
	<ul><li>Alternate source of power</li><li>Hooters' Location</li></ul>	YES	Provided	MR	
		Public Area	Public Area	MR	
8.	MOEFA	Not Required	Provided	MR	
9.	Public Address System/Intercom	Not Required	Provided	MR	
10.	Automatic Sprinkler System				
	Basements	D 1	1-		
		Required N/A	Provided	MR	
		N/A N/A	Provided	MR	
	ceiling	11/11	N/A	N/A	

Alukor

11.	Internal Hydrants				
	Size of riser/down- comer	100 mm	100 mm	MR	
	<ul> <li>Number of hydrants per</li> </ul>	01	01	MR	
	floor				
	<ul> <li>Hose Box</li> </ul>	01	01	MR	
12.	Yard Hydrants				
	Total number of hydrants	Not required	01	MR	
	Hose Box	Not required	01	MR	
13.	Pumping Arrangements				
	Ground Level				
	Discharge of main pump	900 LPM	900 LPM	MR	
	Head of main pump	40 m	40 m	MR	
	Number of main pumps	01	01	MR	
	Jockey pump out put	180 LPM	180 LPM	MR	
	Jockey pump head	40 m	40 m	MR	
	Standby Pump out put	N/A	N/A	N/A	
	Standby Pump Head	N/A	N/A	N/A	
	Auto Staring/Manual	YES	Provided	MR	
	stopping		11011404	1711	
	Pump House Access	YES	YES	MR	
	Terrace level				
	Discharge of pump	N/A	N/A	N/A	
	Head of the pump	N/A	N/A	N/A	
	Power supply	N/A	N/A	N/A	
	Auto starting of pump	N/A	N/A	N/A	
14.	Captive water Storage for fire fighting				
		T = 7/2	1571		
¥	<ul> <li>Under ground tank capacity</li> </ul>	N/A	N/A	N/A	
	Draw of connection	YES	Provided	MR	
	Fire service inlet	YES	Provided	MR	
	> Access to tank	N/A	Provided	MR	
	<ul> <li>Overhead Tank capacity</li> </ul>	10,000 ltr	10,000 ltr	MR	
15	Exit Signage	Required	Provided	MR	
10	9"	redanoa	Tiovided		
16.	Provision of Lifts				
	Pressurization of Lift Shaft	t N/A	N/A	N/A	
	<ul> <li>Pressurization of Lift Share</li> <li>Pressurization of lift lobby</li> </ul>		N/A	N/A	
	Communication in lift Car		N/A	N/A	
	<ul><li>Fireman's Grounding</li></ul>	N/A	N/A	N/A	
	- I II CIII D OI CAIIGIII S	1 1 1/1 1	T 4/ 7 F	1 1 1/1 1	

Alutay

	➤ Lift Signage	N/A	N/A	N/A
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area			
	> Total area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19.	Fire control room	3		
	> Detector system panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	> PA System Panel	N/A	N/A	N/A
	> Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20.	Special Fire Protection Systems	N/A	N/A	N/A
	for Protection of special Risks, if	*		
	any;			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010

Signature of the Inspecting Officer

Name

Signature of the Inspecting Officer

Name

Designa

ATULGARG D(FO/South

Designation