GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2013/ L96

FIRE SAFETY CERTIFICATE

Issued on 18/4/13 at New Delhi by.

Chief Fire Officer Delhi fire service

Dated: 18/4/13

Copy to: -

- 1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Pelhi w.r.t. letter No 4116/Addl.C.P./Lic(H) dated 24.01.2013.
- 2. The Manager, Gharib Nawaj guest house, 966, Bazar Matia Mahal, Jama Masjid, Delhi-110006.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1.	Name & address of the building: <u><u></u> <u><u></u> <u><u></u> <u><u></u> <u></u> <u><u></u> <u> <u></u> <u> </u> <u> <u></u> <u> </u> <u> </u></u></u></u></u></u></u></u>	Nawaj Guest	House, 966, 100300	Malea Mahal,	
2.	1. Name & address of the building: Garib Navaj Guest House, 966, Bazar Mahal 2. Type of Occupancy : Lodging House / Eating House / Club Jama Mayid, Della.				
3.		al / New case			
4	Details of previous NOC: Letter No. F6/DFs/Ns/G4/2010/1103 Dated: 19/4/2010				
5	5. Fire Safety directives letter No :				
6	6. Date of inspection : 11 03 2013				
7	7. Name of the Inspecting Officers: M.K. Chattopadhyay, ADO(CC)				
8	. Name and designation of officers		0 0		
	from the building side : $\underline{\mathcal{M}}$	r. Shahid,	Manager.		
9	. Year of Construction :	1998	U		
1(). Applicant's letter No. : UII	6/ Addl.C.P	uc (H) daled	24/1/2013	
S.	Minimum Standards on fire	NBC	Provided at site	Remarks	
No.	prevention and fire safety U/R 33	Requirement		MR/NMR	
1	Access to building				
	Road width	Spl. area	More than 6m/r	MR	
	• Gate width	-	proceedly accessible	MR	
	 Width of internal road 	N/A	N/A	MA	
2	Number, Width, Type & Arrangement	of Exits			
	a. Number of staircases	-	-	•	
	• Upper Floors	D1:	01	A	
	o opper ricors	01		MR	
	Basements	W/A	17/A	MR N/A	
	• Basements				
	Basements b. Width of staircases	W/4	H7/A	N/A	
	Basementsb. Width of staircasesUpper Floors	N/4	1.0 mt	N/A - MR	
	Basementsb. Width of staircasesUpper FloorsBasements	N/A - 0.80 mt H/A	1.0 mt	N/A - MR	
	 Basements Width of staircases Upper Floors Basements c. Protection of exits 	0.80 mt H/A N/A	1.0 mt 1.0 mt N/A	N/A - MR	
	 Basements Width of staircases Upper Floors Basements Protection of exits Fire check door 	0.80 mt H/A N/A N/A	1.0 mt 1.0 mt N/A N/A	N/A - MR	
	 Basements Width of staircases Upper Floors Basements Protection of exits Fire check door Pressurization 	N/A O. 80 mt H/A N/A N/A N/A	1.0 ml 1.0 ml 1.0 ml N/A N/A N/A	N/A MR N/A	
	 Basements Width of staircases Upper Floors Basements Protection of exits Fire check door Pressurization No. of continuous staircases to terrace 	N/A O. 80 mt H/A N/A N/A N/A O1	1.0 m h 1.0 m h N/A N/A N/A N/A OI	N/A MR N/A	
	 Basements Width of staircases Upper Floors Basements Protection of exits Fire check door Pressurization No. of continuous staircases to terrace g. Width of Corridor 	N/A O. 80 mt N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A N/A	N/A MR N/A	
3	 Basements Width of staircases Upper Floors Basements Protection of exits Fire check door Pressurization No. of continuous staircases to terrace g. Width of Corridor 	N/A O. 80 mt N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A N/A	N/A MR N/A	

do

	 Sealing of electrical shafts 	N/A	N/A	NO. AND NOT THE THE THE THE THE THE		
	 Fire Rating of shaft door 	N/A	N/A			
	Water Curtain	N/A	N/A			
	• Fire Dampers	N/A	N/A			
	Smoke Management System.					
	Basements	30 a/c per hour	N/A	N /.		
	 Upper floors 	12 a/c per hour	14/4	11/4		
			W/A	H/A		
	Fire Extinguishers					
	• Total numbers	20	Provided	MR		
	• Types	ABC, Halis CO, CO,	provided	MR		
	IS marking	ISI marked	provided	MR		
	First-Aid Hose Reels.					
	 Total numbers on each floor 	01	privided	MR		
	 Length of hose reel hose 	30 m	provided	MR		
	Nozzle diameter	5 mm	provided	MR		
	Automatic fire detection and alarming system.					
	Type of detectors	N/A	N/A			
	 Location of Main Panel 	N/A	N/A			
	 Location of Repeater Panel 	N/A	N/A			
	• Alternate source of power	N/A	N/A			
	Hooters' Location	N/A	N/A			
	MOEFA	N/A	N/A	N/A		
	Public Address System.	W/A	W/A	NJA		
	Automatic Sprinkler System.					
	• Basement	N/A	NT/A	W/.		
	 Upper Floor 		W/A	W/A		
The second secon	 Sprinkler above false ceiling 	N/A	N/A			
	O .	N/A	N/A			
	Internal Hydrants					
	 Size of riser/down-comer 	N/A	N/A	NA		
-	Number of hydrants per floor	H/A	N/A	MA		
	 Hose Box 	MA				

12	Yard Hydrants.			-
	Total number of hydrants	N/A	N/A	
	Hose Box	N/A	N/A	
13	Pumping Arrangements.	11/21	IN/A	
	Ground Level	N/A	N/A	
	Discharge of main Pump	N/A	N/A	
	Head of Main pump	N/A	N/A	
	Number of main pumps	N/A	N/A	
	Jockey Pump out put	N/A		
	Jockey pump head		N/A	
	Standby Pump out put	N/A	N/A	
	Standby Pump Head	N/A	N/A	
	Auto Starting/ Manual	N/A	N/A	
-	stopping	N/A	N/A	
	> Pump House Access	N/A	N/A	
1	• Terrace level	N/A	N/A	
	Discharge of pump	225 LPM	provida	MR
	Head of the pump	25 mt	provided	MR
	Power Supply	Required	provided	MR
	Auto Starting of pump	Required	provide	MR
4	Captive Water Storage for fire fightin	g.		,
	 Underground tank capacity 	N/A	N/A	
	Draw-off connection	N/A	N/A	
	Fire service inlet	N/A	N/A	
	Access to tank	N/A	N/A	
	 Overhead Tank capacity 	2500 lbs	provided	MR
5	Exit Signage.	Required	Provided	MR
6	Provision of Lifts.			
	 Pressurization of Lift Shaft 	N/A	N/A	
	 Pressurization of Lift lobby 	N/A	N/A	
	• Communication In lift Car	N/A	N/A	



	Lift Signage	N/A	N/A		
17	Standby power supply	Required	SKVA	MR	
18	8 Refuge Area.				
	> Total Area	N/A	N/A		
	Location	N/A	N/A		
19 Fire Control Room					
	Detector System Panel	N/A	N/A		
	• Flow Switch Panel	N/A	N/A		
	 PA System Panel 	N/A	N/A	NO 40 MI NO 40 MI NO 40 MI NO 40 MI	
	Batter backup	N/A	N/A		
	Building Floor Plans	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	provided of ABC lype fui extensionshir near Electional	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to Agrant / renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

DOCCO) Forwarded pl. 13.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation :- Asstt. Div. Officer (HQ)