FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[SEE SUB-RULE (1) OF RULE 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS las/ School /2013/134

Dated: 01 / 04 /2013

FIRE SAFETY CERTIFICATE

Certified that the Guru Angad Public School located at Gurdwara Complex, Ashok Vihar, Phase-I, Delhi-110052, is comprised of ground plus three upper floors only, occupied by Guru Angad Public School, was issued NOC vide this office letter No. F6/DFS/MS/2009/205 dated 23/01/2009. The premises was re-inspected by the officer concerned of this department on 15/02/2012 and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have therefore, deemed complied with the fire prevention and fire safety requirements in accordance with the Delhi Fire Service Act 2007 Rule 2010 and the building /premises is it for occupancy Class-B (Educational) with effect from sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rule, 2010.

Issued on ollow J13 at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy to:

Sh. P.S. Kholi (Manager)
 Guru Angad Public School located at Gurdwara Complex, Ashok Vihar, Phase-I, Delhi-110052

2. The Director of Education, Old Secretariat, Delhi

Ou

Note: For general fire safety directives please over leaf.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provision of building bye laws.
- 6. This certificate cannot be treated in any case for regularizations of unauthorized construction
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**

May kindly peruse letter no. 6649 dated 04.10.12 received from Sh. P.S. Kholi (Manager) for Guru Angad Public School located at Gurdwara Complex, Ashok Vihar, Phase-I, Delhi-110052, regarding issue renewal of NOC from fire and safety point of view. The premises was inspected by the undersigned on dated 15.10.12 & observed that the school building is comprised of ground plus three upper floors only. However following fire safety measures are put up on the prescribe Performa:

1. Name & address of the building

Guru Angad Public School located at Gurdwara Complex, Ashok

Vihar, Phase-I, Delhi-110052.

2. Type of Occupancy

: Class -B (Educational)

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/2009/205 dated 23/01/2009 V

5. Fire Safety directives letter No.

: N.A.

6. Date of inspection

: 15/02/2013

7. Name of the Inspecting Officers

: D.O. Sunil Chawdhary

8. Name and designation of officers

From the building side

: P.S. Kholi (Manager)

9. Year of Construction

2003

10. Applicant's letter No.

6649 dated 04.10.12

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR
1.	Access to building	1		
	Road width	06 mtrs	12 mtr	Old case M/R
	Gate width	Old case	Old case /	Old case
	Width of internal road	N.R.	N.R.	N.R.
2.	Number, Width, Type & Arrange	ement of Exits		4
	a. Number of staircases	2		
	Upper Floors	02	02	M/R

	Basement	N.A	N.A.	N.A
	b. Width of staircases			
	Upper Floors	Old case	1 staircase 120 cm second is 1 mtr	M/R
	• Basement	N.A	N.A.	N.A.
	c. Protection of exits			
	 Fire check door 	N/R	N/P	N.R.
	 Pressurization 	N/R	N/R	N.R.
	d. No. of continuous staircases to terrace	2	2	M.R.
	e. Width of Corridor	Old case	Old case	Old case M.R.
	f. Door size	Old case	1 mtr appr.	M.R.
3.	Compartmentation.			
	Fire check door	N/R	N/R	N/R
	Sealing of electrical shafts	N/R	N/R	N/R
	Fire Rating of shaft door	N/R	N/R	N/R
	Water Curtain	N/R	N/R	N/R
	Fire Dampers	N/R	1	N/R
4.	Smoke Management System.	N/K	N/R	IVIX
	Basements	N/R	N/R	N/R
	Upper floors	N/R	N/R	N/R
5.	Fire Extinguishers	Required	Provided	MR
	Total numbers	10 nos.	12	M/R
	• Types	ISI marked ABC & CO ² type	provided	M/R
	IS marking	Yes	provided	M/R



6.	First-Aid Hose Rees.	N (see		11.
	Total numbers on each floor	Required	provided	M/R
	Length of hose reel hose	30 m required	provided	M/R
	Nozzle diameter	5 mm required	Provided	M/R
7.	Automatic fire detection and alar	ming system.		
	Type of detectors	N/R	N/R	N/R
	Location of Main Panel	N/R	N/R	N/R
	Location of Repeater Panel	N/R	N/R	N/R
	Alternate source of power	N/R	N/R	N/R
	Hooter's Location	N/R	N/R	N/R
8.	MOEFA	N/R	N/R	N/R
9.	Public Address System.	Required	Provided	M/R
10.	Automatic Sprinkler system		3 \$ 1 3 H C	
A market and a mar	Basement	N.A.	N.A.	N.A.
	Upper Floor	N/R	N/R	N/R
	Sprinkler above false ceiling	No false ceiling	N/R	N/R
11.	Internal Hydrants			I.
	Size of riser/down-comer	4 "	Provided	M/R
	Number of hydrants per floor	One at each floor	Provided	M/R
	Hose Box	required	Provided	M/R
12.	Yard Hydrants.	N/R	N/R	N/R

	3	N Company of the Comp		
	Total number of hydrants	N/R	N/R	N/R
	Hose Box	N/R	N/R	N/R
3. F	Pumping Arrangements.			
0	Ground Level			
	> Discharge of main pump	N/R	N/R	N/R
	➤ Head of Main pump	N/R	N/R	N/R
	➤ Number of main pumps	N/R	N/R	N/R
	> Jockey Pump out put	N/R	N/R	N/R
2 1	> Jockey pump head	N/R	N/R	N/R
	> Standby pump out put	N/R	N/R	N/R
	> Standby pump Head	N/R	N/R	N/R
	> Auto Starting/Manual stopping	N/R	N/R	N/R
	> Pump Hose Access	N/R	N/R	N/R
T	errace level			
	> Discharge of pump	450 & 220 LPM	Provided	M/R
	➤ Head of the pump	40 mtr	Provided	M/R
	> Power supply	Required	Provided	M.R.
	➤ Auto Starting of pump	N/R	N.R.	N.R.
· C	aptive Water Storage for fire ghting.			
U	nderground tank capacity	,		
	> Draw -off connection	N/R	N/R	N/R
	Fire service inlet	N/R	N/R	N/R
	> Access to tank	N/R	N/R	N/R

	Oryanhand Tarah Carania	W 000 1		
	Overhead Tank Capacity	5,000 ltrs	5,000 ltrs	M.R.
15	Exit Signage.	Required	Provided	M/R
16.	Provision of Lifts			
	Pressurization of Lift Shaft	N/R	N/R	N/R
	Pressurization of Lift lobby	N/R	N/R	N/R
	Communication In lift Car	N/R	N/R	N/R
	• Fireman's Grounding Switch	N/R	N/R	N/R
	Lift Signage	N/R	N/R	N/R
17.	Standby power supply			£ ,
18.	Refuge Area			
	Total Area	N/R	N/R	N/R
	> Location	N/R	N/R	N/R
19.	Fire Control Room		N - 1)
	> Detector System Panel	N/R	N/R	N/R
	Flow Switch Panel	N/R	N/R	N/R
	> PA system Panel	N/R	N/R	N/R
	Batter backup	N/R	N/R	N/R
	Building Floor plans	N/R	N/R	N/R
20.	Special Fire Protection Systems for Protection of special Risks, if any:	N/R	N/R	N/R

The fire protection systems provided in the building were test checked and found functional at the time of is spection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Sunil Chowdhary

Name

Designation D.O. (M.N.)

Designation