GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO. F6/DFS/MS/Cinema/2013/1578

Dated: 09/04/13

FIRE SAFETY CERTIFICATE

Issued on _08/04//3_at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

2. The Manager, Moti Cinema, Chandni Chowk, Delhi-110006.

Conditions for the validity of fire safety certificate

a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.

b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.

c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Moti Cinema, Chandni Chowk, Delhi-6.

2. Type of Occupancy

: Assembly

3. Type of Case

:Renewal

4. Details of previous NOC

: Letter No. F.6/DFS/MS/Cinema/2011/1292 dated 22-06-2011

5. Fire Safety directives letter No : N/A

6. Date of inspection

: 18/03/2013

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(CC), Sanjay Kr. Tomer, STO

8. Name and designation of officers

from the building side

: Mr. V.K.Garg, Manager

9. Year of Construction

:1978-79

10. Applicant's letter No.

:12034-37/Addl.CP/Lic(Cinema), dated 12/03/2013

10. Applicant's letter No. :12034-3//Addl.CP/Lic(Cinema), dated 12/03/2013						
S.	Minimum Standards on fire	NBC	Provided at site	Remarks		
No.	prevention and fire safety U/R 33	Requirement	r	MR/NMR		
1	Access to building					
	Road width	6 mts	More than 06 mts	MR		
	Gate width		Directly accessible	MR		
			from the road.			
	 Width of internal road 	N/A	N/A	N/A		
2 Number, Width, Type & Arrangement of Exits						
	a. Number of staircases					
	• Upper Floors	02	03	MR		
	• Basements	N/A	N/A	N/A		
	b. Width of staircases					
	• Upper Floors	1.25 mts	2.0, 1.5, 0.78 mts	MR		
	• Basements	N/A	N/A	N/A		
	c. Protection of exits	N/A	N/A	N/A		
	• Fire check door	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	e. No. of continuous staircases to terrace	01	01	MR		
	g. Width of Corridor	1.5 mts	2.0 mts	MR		
	h. Door Size	1.5 mts (08	Provided	MR		
		+04) Nos)				



3	Compartmentation.	N/A	N/A	N/A		
	Fire check door	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	 Fire Rating of shaft door 	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	• Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basements	30 a/c per hour	N/A	N/A		
	Upper floors	12 a/c per hour	Provided Exhaust fans	MR		
5	Fire Extinguishers					
	Total numbers	14	Provided	MR		
	• Types	WCO ₂ , CO ₂ , Foam type	Provided	MR		
	IS marking	Required	Provided	MR		
6	First-Aid Hose Reels.			* n		
	Total numbers on each floor	02 nos.	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
8.	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	N/A	N/A	N/A		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	N/A	N/A	N/A		
	• Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	Required	Provided at GF	MR		



	Number of hydrants per floorHose Box	01 at ground floor	Provided	MR		
		01	Provided	MR		
12	Yard Hydrants.					
	 Total number of hydrants 	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	N/A	N/A	N/A		
	Head of Main pump	N/A	N/A	N/A		
59	Number of main pumps	N/A	N/A	N/A		
	Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	Standby Pump Head	N/A	N/A	N/A		
	Auto Starting/ Manual	N/A	N/A	N/A		
	stopping	N/A	N/A	N/A		
	Pump House Access	1771	14/11			
	Terrace level	450 7 77 6				
	Discharge of pump	450 LPM	Provided	MR		
	Head of the pump	40 mts.	Provided	MR		
	Power Supply	Required	Provided	MR		
	➤ Auto Starting of pump	Required	Provided	MR		
14	Captive Water Storage for fire fighting	g.				
	Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
	Fire service inlet	N/A	N/A	N/A		
	Access to tank	Required	Provided	MR		
	Overhead Tank capacity	16,000 lts	Provided	MR		
15	Exit Signage.	Required	Provided	MR		
16	6 Provision of Lifts.					
9	Pressurization of Lift Shaft	N/A	N/A	N/A		



	T				
	Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car	N/A	N/A	N/A	
	Fireman's Grounding Switch	N/A	N/A	N/A	
	Lift Signage	N/A	N/A	N/A	
17	Standby power supply	Required	Provided	MR	
18	Refuge Area.			2	
	> Total Area	N/A	N/A	N/A	
	> Location	N/A	N/A	N/A	
19	Fire Control Room				
	Detector System Panel	N/A	N/A	N/A	
	Flow Switch Panel	N/A	N/A	N/A	
	PA System Panel	N/A	N/A	N/A	
	Batter backup	N/A	N/A	N/A	
	Building Floor Plans	N/A	N/A	N/A	
20	Special Fire Protection Systems for	Required	01 CO ₂ type fire	MR	
	Protection of special Risks, if any:		extinguisher found		
		8	provided near elect.		
			panel		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010. DO(CD) Frewerder pl'

Doson fores production

Asstt. Div. Officer